



**Wipaire Worldwide  
Anywhere, Anytime**

SERVICE LETTER: 39

DATE: October 23, 1997

TITLE: Conversion of 3730 Floats to 3800 Floats.

EFFECTIVELY: STC SA7GL (Models A185F, 185A)  
STC SA18GL (Models 206, U206, A, B, C, D, E, F, G,  
TU206A, B, C, D, F, E, G, P206, P206A, TP206A,)

REASON: To convert Amphibian to Seaplane Floats.

CONVERSION INFORMATION:

To convert 3730 Amphibian Floats to 3800 Seaplane floats.

1. Remove the Main and Nose Gear from the floats. Cover and seal the holes in the nose and step bulkheads. Water check float compartments for leaks. It is not necessary to cover main gear wheel well.

2. Optional - remove all hydraulic equipment concerned with the float landing gear (hydraulic hoses, switches, handpump, powerpack, elec. wiring, fittings, etc).

3. Weight and Balance Data; 3800 float Wt & Arm.

(Note adjust weight for items removed, if complete gear and hydraulic removal is not done)

a) Ref: STC SA7GL  
502 lbs @ 49.5 Aft of Datum

b) Ref: STC SA18GL  
502 lbs @ 49.0 Aft of Datum

METHOD OF COMPLIANCE: Work to be per AC 43.13-1A

SHOP HOURS REQUIRED: 8 to 20 hrs

WARRANTY: Parts and Labor for 18 months past the issuance of this service letter.