



Aircraft Hardware

Wipaire Parts Sales Team:

1.888.947.2473

WIPLINE FLOATS - SKIS - MODIFICATIONS

Direct: 1.888.947.2473 | Fax: 651.451.1786 | www.wipaire.com
1700 Henry Avenue South - Fleming Field (KSGS) South St. Paul, MN 55075

| Part Number | Part Description | Unit of Measure |
|---------------|--|-----------------|
| 010-009 | Grease Retainer, 2" DIA | EA |
| 015-002 | Wheel Half, Inner | EA |
| 016-002 | Wheel Half, Outer | EA |
| 01692-0410 | Rivet, Pop, 1/8" DIA, 0.031-0.187 Grip, Large Flange | EA |
| 01692-0410 | Rivet, Pop, 1/8" DIA, 0.031-0.187 Grip, Large Flange | EA |
| 01692-0410 | Rivet, Pop, 1/8" DIA, 0.031-0.187 Grip, Large Flange | EA |
| 01692-0414 | Rivet, Pop, 1/8" DIA, 0.125-0.312 Grip, Large Flange | EA |
| 018-001 | Brake Disc, Black Steel, 3-1/8" DIA, 3 Mounting Holes, 1.6lbs. | EA |
| 018-002 | Brake Disc, Black Steel, 3-1/8" DIA, 3 Mounting Holes, 2.2lbs. | EA |
| 020-001 | Torque Plate Assembly | EA |
| 0310196-4 | Spring | EA |
| 0310280 | Spring | EA |
| 03DU03 | Bushing, Garlock, 3/16 DIA | EA |
| 03DU04 | Bushing, Garlock, 3/16" DIA, 1/4" Length | EA |
| 0405064-1 | Placard Nameplate, "Cessna", Black Letters | EA |
| 0411686 | Clip | EA |
| 0411957-1 | Spacer, 1/4" DIA | EA |
| 0413163-58 | Seal, 2" DIA, Felt | EA |
| 0417016-1 | Spring, 1/4" Width, Cessna | EA |
| 0417016-2 | Spring, 1/4" Width, Cessna | EA |
| 0426013-1 | Gasket, 2-3/4" DIA, Cork | EA |
| 0450039-2-294 | Spacer, 3-3/8" DIA, White | EA |
| 0450211-1 | Spring & Fastener, Baffle, 3-1/4" Long Detachable Hook w/ 1/4" Spring | EA |
| 0450211-2 | Spring & Fastener, Baffle, 5-1/2" Long Detachable Hook w/ 1/2" Spring | EA |
| 0450277-11 | Spring, 1/2" Width, 1-1/4" Length, Used in 0450277 Fastener Baffles | EA |
| 0450277-206 | Spring & Fastener, Baffle, 7" Long Detachable Hook w/ 1/2" Spring | EA |
| 0450277-208 | Spring & Fastener, Baffle, 11-1/4" Long Detachable Hook w/ 1/2" Spring | EA |
| 0453003-2 | Bracket, Cowl Mount | EA |
| 0453003-3 | Bracket, Cowl Mount, 11/16" DIA | EA |
| 0453003-7 | Cowl Mount Supports, Bracket, 11/16" DIA | EA |
| 0505103-1 | Emblem, "Cessna", Sticker | EA |
| 05-05194 | Hole Plug | EA |
| 0513125 | Gasket | EA |
| 0513208-1 | Socket | EA |
| 0513561-3 | Retainer | EA |
| 0518031-1 | Reducer, 5/8" To 3/8" | EA |
| 0523115-3 | Retainer, 6 Holes, Ridge | EA |
| 0523218-2 | Bolt Rod, 1/4-28 Thread Screw Ends, 4-1/4" Grip | EA |
| 0523532 | Gasket | EA |
| 0523816-2 | Pin, w/ hook 9" Length, Used for 0523826-1 Assembly | EA |
| 0541115-2 | Spacer, 5/16" DIA | EA |
| 0541115-3 | Bolt, Eye, Lifting Ring, 7/8" DIA Ring, 1/4-28 Screw End, 2-1/4" Grip | EA |
| 0541126 | Spacer | EA |
| 0541148-1 | Spring, 5/16" Width, 3/8" Length | EA |
| 0541173-1 | Spring, Brake, 1/4" Width, 7/8" Spring Length, 2 End Loops | EA |
| 0541202-4 | Bushing Assembly Main Gear, 2" DIA | EA |
| 0543023 | Clevis | EA |
| 0550154-2 | Pad, 5/8" DIA, Black Rubber | EA |
| 05-50496 | Plug, Hole | EA |
| 05-50857 | Plug | EA |
| 05-51247 | Plug, Hole | EA |
| 05-51576 | Plug, Hole | EA |
| 0552010-42 | Hinge Pin, 8" Length | EA |

| Part Number | Part Description | Unit of Measure |
|------------------|---|-----------------|
| 05-52668 | Plug, Hole | EA |
| 058433 | Switch, Pressure (OBSOLETE engine driven pump) | EA |
| 069-03100 | Bolt, Anchor, Brake Pin, w/ Screw 1/4", Length 2-5/8" | EA |
| 06B23072 | Gasket | EA |
| 0700623-11 | Socket Assembly | EA |
| 0700623-12 | Socket Assembly | EA |
| 0701-153 | Adapter, Nylon 1/4" Tube x 1/8" Pipe | EA |
| 0701-162 | Adapter, Nylon 3/8" Tube X 1/4" Pipe | EA |
| 0706-005 | Connector, Nylon 1/8" Tube x 1/8" Tube | EA |
| 0706-015 | Connector, Nylon 1/4" Tube x 1/4" Tube | EA |
| 0706-020 | Connector, Nylon 3/8" Tube x 3/8" Tube | EA |
| 0711001-29 | Spring, 1/2" Width, 1-7/8" Length, 2 Extended End Hooks | EA |
| 0711-153 | Elbow, Nylon 1/4" Tube x 1/8" Pipe | EA |
| 0711788-1 | Spring, 1/4" Width, 7/8" Length, 2 End Hooks - 1 is Extended Length | EA |
| 0713018-3 | Seal, Gear Leg '185' | EA |
| 0713124-1 | Spring, 1-3/8" Length, 1/2" Width, Black | EA |
| 0713625-1 | Spring, 1/2" Width, 2-1/4" Length, 2 End Hooks - 1 is Extended Length | EA |
| 0716-005 | Tee, Nylon 1/8" Tube x 1/8" Tube x 1/8" Tube | EA |
| 0716-011 | Tee, Nylon 3/16" Tue x 3/16" Tube x 3/16" Tube | EA |
| 0716-011 | Tee, Nylon 3/16" Tue x 3/16" Tube x 3/16" Tube | EA |
| 0716-015 | Tee, Nylon 1/4" Tube x 1/4" Tube x 1/4" Tube | EA |
| 0716-015 | Tee, Nylon 1/4" Tube x 1/4" Tube x 1/4" Tube | EA |
| 0717026-1 | Spring, 1/4" Width, 1" Length, 2 End Hooks | EA |
| 0733118-2 | Clip, LH, Stop | EA |
| 0742200-5 | Spring, 1-3/8" Width, 2-1/2" Length, 2 End hooks | EA |
| 0742410-8 | Ferrule | EA |
| 0750031-1 | Strap. Ground, 11/16" DIA & 3/8" DIA | EA |
| 075-00800 | Torque Plate Assembly, Black & Silver Metal, USED TO MAKE 3A04711-001/002 | EA |
| 0750175-1 | Gasket, Cork, 3" DIA | EA |
| 0750225-1 | Clamp, 3-1/2" | EA |
| 075-04200 | Torque Plate, 1-3/4" DIA, LENGTH 6-1/2" | EA |
| 075-04200 | Torque Plate, 1-3/4" DIA, LENGTH 6-1/2" | EA |
| 0751006-3 | Lug, 3/8" DIA | EA |
| 0752016-11 | Gasket Seal, Black Foam Strip, 3-7/8" length | EA |
| 0752037-1 | Elbow, 3/8-24 to 7/16-20, 45 Deg | EA |
| 0752037-3 | Elbow, 3/8-24 to 5/16-32, 45 Deg | EA |
| 0752609-27 | Pin, Hinge, 5-1/2" Length, w/ Open End Hook | EA |
| 075-30107-1 | Torque Plate Assembly, 3-3/8", MADE INTO 30A05748-001-LEFT | EA |
| 075-30107-2 | Torque Plate Assembly, 3-3/8", MADE INTO 30A05748-002-RIGHT | EA |
| 0760679-2 | Bushing, 3/8" DIA, White Plastic | EA |
| 080-0018 | Gasket | EA |
| 081-00100 | Bleeder Seat Fitting, 1/4" screw hole insert, 3/8" Screw | EA |
| 081-30169 | Bleeder Seat Fitting, 1/4" screw hole insert, 3/8" Screw | EA |
| 0841200-19 | Ring, 1-3/4" DIA, Adjustable | EA |
| 08DU08 | Bushing, 1/2" DIA, Length 1/2" | EA |
| 08DU10 | Bushing, 1/2" DIA, Length 5/8" | EA |
| 08DU12 | Bushing, 1/2" DIA, Length 3/4" | EA |
| 08DU14 | Bushing, 1/2" DIA, Length 7/8" | EA |
| 08FDU12 | Bushing, 1/2" DIA, Length 3/4", Flanged | EA |
| 09-19200 | Ring, Insp | EA |
| 1/8"X1" Roll Pin | 1/8"X1" Roll Pin | EA |
| 1/8x1/2 Roll Pin | 1/8"x1/2" Roll Pin | EA |

| Part Number | Part Description | Unit of Measure |
|---------------------|---|-----------------|
| 10/32 X 1/2 SS | Screw, Baggage Cover, 3/16" DIA | EA |
| 1001886 | Bushing, Oil Groove (w/double figure 8 groove) see comments | EA |
| 1001948 | Lifting Ring, 208 | EA |
| 1002586 | Rivet-MS20470AD3-3, 1/4 Lb Box | EA |
| 1002587 | Rivet-MS20470AD4-4.5, 1/4 Lb Box | EA |
| 1002588 | Rivet-MS20470AD4-5, 1/4 Lb Box | EA |
| 1002589 | Rivet-MS20470AD4-5.5, 1/4 Lb Box | EA |
| 1002590 | Rivet-MS20470AD4-6, 1/4 Lb Box | EA |
| 1002591 | Rivet-MS20470AD4-7, 1/4 Lb Box | EA |
| 1002592 | Rivet-MS20470AD4-8, 1/4 Lb Box | EA |
| 1002593 | Rivet-MS20470AD5-8, 1/4 Lb Box | EA |
| 1002594 | Rivet-MS20470AD5-9, 1/4 Lb Box | EA |
| 1002644 | Rivet-MS20426AD4-6, 1/4 LB Box | EA |
| 1003069 | Bushing, 5/8" x 3/4" x 3/4" (13000 Drag brace) | EA |
| 1003411 | Clamp, Hose, T-bolt, 3.25 | EA |
| 1003413 | Clamp, Hose, T-bolt, 3.38 | EA |
| 1003414 | Clamp, Hose, T-Bolt, 5.06 | EA |
| 10-1960-2 | Seal, 1/4" DIA | EA |
| 1032 NF X 3/16 | Set Screw, Cone Point, S.S., 3/16 DIA | EA |
| 1032 X 1 1/2INCH SS | Bolt, SSTL Machine Hex Head, 3/16" DIA, 1-1/2" Length | EA |
| 1032 X 2INCH SS | Bolt, SSTL Machine Hex Head, 3/16" DIA, 2" Length | EA |
| 104-04700 | Brake Fitting, #4, 45 Degree | EA |
| 105-00300 | Rivet Brake Lining, 1/8" DIA, Black | EA |
| 1095K41 | Fitting, Grease, Steel, Straight Taper, Ends are 1/4-28 Male & Ball Valve, 10pcs/pkg, 1/2" Length | EA |
| 1095K42 | Fitting, Grease, Steel, Straight Taper, Ends are 1/4-28 Male & Ball Valve, 10pcs/pkg, 3/4" Length | EA |
| 1095K43 | Fitting, Grease, Steel, Straight Taper, Ends are 1/4-28 Male & Ball Valve, 10pcs/pkg, 1" Length | EA |
| 1095K47 | Fitting, Grease, 90 degree Taper, Ends are 1/4-28 Male & Ball Valve | EA |
| 10B3349-5 | Bushing | EA |
| 10DU10 | Teflon Lined Bearing, 5/8" DIA, 5/8" Length | EA |
| 10DU12 | Bushing, 5/8" DIA, 3/4" Length | EA |
| 10FDU10 | Teflon Lined Bearing, 5/8" DIA, 5/8" Length, Flanged 1/8" | EA |
| 110 X 3/16 | Washer, Dynaseal, 3/16" DIA | EA |
| 110X1/4 | Washer, Dynaseal, 1/4" DIA | EA |
| 111-10 | Hose, Stratoflex, 5/8" | FT |
| 111-12 | Hose, Stratoflex, 1" | FT |
| 11-12314 | Spiral Wrap, 1/4" - Clear | FT |
| 11-12318 | Spiral Wrap, 1/8" - Clear | FT |
| 111-3 | Hose, Stratoflex, 3/16" | FT |
| 111-4 | Hose, Strato Flex (1/4") | FT |
| 111-4 | Hose, Strato Flex (1/4") | FT |
| 111-5 | Hose, Stratoflex, 5/16" | FT |
| 111-6 | Hose, Stratoflex, 3/8" | FT |
| 111-8 | Hose, Stratoflex, 1/2" | FT |
| 1126000-1 | Camloc, Protruding Head, Slotted Head, Carbon Steel, 0.030-0.059 Thickness | EA |
| 1126000-2 | Camloc, Protruding Head, Slotted Head, Carbon Steel, 0.060-0.089 Thickness | EA |

| Part Number | Part Description | Unit of Measure |
|----------------|---|-----------------|
| 1126000-3 | Camloc, Protruding Head, Slotted Head, Carbon Steel, 0.060-0.089 Thickness | EA |
| 1126000-4 | Camloc, Protruding Head, Slotted Head, Carbon Steel, 0.210-0.0239 Thickness | EA |
| 1126000-5 | Camloc, Protruding Head, Slotted Head, Carbon Steel, 0.150-0.179 Thickness | EA |
| 1126000-6 | Camloc, Protruding Head, Slotted Head, Carbon Steel, 0.180-0.0299 Thickness | EA |
| 1142005-14 | Stud, Airloc, #7 Stud Assembly, Stud Length 1.05 Inch, 1142 High Strength 1/4 Turn Fastening System | EA |
| 1142005-15 | Stud, Airloc, #7 Stud Assembly, Stud Length 1.08 Inch, 1142 High Strength 1/4 Turn Fastening System | EA |
| 1142005-16 | Stud, Airloc, #7 Stud Assembly, Stud Length 1.11 Inch, 1142 High Strength 1/4 Turn Fastening System | EA |
| 1142005-17 | Stud, Airloc, #7 Stud Assembly, Stud Length 1.14 Inch, 1142 High Strength 1/4 Turn Fastening System | EA |
| 1142005-18 | Stud, Airloc, #7 Stud Assembly, Stud Length 1.17 Inch, 1142 High Strength 1/4 Turn Fastening System | EA |
| 1142005-19 | Stud, Airloc | EA |
| 1142005-5 | Stud, Airloc, #7 Stud Assembly, Stud Length 0.78 Inch, 1142 High Strength 1/4 Turn Fastening System | EA |
| 1142005-6 | Stud, Airloc, #7 Stud Assembly, Stud Length 0.81 Inch, 1142 High Strength 1/4 Turn Fastening System | EA |
| 1142005-7 | Stud, Airloc, #7 Stud Assembly, Stud Length 0.84 Inch, 1142 High Strength 1/4 Turn Fastening System | EA |
| 1211203-1 | Eyebolt, 3/8" DIA Eye Ring, 5-44 Thread | EA |
| 12PLIL | Insert, Plastic 1/2", 90 Degree Fitting, 1-1/2" Side A, 2" Side B | EA |
| 12RX1/2FHA(82) | Screw | EA |
| 13587 | Bungee cord, 1/2" Thick, Grey | FT |
| 1-375-1-3 | Poppet, 3.8" DIA | EA |
| 13A02458-002 | Barrel Nut | EA |
| 13A02458-005 | Barrel Nut | EA |
| 153-00800 | Ring, Grease | EA |
| 155-00200 | Ring, Snap | EA |
| 155-14300 | Snap Ring, 2-1/2" DIA, | EA |
| 156-4 | Hose, Stratoflex, 1/4", Steel Lining | FT |
| 160200 | Sleeve, Brass, 1/8" DIA | EA |
| 160300 | Sleeve, Brass, 3/16" DIA | EA |
| 1-796 | Y Channel, Rubber | EA |
| 190297-4 | Fitting, Aero Quip #4, 130 Degrees Taper | EA |
| 190297-4S | Hose End Fitting, 45 Deg, 3/8", 1/2", Steel | EA |
| 190772-3 | Fitting, Aeroquip #3, 90 Degree | EA |
| 190772-4 | Fitting, Aero Quip #4, 90 Degree | EA |
| 193-10 | Hose, Vac Stratoflex, 5/8" | FT |
| 193-2 | HOSE, LOW PRESSURE, VAC, RUBBER, Parker - Stratoflex, 1/8" | FT |
| 193-3 | Hose, Vac Stratoflex, 3/16" | FT |
| 193-4 | Hose, Vac Stratoflex, 1/4" | FT |
| 193-6 | Hose, Vac Stratoflex, 3/8" | FT |
| 193-8 | Hose, Vac Stratoflex, 1/2" | FT |
| 19492 | Packing (O'Ring) | EA |
| 1972 | Tow bar, 12' Heavy duty knock down | EA |
| 205980-1 | Screw Kit, Male (1 used on one Float Installation) | EA |
| 212-12 | 3/32 Nut Plate Rivets | EA |

| Part Number | Part Description | Unit of Measure |
|----------------|---|-----------------|
| 215-125-0750 | Pin, Roll, 1/8 x 3/4 Spring Pin | EA |
| 217-00100 | Grommet | EA |
| 2404-S16-16-16 | Fitting | EA |
| 25141-135 | O-ring, Standard, 2" DIA | EA |
| 2600-3 | Stud, Camlock | EA |
| 2600-8 | Stud, Camlock | EA |
| 2601240-4 | Washer, 1/2" DIA | EA |
| 2650-12 | Firesleeve, 3/4", Stratoflex, Red | FT |
| 2650-16 | Firesleeve, 1", Stratoflex, Red | FT |
| 26DU16 | Bushing, 1-5/8" DIA | EA |
| 27S3-3 | Stud | EA |
| 27S3-6 | Stud | EA |
| 27S3-8 | Stud | EA |
| 300-10D | Fitting, Stratoflex | EA |
| 300-16D | Fitting, Stratoflex | EA |
| 300-4S | Fitting, Stratoflex | EA |
| 311-4D | STRAIGHT FLARED FITTING, FOR 193 HOSE, STRATOFLEX | EA |
| 311-6D | Fitting, Stratoflex | EA |
| 3124672 | Gasket, 4" DIA | EA |
| 313 GE | Lamp (MS25231-313) | EA |
| 31C12 | Stud, Engine | EA |
| 31C12P03 | Stud, Engine | EA |
| 32120 | Gasket - Regulator to Oil Cooler | EA |
| 32DU16 | Bushing, 2" DIA | EA |
| 32DX16 | Teflon Lined Bearing, 2" DIA, 5/16" Hole | EA |
| 33056 | COUPLING Set Screw, 10/32 X 1/4, 3/16" DIA | EA |
| 3506SC38A | Dzus Fastener | EA |
| 3506SC44A | Dzus Fastener | EA |
| 359071 | Washer, Seating, Rubber Center Ring, 1/8" center hole | EA |
| 3591-4CN500 | Heli-Coil, Maroon Spring, 1/4 - 28 X .500 in | EA |
| 360824 | Screw, Thread 3/8-11, 1/4" Length | EA |
| 361049 | Retainer, O - Ring Flat, 1/2" DIA | EA |
| 361523 | Washer, 3/8" DIA | EA |
| 38-190627-2-4 | Hose End | EA |
| 38-190627-4-4 | Hose End | EA |
| 38-190627-4-5 | Hose End | EA |
| 382 | Bulb | EA |
| 39997 | Bolt | EA |
| 4002-14S | Camloc (May Substitute 1142002-14) | EA |
| 4002-15S | Camloc (May Substitute 1142002-15) | EA |
| 4002-16S | Camloc (May Substitute 1142002-16) | EA |
| 4002HS | Camloc, 3/8 DIA, SSTL | EA |
| 4002NS | Grommet, SS | EA |
| 402129P003 | Stud, Two Ends at 1/4-20 & 1/4-28, 1-1/4" Grip | EA |
| 409076 | O Ring, 7/16" DIA | EA |
| 409211 | Lock Screw, 7/16" DIA | EA |
| 409263 | Pipe Plug, Plastic, Dark Blue, 1/4" DIA | EA |
| 409357 | Washer, 3/16 DIA | EA |
| 409715 | Screw, 5-44 thread, 2-1/2 Length | EA |
| 40S41-10SC | Stud, Camlock (S3413-110) | EA |
| 40s41-2sc | Stud, Camlock | EA |
| 40S41-3SC | Stud, Camlock | EA |
| 40S41-5SC | Stud, Camlock | EA |

| Part Number | Part Description | Unit of Measure |
|----------------------|---|-----------------|
| 40S41-6SC | Stud, Camlock | EA |
| 40S41-7SC | Stud, Camlock | EA |
| 40S41-8SC | Stud, Camlock | EA |
| 40S41-9SC | Stud, Camlock | EA |
| 40S5-14S | Stud, Camloc Stainless Steel, Phillips | EA |
| 40S5-15S | Stud, Camloc Stainless Steel, Phillips | EA |
| 40S5-17S | Stud, Camloc Stainless Steel, Phillips | EA |
| 40S5-3S | Stud, Camloc Stainless Steel, Phillips | EA |
| 40S5-4S | Stud, Camloc Stainless Steel | EA |
| 40S5-5S | Stud, Camloc Stainless Steel, Phillips | EA |
| 40S5-6S | Stud, Camloc Stainless Steel, Phillips | EA |
| 410465 | Flap Pump Bolt, 3/16" DIA, 1-1/2" Length | EA |
| 410578 | Seal, 3-1/2 DIA | EA |
| 410610 | Spring, 1/4" DIA, 5/8" Length | EA |
| 410776 | Nut, Brass, 3/8" DIA | EA |
| 411874 | Spring, 1/2" DIA, 1/2" Length | EA |
| 4137336P1 | Washer, Nonmetallic, Fuel Trans., Paper, 1-3/4" DIA | EA |
| 472439 | Seal, National Oil, 1-1/4" DIA | EA |
| 473232 | Seal, National Oil, 1-1/2" DIA | EA |
| 48212 | Stud, 1/16" | EA |
| 48725642 | 90Degree 1/2 Barb | EA |
| 48726202 | Tee Fitting 1/2 Barb | EA |
| 490405 | Steel Ball, 11/32, GR200 | EA |
| 499878 | Rocker Shaft Seal, R985, Packing, 3/4" DIA | EA |
| 4L4F | Nyliner, Plastic, Flanged, 1/2" DIA | EA |
| 5/16 X 1.5" ROLL PIN | 5/16 X 1.5" ROLL PIN | EA |
| 5/32"X7/8" Roll Pin | 5/32"X7/8" Roll Pin | EA |
| 50003 | Gasket, Prop., Copper, 3-3/4" DIA | EA |
| 50915K153 | Fitting, Compression, Tee, 1/4" | EA |
| 5100-46-H | Ring, snap | EA |
| 5100-62H | Ring, snap | EA |
| 5100-87-H | Snap Rings, Retaining Ring, 3/16" DIA | EA |
| 5233K66 | Clear Tubing PVC, 5/8" OD X 1/2" ID | FT |
| 5-2755-2 | Spring, 7/16" DIA, AN6201-1 | EA |
| 52NA1-070 | Nut, Mounting, 3/8" | EA |
| 53 | Lamp | EA |
| 5312K16 | Hose Clamp, 4-1/2 DIA | EA |
| 5312K18 | Hose Clamp, 5-1/2 DIA | EA |
| 532200 | Packing, Black Rubber Ring, 16" Circumfrence | EA |
| 5372K124 | Pipe Adapter, White Nylon 1/2" ID X 3/8", A3812 | EA |
| 5410 | Clamp, Hose Fits 3/8'-5/8" Hose 1/2"-1 1/16" Clamp | EA |
| 5412 | Clamp, Hose - same as S1891-12S | EA |
| 5416 | Clamp, Hose Fits 3/4"-7/8" Hose 3/4"-1" Pipe | EA |
| 54195K14 | Hose Clamp,7/32"-5/8" SSTL, Breeze | EA |
| 54195K16 | Hose Clamp, Hose Fits 7/16" X 25/32", Breeze | EA |
| 54195K22 | Hose Clamp, 11/16"-1, 1/4" SSTL, Breeze | EA |
| 54195K32 | Clamp, 2 1/4"ID (10/PKG) | EA |
| 54195K32 | Clamp, 2 1/4"ID (10/PKG) | EA |
| 54195K32 | Clamp, 2 1/4"ID (10/PKG) | EA |
| 5420 | Clamp, Hose | EA |
| 5428 | Clamp, Hose Fits | EA |

| Part Number | Part Description | Unit of Measure |
|--------------|--|-----------------|
| 5432 | Clamp, Hose | EA |
| 5436 | Clamp, Hose Fits 3/4"-2" Hose 1 1/2"-2" Pipe | EA |
| 5444 | Clamp, Hose Fits 1 1/4"-2 1/2" Hose 2 1/2" Pipe | EA |
| 5448 | Clamp, Hose | EA |
| 5456 | Clamp, Hose Fits 2" - 3" Hose 3" Pipe | EA |
| 5457 | 2 1/4" - 3 1/8" stainless hose clamp | EA |
| 5457 | 2 1/4" - 3 1/8" stainless hose clamp | EA |
| 5548172 | Hole Plug, For 3/4" DIA Hole | EA |
| 5548174 | Hole Plug, For 1-1/4" DIA Hole | EA |
| 5706 | Clamp, Hose Fits 5/16"-3/8" Hose 1/2" Pipe | EA |
| 57134 | Clamp, Plastic, White, 7/8" DIA (Adjustable to have smaller DIA) | EA |
| 5772 | Clamp, Hose Fits 3" - 4" Hose 4" Pipe | EA |
| 5780 | Clamp, Hose | EA |
| 5796 | Clamp, Hose | EA |
| 5L5F | Nyliner, Plastic, Flanged, 5/16" DIA | EA |
| 60552 | Union | EA |
| 61173 | Gasket, Oil Pressure Reg | EA |
| 6121 | Clamp, Cable Assy | EA |
| 6202 | Clamp, Hose Fits 1/4" - 5/8" (order 6204) | EA |
| 6202RS | Bearing, Ball & Roller, 5/8" DIA | EA |
| 6203 | Clamp, Hose | EA |
| 62NTA-4 | Union Fitting, Brass, 3/8-24 | EA |
| 630286 | Pushrod Tube Seal O-ring, 3/4" DIA, Replacement for Continental 630286 | EA |
| 630365 | Gasket, Continental Replacement, 1-1/2" DIA | EA |
| 630519 | Bushing, 7/16" DIA, Black Rubber | EA |
| 63102 | Elbow, 3/8inx1/4in | EA |
| 631544 | Gasket, Continental Replacement, 1-3/4" DIA | EA |
| 632006-09 | O Ring, Oxygen | EA |
| 632837 | Gasket, Continental Replacement, 1-7/16" DIA | EA |
| 637 | Cap, Valve (VC5) | EA |
| 64016 | Connector | EA |
| 64104 | Connector, 4 Way | EA |
| 646-10D | Fitting, Stratoflex | EA |
| 6504 | Hose Clamp | EA |
| 6504 | Hose Clamp | EA |
| 6506 | Hose Clamp | EA |
| 6L11F | Nyliner, Plastic, Flanged, 3/8" DIA | EA |
| 6L6F | Nyliner | EA |
| 7277-2-NUT | Hardware Kit, Klixon Circuit Breaker | EA |
| 74-451-192 | Cloth, Medium Grit Emery | EA |
| 769-8 | Clamp | EA |
| 769-8R | Clamp, Cushion, 1/2" | EA |
| 8 X 3/4 | Screw, SSTL #8X3/4" Phillips Type A Flat Head 82 degree (price/1000) | EA |
| 8/32 X 5/8IN | S.S. Phillips Head, Wear Strip | EA |
| 8/32 X 5/8IN | S.S. Phillips Head, Wear Strip | EA |
| 8-36X1/2 | Screw, 8-36x1/2, Drilled Fillister | EA |
| 85-11-140-16 | Fastener | EA |
| 85-34-101-20 | Washer | EA |
| 856B | Nut | EA |
| 863-BRAID | Braid, 1/4, Tinned Copper | FT |
| 8756 | Screw, 3/8" | EA |
| 88002A | Washer | EA |
| 8RX1/2FBS | Screw SS Fairing | EA |

| Part Number | Part Description | Unit of Measure |
|---------------|--|-----------------|
| 8RX1/2FHA | Screw, Sheet Metal 8 x 1/2 Flat Head Type A Phillip | EA |
| 8RX1/2TBS | Screw SS Faring | EA |
| 8RX5/8FBS | 8 x 5/8 Flat B Stainless | EA |
| 900568-3B | Ferrel, Brass # 3 | EA |
| 900568-4B | Ferrel, Brass # 4 | EA |
| 900568-5B | Ferrel, Brass # 5 | EA |
| 900952-16 | Spiral Wrap 1" - Black | FT |
| 900952-4 | Spiral Wrap 1/4" - Black | FT |
| 900952-4 | Spiral Wrap 1/4" - Black | FT |
| 900952-5 | Spiral Wrap | FT |
| 900952-6 | Spiral Wrap 3/8" - Black | FT |
| 90273A831 | Screw, machine,flat head, 82 degree 10-32x 3/4" with .362 head | EA |
| 94020A311 | Rivnut (Cessna 350) | EA |
| 951391 | O-Ring, 5/16" DIA, Blue Rubber | EA |
| 9753K14 | Cap, Black Vinyl, 1/4" | EA |
| 98-9228-01 | Washer | EA |
| A10-140 | Rivnut, Flat Head, #10-32 DIA, Grip 0.09-0.14", Aluminum Open-End | EA |
| A10K75 | Rivenuts | EA |
| A1110-10 | Bearing, Oilite, 1" | EA |
| A1348-8Z1 | Nut | EA |
| A14514 | Retainer | EA |
| A1635-73 | Screw, Bolt, 1/4-28 Thread, 7/8" Length, Socket Head | EA |
| A1635-79 | Screw, 1/4-28 Thread, 1" Length, Socket Head | EA |
| A1638-21 | Washer, 3/16" DIA | EA |
| A1638-7 | Washer, 3/16" DIA | EA |
| A1663-028-1 | Spring Catch | EA |
| A1758-10Z1 | Nut Tinnerman, U-Type Speed, Screw Size #10, 0.64" Length, 7/16" Width | EA |
| A1776-4Z1D | Nut Tinnerman, Flat Type Speed, Screw Size #5, 1/2" Length, 5/16" Width | EA |
| A1777-6Z1D | Nut Tinnerman, Flat Type Speed, Screw Size #6, 5/8" Length, 7/16" Width | EA |
| A1778-8Z1 | Nut Tinnerman, Flat Type Speed, Screw Size #8, 5/8" Length, 7/16" Width | EA |
| A1779-10Z1 | Nut Tinnerman, Flat Type Speed, Screw Size #10, 7/8" Length, 1/2" Width | EA |
| A1784-6Z1 | Nut Tinnerman, U-Type Speed, Screw Size #6, 0.64" Length, 7/16" Width | EA |
| A1785-6Z1 | Nut Tinnerman, U-Type Speed, Screw Size #6, 0.843" Length, 7/16" Width | EA |
| A1787-10Z1 | Nut Tinnerman, U-Type Speed, Screw Size #10, 0.843" Length, 7/16" Width | EA |
| A1787-8Z1 | Nut Tinnerman, U-Type Speed, Screw Size #8, 0.531" Length, 7/16" Width | EA |
| A1789-8Z1 | Nut Tinnerman, U-Type Speed, Screw Size #6, 0.64" Length, 7/16" Width | EA |
| A1861 | Bushing, Rubber | EA |
| A2108A | Retainer Lens, 1-3/8" DIA | EA |
| A30010 | Seal Felt, 2-1/4" DIA | EA |
| A30014 | Retainer Wheel, 2" DIA | EA |
| A30015 | Washer, 1-1/2" DIA | EA |
| A3135-8 | Washer, Stainless Steel Counter Sunk | EA |
| A3235-020-24A | Washer, Tinnerman Countersunk, Nom. Size #8, 3/4" Outside DIA, 0.196" Inside DIA | EA |
| A3235-028-935 | Washer, Tinnerman Couantersunk | EA |
| A3235-10 | Washer, SSTL Counter Sunk (25/Pkg) | EA |
| A3235SS020-27 | Washer | EA |
| A3236-6 | Stainless Steel Washer Counter Sunk | EA |
| A426 | Retainer, Lens, Assmevly | EA |
| A6191-10Z1 | Nut Tinnerman, Anchor Type Speed, Screw Size #8, 2 Lug Flat Rivet Holes | EA |
| A6191-6Z1 | Nut Tinnerman, Anchor Type Speed, 2 Lug Flat Rivet Holes | EA |
| A6191-8Z1 | Nut Tinnerman, Anchor Type Speed, Screw Size 1- Lug, Lug Flat Rivet Holes | EA |

| Part Number | Part Description | Unit of Measure |
|--------------|--|-----------------|
| A6195-10Z1 | Nutplate, Anchor Tinnerman | EA |
| A6195-8Z1 | Nut Tinnerman, Anchor Type Speed, Screw Size #8, 2 Lug Dimpled Rivet Holes | EA |
| A6196-8Z3 | Nut Plate (Cessna # S3430-2A) | EA |
| A626 | Retainer Lens Assembly | EA |
| A628 | Bearing, Oilite, 1/2" | EA |
| A6914-1024-1 | Cover Plate, Tinnerman Patch | EA |
| A7852-8Z1 | Tinnerman | EA |
| A9002 | Retaining Clip | EA |
| A9008 | Stud, Ball Pivot Hydrollic Door Stay, 1/4-28 Thread | EA |
| AA1049-6 | Oilite Bearing | EA |
| AA1232-8 | Oilite Bushing (SS-3240-28) | EA |
| AA1407-5 | Oilite Bearing | EA |
| AA1525 | Spacer | EA |
| AA630-11 | Oilite Bearing | EA |
| AAP-41 | Rivet, Pop Non-Structural | EA |
| AAP-42 | Rivet, Pop Non-Structural | EA |
| AAP-43 | Rivet, Pop Non-Structural | EA |
| AAP-44 | Rivet, Pop Non-Structural | EA |
| AAPQ-43 | Rivet Structural | EA |
| AC1012Y | Clamp, Safeline 1/8 | EA |
| AC1018Y | Clamp, Safeline 3/16 | EA |
| AGS1187-F | Nut, 1" | EA |
| AN100-3 | Thimble Cable, Carbon Steel, To fit Cable DIA 3/32" and 1/8" | EA |
| AN100-4 | Cable Thimble, Steel, To Fit Cale DIA 3/32-1/8" | EA |
| AN100-6 | Thimble Cable, Carbon Steel, To fit Cable DIA 3/16" | EA |
| AN100C3 | Thimble Cable, Stainless Steel, To fit Cable DIA 1/16" and 5/64" | EA |
| AN100C4 | Thimble Cable, Stainless Steel, To fit Cable DIA 3/32" and 1/8" | EA |
| AN100C5 | Thimble Cable, Stainless Steel, To fit Cable DIA 5/32" | EA |
| AN10-23 | Bolt, Airframe, 5/8-18 Thread, 1-9/16" Grip, 2-33/64" Length, Drilled Shank | EA |
| AN10-23A | Bolt, Airframe, 5/8-18 Thread, 1-9/16" Grip, 2-33/64" Length, Undrilled Shank | EA |
| AN10-24A | Bolt, Airframe, 5/8-18 Thread, 1-11/16" Grip, 2-41/64" Length, Undrilled Shank | EA |
| AN10-25A | Bolt, Airframe, 5/8-18 Thread, 1-13/16" Grip, 2-49/64" Length, Undrilled Shank | EA |
| AN10-27A | Bolt, Airframe, 5/8-18 Thread, 2-1/16" Grip, 3-1/64" Length, Undrilled Shank | EA |
| AN10-30 | Bolt, Airframe, 5/8-18 Thread, 2-3/16" Grip, 3-9/64" Length, Drilled Shank | EA |
| AN10-33 | Bolt, Airframe, 5/8-18 Thread, 2-9/16" Grip, 3-33/64" Length, Drilled Shank | EA |
| AN10-33A | Bolt, Airframe, 5/8-18 Thread, 2-9/16" Grip, 3-33/64" Length, Undrilled Shank | EA |
| AN10-34A | Bolt, Airframe, 5/8-18 Thread, 2-11/16" Grip, 3-41/64" Length, Undrilled Shank | EA |
| AN10-35A | Bolt, Airframe, 5/8-18 Thread, 2-13/16" Grip, 3-49/64" Length, Undrilled Shank | EA |
| AN10-37A | Bolt, Airframe, 5/8-18 Thread, 3-1/16" Grip, 4-1/64" Length, Undrilled Shank | EA |
| AN10-40A | Bolt, Airframe, 5/8-18 Thread, 3-3/16" Grip, 4-9/64" Length, Undrilled Shank | EA |
| AN10-41A | Bolt, Airframe, 5/8-18 Thread, 3-5/16" Grip, 4-17/64" Length, Undrilled Shank | EA |
| AN10-41A | Bolt, Airframe, 5/8-18 Thread, 3-5/16" Grip, 4-17/64" Length, Undrilled Shank | EA |
| AN10-46A | Bolt, Airframe, 5/8-18 Thread, 3-15/16" Grip, 4-57/64" Length, Undrilled Shank | EA |
| AN10-50A | Bolt, Airframe, 5/8-18 Thread, 4-3/16" Grip, 5-9/64" Length, Undrilled Shank | EA |
| AN10-50A | Bolt, Airframe, 5/8-18 Thread, 4-3/16" Grip, 5-9/64" Length, Undrilled Shank | EA |
| AN10-56A | Bolt Not used | EA |
| AN115-16 | Shackle Cable, Steel Cadmium Plated, Cable DIA 3/32", Strength 1600 lbs | EA |

| Part Number | Part Description | Unit of Measure |
|-------------|---|-----------------|
| AN115-32 | Shackle Cable, Steel Cadmium Plated, Cable DIA 5/32", Strength 3200 lbs | EA |
| AN115-46 | Shackle, 3/16" Cable DIA, Steel & Cadmium Plated | EA |
| AN115-8 | Shackle Cable, Steel Cadmium Plated, Cable DIA 1/16", Strength 800 lbs | EA |
| AN12-24A | Bolt, Airframe, 3/4-16 Thread, 1-9/16" Grip, 2-21/32" Length, Undrilled Shank | EA |
| AN12-32A | Bolt, Airframe, 3/4-16 Thread, 2-5/16" Grip, 3-13/32" Length, Undrilled Shank | EA |
| AN12-36A | Bolt, Steel, 3/4-16 Thread, 2.813" Grip, 3.906" Overall Length, No Shank Hole | EA |
| AN1496 | Bolt, Pivot Arm, 1" | EA |
| AN173-12A | Bolt, Close Tolerance, 10-32 Thread, 7/8" Grip, 1-9/32 Length, Undrilled Shank | EA |
| AN173-14A | Bolt, Close Tolerance, 10-32 Thread, 1-1/8" Grip, 1-17/32 Length, Undrilled Shank | EA |
| AN173-16A | Bolt, Close Tolerance, 10-32 Thread, 1-3/8" Grip, 1-25/32 Length, Undrilled Shank | EA |
| AN173-17A | Bolt, Close Tolerance, 10-32 Thread, 1-1/2" Grip, 1-29/32 Length, Undrilled Shank | EA |
| AN173-20A | Bolt, Close Tolerance, 10-32 Thread, 1-5/8" Grip, 2-1/32 Length, Undrilled Shank | EA |
| AN173-6 | Bolt | EA |
| AN174-11 | Bolt, Close Tolerance, 1/4-28 Thread, 11/16" Grip, 1-5/32 Length, Drilled Shank | EA |
| AN174-11A | Bolt, Close Tolerance, 1/4-28 Thread, 11/16" Grip, 1-5/32 Length, Undrilled Shank | EA |
| AN174-12 | Bolt, Close Tolerance, 1/4-28 Thread, 13/16" Grip, 1-9/32 Length, Drilled Shank | EA |
| AN174-12A | Bolt, Close Tolerance, 1/4-28 Thread, 13/16" Grip, 1-9/32 Length, Undrilled Shank | EA |
| AN174-13 | Bolt, Close Tolerance, 1/4-28 Thread, 15/16" Grip, 1-5/32 Length, Drilled Shank | EA |
| AN174-14 | Bolt, Close Tolerance, 1/4-28 Thread, 1-1/16" Grip, 1-17/32 Length, Drilled Shank | EA |
| AN174-15 | Bolt, Close Tolerance, 1/4-28 Thread, 1-3/16" Grip, 1-21/32 Length, Drilled Shank | EA |
| AN174-16A | Bolt, Close Tolerance, 1/4-28 Thread, 1-5/16" Grip, 1-25/32 Length, Undrilled Shank | EA |
| AN174-17A | Bolt, Close Tolerance, 1/4-28 Thread, 1-7/16" Grip, 1-29/32 Length, Undrilled Shank | EA |
| AN174-20A | Bolt, Close Tolerance, 1/4-28 Thread, 1-9/16" Grip, 2-1/32 Length, Undrilled Shank | EA |
| AN174-24A | Bolt, Close Tolerance, 1/4-28 Thread, 2-1/16" Grip, 2-17/32 Length, Undrilled Shank | EA |
| AN174-25A | Bolt, Close Tolerance, 1/4-28 Thread, 2-3/16" Grip, 2-21/32 Length, Undrilled Shank | EA |
| AN174-33 | Bolt, Close Tolerance, 1/4-28 Thread, 1-9/16" Grip, 2-1/32 Length, Drilled Shank | EA |
| AN174H12A | Bolt, Close Tolerance, 1/4-28 Thread, 13/16" Grip, 1-9/32 Length, Undrilled Shank, Drilled Head | EA |
| AN175-16 | Bolt, Close Tolerance, 5/16-24 Thread, 1-5/16" Grip, 1-27/32 Length, Drilled Shank | EA |
| AN175-20A | Bolt, Close Tolerance, 5/16-24 Thread, 1-9/16" Grip, 2-3/32 Length, Undrilled Shank | EA |
| AN175-32 | Bolt, Close Tolerance, 5/16-24 Thread, 2-131/16" Grip, 3-11/32 Length, Drilled Shank | EA |

| Part Number | Part Description | Unit of Measure |
|-------------|---|-----------------|
| AN175-33 | Bolt, Close Tolerance, 5/16-24 Thread, 2-15/16" Grip, 3-15/32 Length, Drilled Shank | EA |
| AN175-34 | Bolt, Close Tolerance, 5/16-24 Thread, 3-1/16" Grip, 3-19/32 Length, Drilled Shank | EA |
| AN176-10A | Bolt, Close Tolerance, 3/8-24 Thread, 7/16" Grip, 1-5/64 Length, Undrilled Shank | EA |
| AN176-13 | Bolt, Close Tolerance, 3/8-24 Thread, 13/16" Grip, 1-29/64 Length, Drilled Shank | EA |
| AN176-14A | Bolt, Close Tolerance, 3/8-24 Thread, 15/16" Grip, 1-37/64 Length, Undrilled Shank | EA |
| AN176-21A | Bolt, Close Tolerance, 3/8-24 Thread, 1-9/16" Grip, 2-13/64 Length, Undrilled Shank | EA |
| AN176-27 | Bolt, Close Tolerance, 3/8-24 Thread, 2-5/16" Grip, 2-61/64 Length, Drilled Shank | EA |
| AN176-7A | Bolt, Close Tolerance, 3/8-24 Thread, 5/16" Grip, 61/64 Length, Undrilled Shank | EA |
| AN178-40 | Bolt, Close Tolerance, 1/2-20 Thread, 3-5/16" Grip, 4-1/16" Length, Drilled Shank | EA |
| AN179-22 | Bolt, Close Tolerance, 9/16-18 Thread, " Grip, " Length, Drilled Shank | EA |
| AN180-26 | Bolt, Close Tolerance, 5/8-18 Thread, 1-15/16" Grip, 3-4/25" Length, Drilled Shank | EA |
| AN180-72 | Bolt, Pivot Arm, 5/8" | EA |
| AN21-6 | Bolt | EA |
| AN23-12 | Bolt, Clevis, 10-32 Thread, 7/16" Grip, 25/32" Length, Drilled Shank | EA |
| AN23-13A | Bolt, Clevis, 10-32 Thread, 1/2" Grip, 27/32" Length, Undrilled Shank | EA |
| AN23-14 | Bolt, Clevis, 10-32 Thread, 9/16" Grip, 29/32" Length, Drilled Shank | EA |
| AN23-14A | Bolt, Clevis, 10-32 Thread, 9/16" Grip, 29/32" Length, Undrilled Shank | EA |
| AN23-15 | Bolt, Clevis, 10-32 Thread, 5/8" Grip, 31/32" Length, Drilled Shank | EA |
| AN23-16 | Bolt, Clevis, 10-32 Thread, 11/16" Grip, 1-1/32" Length, Drilled Shank | EA |
| AN23-16A | Bolt, Clevis, 10-32 Thread, 11/16" Grip, 1-1/32" Length, Undrilled Shank | EA |
| AN23-17 | Bolt, Clevis, 10-32 Thread, 3/4" Grip, 1-3/32" Length, Drilled Shank | EA |
| AN23-20A | Bolt, Clevis, 10-32 Thread, 1-15/16" Grip, 2-9/32" Length, Undrilled Shank | EA |
| AN23-36A | Bolt, Clevis, 10-32 Thread, 15/16" Grip, 1-9/32" Length, Undrilled Shank | EA |
| AN23-40 | Bolt, Clevis, 10-32 Thread, 2-3/16" Grip, 2-17/32" Length, Drilled Shank | EA |
| AN23-8 | Bolt, Clevis, 10-32 Thread, 3/16" Grip, 17/32" Length, Drilled Shank | EA |
| AN23-9 | Bolt, Clevis, 10-32 Thread, 1/4" Grip, 19/32" Length, Drilled Shank | EA |
| AN24-12 | Bolt, Clevis, 1/4-28 Thread, 7/16" Grip, 25/32" Length, Drilled Shank | EA |
| AN24-13 | Bolt, Clevis, 1/4-28 Thread, 1/2" Grip, 27/32" Length, Drilled Shank | EA |
| AN24-18 | Bolt, Clevis, 1/4-28 Thread, 13/16" Grip, 1-5/32" Length, Drilled Shank | EA |
| AN24-19 | Bolt, Clevis, 1/4-28 Thread, 7/8" Grip, 1-7/32" Length, Drilled Shank | EA |
| AN24-20 | Bolt, Clevis, 1/4-28 Thread, 15/16" Grip, 1-9/32" Length, Drilled Shank | EA |
| AN24-23 | Bolt, Clevis, 1/4-28 Thread, 1-1/8" Grip, 1-15/32" Length, Drilled Shank | EA |
| AN24-27 | Bolt, Clevis, 1/4-28 Thread, 1-3/8" Grip, 1-23/32" Length, Drilled Shank | EA |
| AN24-28A | Bolt, Clevis, 1/4-28 Thread, 1-7/16" Grip, 1-25/32" Length, Undrilled Shank | EA |
| AN24-31A | Bolt, Clevis, 1/4-28 Thread, 1-5/8" Grip, 1-31/32" Length, Undrilled Shank | EA |
| AN24-32 | Bolt, Clevis, 1/4-28 Thread, 1-11/16" Grip, 2-1/32" Length, Drilled Shank | EA |
| AN24-40 | Bolt, Clevis, 1/4-28 Thread, 2-3/16" Grip, 2-17/32" Length, Drilled Shank | EA |
| AN25-26 | Bolt, Clevis, 5/16-24 Thread, 1-1/4" Grip, 1-43/64" Length, Drilled Shank | EA |
| AN25-42 | Bolt, Clevis, 5/16-24 Thread, 2-1/4" Grip, 2-43/64" Length, Drilled Shank | EA |
| AN25-44 | Bolt, Clevis, 5/16-24 Thread, 2-3/8" Grip, 2-51/64" Length, Drilled Shank | EA |
| AN25-52 | Bolt, Clevis, 5/16-24 Thread, 2-7/8" Grip, 3-19/64" Length, Drilled Shank | EA |
| AN25-52A | Bolt, Clevis, 5/16-24 Thread, 2-7/8" Grip, 3-19/64" Length, Undrilled Shank | EA |
| AN26-21 | Bolt, Clevis, 3/8-24 Thread, 1-5/16" Grip, 1-43/64" Length, Drilled Shank | EA |

| Part Number | Part Description | Unit of Measure |
|-------------|---|-----------------|
| AN26-25 | Bolt, Clevis, 3/8-24 Thread, 1-1/4" Grip, 1-39/64" Length, Drilled Shank | EA |
| AN26-29A | Bolt, Clevis, 3/8-24 Thread, 1-1/2" Grip, 1-55/64" Length, Undrilled Shank | EA |
| AN26-34A | Bolt, Clevis, 3/8-24 Thread, 1-13/16" Grip, 2-11/64" Length, Undrilled Shank | EA |
| AN26-44 | Bolt, Clevis, 3/8-24 Thread, 2-3/8" Grip, 2-51/64" Length, Undrilled Shank | EA |
| AN27-21A | Bolt, Clevis | EA |
| AN27-21A | Bolt, Clevis | EA |
| AN28-30 | Bolt | EA |
| AN29-31A | Bolt | EA |
| AN29-32A | Bolt | EA |
| AN30-31A | Bolt | EA |
| AN3-10 | Bolt, Airframe, 10-32 Thread, 5/8" Grip, 1-1/32" Length, Drilled Shank | EA |
| AN310-10 | Nut Castellated, Full-Height, 5/8-18 Thread, Carbon Steel | EA |
| AN310-12 | Nut Castellated, Full-Height, 3/4-16 Thread, Carbon Steel | EA |
| AN310-4 | Nut Castellated, Full-Height, 1/4-28 Thread, Carbon Steel | EA |
| AN310-5 | Nut Castellated, Full-Height, 5/16-24 Thread, Carbon Steel | EA |
| AN310-6 | Nut Castellated, Full-Height, 3/8-24 Thread, Carbon Steel | EA |
| AN310-7 | Nut Castellated, Full-Height, 7/16-20 Thread, Carbon Steel | EA |
| AN310-8 | Nut Castellated, Full-Height, 1/2-20 Thread, Carbon Steel | EA |
| AN310-9 | Nut Castellated, Full-Height, 9/16-18 Thread, Carbon Steel | EA |
| AN3-10A | BOLT HEX HEAD ALLOY STEEL CAD 2 UNDRILLED, Thread size 10-32, Length +/- 1/64 - 1-1/32, Grip length 5/8 | EA |
| AN3-10A | BOLT HEX HEAD ALLOY STEEL CAD 2 UNDRILLED, Thread size 10-32, Length +/- 1/64 - 1-1/32, Grip length 5/8 | EA |
| AN3-11 | Bolt, Airframe, 10-32 Thread, 3/4" Grip, 1-5/32" Length, Drilled Shank | EA |
| AN3-11A | Bolt, Airframe, 10-32 Thread, 3/4" Grip, 1-5/32" Length, Undrilled Shank | EA |
| AN3-12 | Bolt, Airframe, 10-32 Thread, 7/8" Grip, 1-9/32" Length, Drilled Shank | EA |
| AN3-12A | Bolt, Airframe, 10-32 Thread, 7/8" Grip, 1-9/32" Length, Undrilled Shank | EA |
| AN3-13 | Bolt, Airframe, 10-32 Thread, 1" Grip, 1-13/32" Length, Drilled Shank | EA |
| AN3-13A | Bolt, Airframe, 10-32 Thread, 1" Grip, 1-13/32" Length, Undrilled Shank | EA |
| AN3-14 | Bolt, Airframe, 10-32 Thread, 1-1/8" Grip, 1-17/32" Length, Drilled Shank | EA |
| AN3-14A | Bolt, Airframe, 10-32 Thread, 1-1/8" Grip, 1-17/32" Length, Undrilled Shank | EA |
| AN3-14A | Bolt, Airframe, 10-32 Thread, 1-1/8" Grip, 1-17/32" Length, Undrilled Shank | EA |
| AN3-15 | Bolt, Airframe, 10-32 Thread, 1-1/4" Grip, 1-21/32" Length, Drilled Shank | EA |
| AN315-3L | Nut Plain, Hexagon, 10-32 Thread, Left | EA |
| AN315-3R | Nut Plain, Hexagon, 10-32 Thread, Right | EA |
| AN315-4R | Nut Plain, Hexagon, 1/4-28 Thread, Right | EA |
| AN315-5R | Nut Plain, Hexagon, 5/16-24 Thread, Right | EA |
| AN315-6L | Nut Plain, Hexagon, 3/8-24 Thread, Left | EA |
| AN315-6R | Nut Plain, Hexagon, 3/8-24 Thread, Right | EA |
| AN315-7R | Nut Plain, Hexagon, 7/16-20 Thread, Right | EA |
| AN315-8R | Nut Plain, Hexagon, 1/2-20 Thread, Right | EA |
| AN315-8R | Nut Plain, Hexagon, 1/2-20 Thread, Right | EA |
| AN3-15A | Bolt, Airframe, 10-32 Thread, 1-1/4" Grip, 1-21/32" Length, Undrilled Shank | EA |
| AN3-16 | Bolt, Airframe, 10-32 Thread, 1-3/8" Grip, 1-25/32" Length, Drilled Shank | EA |
| AN316-10L | Nut Jam, Hexagon, 5/8-18 Thread, Left | EA |
| AN316-10R | Nut Jam, Hexagon, 5/8-18 Thread, Right | EA |
| AN316-12L | Nut, Jam | EA |
| AN316-12R | Nut Jam, Hexagon, 3/4-16 Thread, Right | EA |
| AN316-16 | Nut, Jam | EA |
| AN316-4L | Nut Jam, Hexagon, 1/4-28 Thread, Left | EA |
| AN316-5L | Nut Jam, Hexagon, 5/16-24 Thread, Left | EA |
| AN316-5R | Nut Jam, Hexagon, 5/16-24 Thread, Right | EA |
| AN316-6L | Nut Jam, Hexagon, 3/8-24 Thread, Left | EA |

| Part Number | Part Description | Unit of Measure |
|-------------|---|-----------------|
| AN316-6R | Nut Jam, Hexagon, 3/8-24 Thread, Right | EA |
| AN316-7L | Nut Jam, Hexagon, 7/16-20 Thread, Left | EA |
| AN316-7R | Nut Jam, Hexagon, 7/16-20 Thread, Right | EA |
| AN316-8L | Nut Jam, Hexagon, 1/2-20 Thread, Left | EA |
| AN316-8R | Nut Jam, Hexagon, 1/2-20 Thread, Right | EA |
| AN316-9L | Nut Jam, Hexagon, 9/16-18 Thread, Left | EA |
| AN316-9R | Nut Jam, Hexagon, 9/16-18 Thread, Right | EA |
| AN3-16A | Bolt, Airframe, 10-32 Thread, 1-3/8" Grip 1/25/32" Length, Undrilled Shank | EA |
| AN316C10L | Jam Nut, Hexagon, Stainless Steel, 5/8-18, LH | EA |
| AN316C12L | Jam Nut, Stainless Steel, 3/4-16 LH | EA |
| AN316C5L | Nut, Jam (Stainless) | EA |
| AN316C5R | Nut Jam, Hexagon, Corrosion Resistant, 5/16-24 Thread, Right | EA |
| AN316C6L | Nut, Jam (Stainless) | EA |
| AN316C6R | Nut, Jam (Stainless) | EA |
| AN316C7L | Nut, Jam (Stainless) | EA |
| AN316C7R | Nut, Jam (Stainless) | EA |
| AN316C8L | Nut, Jam (Stainless) | EA |
| AN316C8R | Nut Jam, Hexagon, Corrosion Resistant, 1/2-20 Thread, Right | EA |
| AN316C9L | Nut, Jam (Stainless) | EA |
| AN316C9R | Nut, Jam (Stainless) | EA |
| AN3-17 | Bolt, Airframe, 10-32 Thread, 1-1/2" Grip, 1-29/32" Length, Drilled Shank | EA |
| AN3-17A | Bolt, Airframe, 1-29/32 Length, 1-1/2 Grip, 10-32 Thread, Undrilled Shank | EA |
| AN3-20 | Bolt, Airframe, 10-32 Thread, 1-5/8" Grip, 2-1/32" Length, Drilled Shank | EA |
| AN320-1 | Nut, Shear Castellated, 6-40 Thread | EA |
| AN320-10 | Nut, Shear Castellated, 5/8-18 Thread | EA |
| AN320-12 | Nut, Shear Castellated, 3/4-16 Thread | EA |
| AN320-14 | Nut, Shear Castellated, 7/8-14 Thread | EA |
| AN320-16 | Nut, Shear Castellated, 1"-14 Thread | EA |
| AN320-3 | Nut, Shear Castellated, 10-32 Thread | EA |
| AN320-4 | Nut, Shear Castellated, 1/4-28 Thread | EA |
| AN320-5 | Nut, Shear Castellated, 5/16-24 Thread | EA |
| AN320-6 | Nut, Shear Castellated, 3/8-24 Thread | EA |
| AN320-7 | Nut, Shear Castellated, 7/16-20 Thread | EA |
| AN320-8 | Nut, Shear Castellated, 1/2-20 Thread | EA |
| AN320-9 | Nut, Shear Castellated, 9/16-18 Thread | EA |
| AN3-20A | Bolt, Airframe, 10-32 Thread, 1-5/8" Grip, 2-1/32" Length, Undrilled Shank | EA |
| AN3-20A | Bolt, Airframe, 10-32 Thread, 1-5/8" Grip, 2-1/32" Length, Undrilled Shank | EA |
| AN3-21 | Bolt, Airframe, 10-32 Thread, 2-1/4" Grip, 2-21/32" Length, Drilled Shank | EA |
| AN3-21A | Bolt, Airframe, 10-32 Thread, 2-1/4" Grip, 2-21/32" Length, Undrilled Shank | EA |
| AN32-28A | Bolt, Clevis | EA |
| AN3-22A | Bolt, Airframe, 10-32 Thread, 1-7/8" Grip, 2-9/32" Length, Undrilled Shank | EA |
| AN32-32A | Bolt | EA |
| AN3-23A | Bolt, Airframe, 10-32 Thread, 2" Grip, 2-13/32" Length, Undrilled Shank | EA |
| AN3-24 | Bolt, Airframe, 10-32 Thread, 2-1/16" Grip, 2-17/32" Length, Drilled Shank | EA |
| AN3-24A | Bolt, Airframe, 10-32 Thread, 2-1/8" Grip, 2-17/32" Length, Undrilled Shank | EA |
| AN3-24A | Bolt, Airframe, 10-32 Thread, 2-1/8" Grip, 2-17/32" Length, Undrilled Shank | EA |
| AN3-25 | Bolt, Airframe, 10-32 Thread, 2-1/4" Grip, 2-21/32" Length, Drilled Shank | EA |
| AN3-25A | Bolt, Airframe, 10-32 Thread, 2-1/4" Grip, 2-21/32" Length, Undrilled Shank | EA |
| AN3-26A | Bolt, Airframe, 10-32 Thread, 2-3/8" Grip, 2-25/32" Length, Undrilled Shank | EA |
| AN3-27A | Bolt, Airframe, 10-32 Thread, 2-1/2" Grip, 2-29/32" Length, Undrilled Shank | EA |
| AN3-3 | Bolt, Airframe, 10-32 Thread, 1/16" Grip, 15/32" Length, Drilled Shank | EA |
| AN3-30A | Bolt, Airframe, 10-32 Thread, 2-5/8" Grip, 3-1/32" Length, Undrilled Shank | EA |
| AN3-32A | Bolt, Airframe, 10-32 Thread, 2-7/8" Grip, 3-9/32" Length, Undrilled Shank | EA |

| Part Number | Part Description | Unit of Measure |
|-------------|--|-----------------|
| AN3-33A | Bolt, Airframe, 10-32 Thread, 3" Grip, 3-13/32" Length, Undrilled Shank | EA |
| AN3-34A | Bolt, Airframe, 10-32 Thread, 3-1/8" Grip, 3-17/32" Length, Undrilled Shank | EA |
| AN3-35A | Bolt, Airframe, 10-32 Thread, 3-1/4" Grip, 3-21/32" Length, Undrilled Shank | EA |
| AN3-36A | Bolt, Airframe, 10-32 Thread, 3-3/8" Grip, 3-25/32" Length, Undrilled Shank | EA |
| AN3-37A | Bolt, Airframe, 10-32 Thread, 3-1/2" Grip, 3-29/32" Length, Undrilled Shank | EA |
| AN3-3A | Bolt, Airframe, 10-32 Thread, 1/16" Grip, 15/32" Length, Undrilled Shank | EA |
| AN3-4 | Bolt, Airframe, 10-32 Thread, 1/8" Grip, 17/32" Length, Drilled Shank | EA |
| AN340-3 | Nut Plain, Hexagon, Coarse Thread, 2-64 Thread | EA |
| AN3-43A | Bolt, Airframe, 10-32 Thread, 4" Grip, 4-13/32" Length, Undrilled Shank | EA |
| AN3-4A | BOLT HEX HEAD ALLOY STEEL CAD 2 UNDRILLED, Thread size 10-32, Length +/- 1/64 - 17/32, Grip length 1/8 | EA |
| AN3-4A | BOLT HEX HEAD ALLOY STEEL CAD 2 UNDRILLED, Thread size 10-32, Length +/- 1/64 - 17/32, Grip length 1/8 | EA |
| AN3-4A | BOLT HEX HEAD ALLOY STEEL CAD 2 UNDRILLED, Thread size 10-32, Length +/- 1/64 - 17/32, Grip length 1/8 | EA |
| AN3-5 | Bolt, Airframe, 10-32 Thread, 1/4" Grip, 21/32" Length, Drilled Shank | EA |
| AN356-1032 | Nut, Lock | EA |
| AN356-428 | Nut, Lock | EA |
| AN356-524 | Nut, Lock | EA |
| AN356-632 | Nut, Lock | EA |
| AN356-720 | Nut, Lock | EA |
| AN356-832 | Nut, Lock | EA |
| AN3-5A | BOLT HEX HEAD ALLOY STEEL CAD 2 UNDRILLED, Thread size 10-32, Length +/- 1/64 - 21/32, Grip length 1/4 | EA |
| AN3-5A | BOLT HEX HEAD ALLOY STEEL CAD 2 UNDRILLED, Thread size 10-32, Length +/- 1/64 - 21/32, Grip length 1/4 | EA |
| AN3-5A | BOLT HEX HEAD ALLOY STEEL CAD 2 UNDRILLED, Thread size 10-32, Length +/- 1/64 - 21/32, Grip length 1/4 | EA |
| AN3-6 | Bolt, Airframe, 10-32 Thread, 3/8" Grip, 25/32" Length, Drilled Shank | EA |
| AN3-6A | BOLT HEX HEAD ALLOY STEEL CAD 2 UNDRILLED, Thread size 10-32, Length +/- 1/64 - 25/32, Grip length 3/8 | EA |
| AN3-6A | BOLT HEX HEAD ALLOY STEEL CAD 2 UNDRILLED, Thread size 10-32, Length +/- 1/64 - 25/32, Grip length 3/8 | EA |
| AN3-7 | Bolt, Airframe, 10-32 Thread, 1/2" Grip, 29/32" Length, Drilled Shank | EA |
| AN3-73A | Bolt, Airframe, 10-32 Thread, 7" Grip, 7-13/32" Length, Undrilled Shank | EA |
| AN3-7A | BOLT HEX HEAD ALLOY STEEL CAD 2 UNDRILLED, Thread size 10-32, Length +/- 1/64 - 29/32, Grip length 1/2 | EA |
| AN3-7A | BOLT HEX HEAD ALLOY STEEL CAD 2 UNDRILLED, Thread size 10-32, Length +/- 1/64 - 29/32, Grip length 1/2 | EA |
| AN3C10 | Bolt, Airframe, Corrosion Resistant, 10-32 Thread, 5/8" Grip, 1-1/32" Length, Drilled Shank | EA |
| AN3C10A | Bolt, Airframe, Corrosion Resistant, 10-32 Thread, Undrilled Shank | EA |
| AN3C10A | Bolt, Airframe, Corrosion Resistant, 10-32 Thread, Undrilled Shank | EA |
| AN3C12A | Bolt, Airframe, Corrosion Resistant, 10-32 Thread, 7/8" Grip, 1-9/32" Length, Undrilled Shank | EA |
| AN3C20A | Bolt, Airframe, Corrosion Resistant, 10-32 Thread, 1-5/8" Grip, 2-1/32" Length, Undrilled Shank | EA |
| AN3C3A | Bolt, Airframe, Corrosion Resistant, 10-32 Thread, 1/16" Grip, 15/32" Length, Undrilled Shank | EA |
| AN3C5A | Bolt, Airframe, Corrosion Resistant, 10-32 Thread, 1/4" Grip, 21/32" Length, Undrilled Shank | EA |
| AN3C5A | Bolt, Airframe, Corrosion Resistant, 10-32 Thread, 1/4" Grip, 21/32" Length, Undrilled Shank | EA |

| Part Number | Part Description | Unit of Measure |
|-------------|--|-----------------|
| AN3C6 | Bolt, Airframe, Corrosion Resistant, 10-32 Thread, 3/8" Grip, 25/32" Length, Drilled Shank | EA |
| AN3C6A | Bolt, Airframe, Corrosion Resistant, 10-32 Thread, 3/8" Grip, 25/32" Length, Undrilled Shank | EA |
| AN3C7 | Bolt, Airframe, Corrosion Resistant, 10-32 Thread, 1/2" Grip, 29/32" Length, Drilled Shank | EA |
| AN3C7A | Bolt, Airframe, Corrosion Resistant, 10-32 Thread, 1/2" Grip, 29/32" Length, Undrilled Shank | EA |
| AN3H3A | Bolt, Airframe, 10-32 Thread, 1/16" Grip, 15/32" Length, Drilled Head, Undrilled Shank | EA |
| AN3H5A | Bolt, Airframe, 10-32 Thread, 1/4" Grip, 21/32" Length, Drilled Head, Undrilled Shank | EA |
| AN3H6A | Bolt, Airframe, 10-32 Thread, 3/8" Grip, 25/32" Length, Drilled Head, Undrilled Shank | EA |
| AN3H7A | Bolt, Airframe, 0-32 Thread, 1/2" Grip, 29/32" Length, Drilled Head, Undrilled Shank | EA |
| AN4-10 | Bolt, Airframe, 1/4-28 Thread, 9/16" Grip, 1-1/32" Length, Drilled Shank, Steel Cad II Plating | EA |
| AN4-11 | Bolt, Airframe, 1/4-28 Thread, 11/16" Grip, 1-5/32" Length, Drilled Shank, Steel Cad II Plating | EA |
| AN4-12 | Bolt, Airframe, 1/4-28 Thread, 13/16" Grip, 1-9/32" Length, Drilled Shank, Steel Cad II Plating | EA |
| AN4-12A | Bolt, Airframe, 1/4-28 Thread, 13/16" Grip, 1-9/32" Length, Undrilled Shank, Steel Cad II Plating | EA |
| AN4-13 | Bolt, Airframe, 1/4-28 Thread, 15/16" Grip, 1-13/32" Length, Drilled Shank, Steel Cad II Plating | EA |
| AN4-13A | Bolt, Airframe, 1/4-28 Thread, 15/16" Grip, 1-13/32" Length, Undrilled Shank, Steel Cad II Plating | EA |
| AN4-14 | Bolt, Airframe, 1/4-28 Thread, 1-1/16" Grip, 1-17/32" Length, Drilled Shank, Steel Cad II Plating | EA |
| AN4-14A | Bolt, Airframe, 1/4-28 Thread, 1-1/16" Grip, 1-17/32" Length, Undrilled Shank, Steel Cad II Plating | EA |
| AN4-15 | Bolt, Airframe, 1/4-28 Thread, 1-3/16" Grip, 1-21/32" Length, Drilled Shank, Steel Cad II Plating | EA |
| AN415-2 | Pin Locking, Hitch (Hair), 0.08" Wire DIA, 1-15/16" Length | EA |
| AN4-15A | Bolt, Airframe, 1/4-28 Thread, 1-3/16" Grip, 1-21/32" Length, Undrilled Shank, Steel Cad II Plating | EA |
| AN4-16 | Bolt, Airframe, 1/4-28 Thread, 1-5/16" Grip, 1-25/32" Length, Drilled Shank, Steel Cad II Plating | EA |
| AN416-1 | Pin Locking, Safety, 0.051" Wire DIA, 1-1/16" Length | EA |
| AN416-2 | Pin Locking, Safety, 0.041" Wire DIA, 3/4" Length | EA |
| AN4-16A | BOLT HEX HEAD ALLOY STEEL CAD 2 UNDRILLED, Thread size 1/4-28, Length +/- 1/64 - 1-25/32, Grip length 1-5/16 | EA |
| AN4-16A | BOLT HEX HEAD ALLOY STEEL CAD 2 UNDRILLED, Thread size 1/4-28, Length +/- 1/64 - 1-25/32, Grip length 1-5/16 | EA |
| AN4-17 | Bolt, Airframe, 1/4-28 Thread, 1-7/16" Grip, 1-29/32" Length, Drilled Shank, Steel Cad II Plating | EA |
| AN4-17A | Bolt, Airframe, 1/4-28 Thread, 1-7/16" Grip, 1-29/32" Length, Undrilled Shank, Steel Cad II Plating | EA |
| AN4-20 | Bolt, Airframe, 1/4-28 Thread, 1-9/16" Grip, 2-1/32" Length, Drilled Shank, Steel Cad II Plating | EA |
| AN4-20A | BOLT HEX HEAD ALLOY STEEL CAD 2 UNDRILLED, Thread size 1/4-28, Length +/- 1/64 - 2-1/32, Grip length 1-9/16 | EA |

| Part Number | Part Description | Unit of Measure |
|-------------|---|-----------------|
| AN4-20A | BOLT HEX HEAD ALLOY STEEL CAD 2 UNDRILLED, Thread size 1/4-28, Length +/- 1/64 - 2-1/32, Grip length 1-9/16 | EA |
| AN4-21 | Bolt, Airframe, 1/4-28 Thread, 1-11/16" Grip, 2-5/32" Length, Drilled Shank, Steel Cad II Plating | EA |
| AN4-21A | Bolt, Airframe, 1/4-28 Thread, 1-11/16" Grip, 2-5/32" Length, Undrilled Shank, Steel Cad II Plating | EA |
| AN4-22A | Bolt, Airframe, 1/4-28 Thread, 1-13/16" Grip, 2-9/32" Length, Undrilled Shank, Steel Cad II Plating | EA |
| AN4-23 | Bolt, Drilled Shank, 1/4-28 Thread, 1.02 Grip | EA |
| AN4-23A | Bolt, Airframe, 1/4-28 Thread, 1-15/16" Grip, 2-13/32" Length, Undrilled Shank, Carbon Steel | EA |
| AN4-24A | Bolt, Airframe, 1/4-28 Thread, 2-1/16" Grip, 2-17/32" Length, Undrilled Shank, Carbon Steel | EA |
| AN4-25 | Bolt, Airframe, 1/4-28 Thread, 2-3/16" Grip, 2-21/32 Length, Drilled Shank, Steel Cad II Plating | EA |
| AN4-25A | Bolt, Airframe, 1/4-28 Thread, 2-3/16" Grip, 2-21/32 Length, Undrilled Shank, Steel Cad II Plating | EA |
| AN4-26 | Bolt, Airframe, 1/4-28 Thread, 2-5/16" Grip, 2-25/32" Length, Drilled Shank, Carbon Steel | EA |
| AN4-26A | Bolt, Airframe, 1/4-28 Thread, 2-5/16" Grip, 2-25/32" Length, Undrilled Shank, Steel Cad II Plating | EA |
| AN4-27A | Bolt, Airframe, 1/4-28 Thread, 2-7/16" Grip, 2-29/32" Length, Undrilled Shank, Steel Cad II Plating | EA |
| AN42B13A | Bolt Eye, 10-32 Thread, #10 Bolt Size, 1" Grip, 1-13/32" Length, Undrilled | EA |
| AN42B14A | Bolt Eye, 10-32 Thread, #10 Bolt Size, 1-1/8" Grip, 1-17/32" Length, Undrilled | EA |
| AN42B16A | Bolt Eye, 10-32 Thread, #10 Bolt Size, 1-3/8" Grip, 1-25/32" Length, Undrilled | EA |
| AN42B4A | Bolt Eye, 10-32 Thread, #10 Bolt Size, 1/8" Grip, 17/32" Length, Undrilled | EA |
| AN42B5A | Bolt Eye, 10-32 Thread, #10 Bolt Size, 1/4" Grip, 21/32" Length, Undrilled | EA |
| AN42B6A | Bolt Eye, 10-32 Thread, #10 Bolt Size, 3/8" Grip, 25/32" Length, Undrilled | EA |
| AN4-3 | Bolt, Airframe, 1/4-28 Thread, 1/16" Grip, 15/32" Length, Drilled Shank, Steel Cad II Plating | EA |
| AN4-30A | Bolt, Airframe, 1/4-28 Thread, 2-9/16" Grip, 3-1/32" Length, Undrilled Shank, Steel Cad II Plating | EA |
| AN4-32A | Bolt, Airframe, 1/4-28 Thread, 2-13/16" Grip, 3-9/32" Length, Undrilled Shank, Steel Cad II Plating | EA |
| AN4-33A | Bolt, Airframe, 1/4-28 Thread, 2-15/16" Grip, 3-13/32" Length, Undrilled Shank, Steel Cad II Plating | EA |
| AN4-34A | Bolt, Airframe, 1/4-28 Thread, 3-1/16" Grip, 3-17/32" Length, Undrilled Shank, Steel Cad II Plating | EA |
| AN4-35A | Bolt, Airframe, 1/4-28 Thread, 3-3/16" Grip, 3-21/32" Length, Undrilled Shank, Steel Cad II Plating | EA |
| AN4-36 | Bolt, Airframe, 1/4-28 Thread, 3-5/16" Grip, 3-25/32" Length, Drilled Shank, Steel Cad II Plating | EA |
| AN4-36A | Bolt, Airframe, 1/4-28 Thread, 3-5/16" Grip, 3-25/32" Length, Undrilled Shank, Steel Cad II Plating | EA |
| AN4-37A | Bolt, Airframe, 1/4-28 Thread, 3-7/16" Grip, 3-29/32" Length, Undrilled Shank, Steel Cad II Plating | EA |
| AN4-3A | Bolt, Airframe, 1/4-28 Thread, 1/16" Grip, 15/32" Length, Undrilled Shank, Steel Cad II Plating | EA |
| AN43B5A | Bolt Eye, 1/4-28 Thread, #10 Bolt Size, 3/16" Grip, 21/32" Length, Undrilled | EA |

| Part Number | Part Description | Unit of Measure |
|-------------|--|-----------------|
| AN4-4 | Bolt, Airframe, 1/4-28 Thread, 1/16" Grip, 17/32" Length, Drilled Shank, Steel Cad II Plating | EA |
| AN4-40A | Bolt, Airframe, 1/4-28 Thread, 3-9/16" Grip, 4-1/32" Length, Undrilled Shank, Steel Cad II Plating | EA |
| AN44-10A | Bolt Eye, 15/16-24 Thread, 1/4" Bolt Size, 9/16" Grip, 1-3/32" Length, Undrilled | EA |
| AN44-11A | Bolt Eye, 15/16-24 Thread, 1/4" Bolt Size, 11/16" Grip, 1-7/32" Length, Undrilled | EA |
| AN44-13A | Bolt Eye, 15/16-24 Thread, 1/4" Bolt Size, 15/16" Grip, 1-15/32" Length, Undrilled | EA |
| AN44-15A | Bolt Eye, 15/16-24 Thread, 1/4" Bolt Size, 1-3/16" Grip, 1-23/32" Length, Undrilled | EA |
| AN44-22A | Bolt Eye, 15/16-24 Thread, 1/4" Bolt Size, 1-13/16" Grip, 2-11/32" Length, Undrilled | EA |
| AN44-30A | Bolt Eye, 15/16-24 Thread, 1/4" Bolt Size, 2-9/16" Grip, 3-3/32" Length, Undrilled | EA |
| AN44-34A | Bolt Eye, 15/16-24 Thread, 1/4" Bolt Size, 3-1/16" Grip, 3-19/32" Length, Undrilled | EA |
| AN44-5A | Bolt Eye, 15/16-24 Thread, 1/4" Bolt Size, 3/16" Grip, 23/32" Length, Undrilled | EA |
| AN44-6A | Bolt Eye, 15/16-24 Thread, 1/4" Bolt Size, 5/16" Grip, 27/32" Length, Undrilled | EA |
| AN4-4A | BOLT HEX HEAD ALLOY STEEL CAD 2 UNDRILLED, Thread size 1/4-28, Length +/- 1/64 - 17/32, Grip length 1/16 | EA |
| AN4-4A | BOLT HEX HEAD ALLOY STEEL CAD 2 UNDRILLED, Thread size 1/4-28, Length +/- 1/64 - 17/32, Grip length 1/16 | EA |
| AN4-5 | Bolt, Airframe, 1/4-28 Thread, 3/16" Grip, 21/32" Length, Drilled Shank, Steel Cad II Plating | EA |
| AN4-50A | Bolt, Airframe, 1/4-28 Thread, 4-9/16" Grip, 5-1/32" Length, Undrilled Shank, Steel Cad II Plating | EA |
| AN45-10A | Bolt Eye, 15/16-24 Thread, 5/16" Bolt Size, 9/16" Grip, 1-3/32" Length, Undrilled | EA |
| AN45-11A | Bolt Eye, 15/16-24 Thread, 5/16" Bolt Size, 11/16" Grip, 1-7/32" Length, Undrilled | EA |
| AN45-12A | Bolt Eye, 15/16-24 Thread, 5/16" Bolt Size, 13/16" Grip, 1-11/32" Length, Undrilled | EA |
| AN45-24A | Bolt Eye, 15/16-24 Thread, 5/16" Bolt Size, 2-1/16" Grip, 2-19/32" Length, Undrilled | EA |
| AN4-53A | Bolt, Airframe, 1/4-28 Thread, 4-15/16" Grip, 5-13/32 Length, Undrilled Shank, Steel Cad II Plating | EA |
| AN4-53A | Bolt, Airframe, 1/4-28 Thread, 4-15/16" Grip, 5-13/32 Length, Undrilled Shank, Steel Cad II Plating | EA |
| AN4-55A | Bolt, Airframe, 1/4-28 Thread, 5-3/16" Grip, 5-21/32" Length, Undrilled Shank, Carbon Steel | EA |
| AN4-55A | Bolt, Airframe, 1/4-28 Thread, 5-3/16" Grip, 5-21/32" Length, Undrilled Shank, Carbon Steel | EA |
| AN4-5A | Bolt, Airframe, 1/4-28 Thread, 3/16" Grip, 21/32" Length, Undrilled Shank, Carbon Steel | EA |
| AN4-6 | Bolt, Airframe, 1/4-28 Thread, 5/16" Grip, 25/32" Length, Drilled Shank, Steel Cad II Plating | EA |
| AN46-11A | Bolt Eye, 3/8-24 Thread, 3/8" Bolt Size, 9/16" Grip, 2-19/32" Length, Undrilled | EA |

| Part Number | Part Description | Unit of Measure |
|-------------|--|-----------------|
| AN46-16A | Bolt Eye, 3/8-24 Thread, 3/8" Bolt Size, 1-3/16" Grip, 1-27/32" Length, Undrilled | EA |
| AN46-17A | Bolt Eye, 3/8-24 Thread, 3/8" Bolt Size, 1-5/16" Grip, 1-31/32" Length, Undrilled | EA |
| AN46-24A | Bolt Eye, 3/8-24 Thread, 3/8" Bolt Size, 1-15/16" Grip, 1-19/32" Length, Undrilled | EA |
| AN4-62A | Bolt, Airframe, 1/4-28 Thread, 5-13/16" Grip, 6-9/31" Length, Undrilled Shank, Steel Cad II Plating | EA |
| AN46-32A | Eye Bolt | EA |
| AN4-65A | Bolt, Airframe, 1/4-28 Thread, 6-3/16" Grip, 6-21/31" Length, Undrilled Shank, Steel Cad II Plating | EA |
| AN4-6A | BOLT HEX HEAD ALLOY STEEL CAD 2 UNDRILLED, Thread size 1/4-28, Length +/- 1/64 - 25/32, Grip length 5/16 | EA |
| AN4-6A | BOLT HEX HEAD ALLOY STEEL CAD 2 UNDRILLED, Thread size 1/4-28, Length +/- 1/64 - 25/32, Grip length 5/16 | EA |
| AN4-7 | Bolt, Airframe, 1/4-28 Thread, 7/16" Grip, 29/32" Length, Drilled Shank, Steel Cad II Plating | EA |
| AN47-22 | Bolt Eye, 7/16-20 Thread, 3/8" Bolt Size, 1-11/16" Grip, 2-11/32" Length, Undrilled | EA |
| AN47-30A | Bolt Eye, 7/16-20 Thread, 3/8" Bolt Size, 2-7/16" Grip, 3-3/32" Length, Undrilled | EA |
| AN4-7A | Bolt, Airframe, 1/4-28 Thread, 7/16" Grip, 29/32" Length, Undrilled Shank, Steel Cad II Plating | EA |
| AN47C22A | Bolt Eye, 7/16-20 Thread, 3/8" Bolt Size, Corrosion Resistant Steel, 1-11/16" Grip, 2-11/32" Length, Undrilled | EA |
| AN4-80A | Bolt, Airframe, 1/4-28 Thread, 7-9/16" Grip, 8-1/32" Length, Undrilled Shank, Steel Cad II Plating | EA |
| AN48-10 | Bolt Eye, 1/2-20 Thread, 5/16" Bolt Size, 5/16" Grip, 1-3/32" Length, Undrilled | EA |
| AN48-22A | Bolt Eye, 1/2-20 Thread, 7/16" Bolt Size, 1-9/16" Grip, 2-11/32" Length, Undrilled | EA |
| AN4C12A | Bolt, Airframe, Corrosion Resistant, 1/4-28 Thread, 13/16" Grip, 1-9/32" Length, Undrilled Shank | EA |
| AN4C5A | Bolt, Airframe, Corrosion Resistant, 1/4-28 Thread, 3/16" Grip, 21/32" Length, Undrilled Shank | EA |
| AN4C7A | Bolt, Airframe, Corrosion Resistant, 1/4-28 Thread, 7/16" Grip, 29/32" Length, Undrilled Shank | EA |
| AN4H10A | Bolt, Airframe, 1/4-28 Thread, 9/16" Grip, 1-1/32" Length, Drilled Head, Undrilled Shank, Steel Cad II Plating | EA |
| AN4H11A | Bolt, Airframe, 1/4-28 Thread, 11/16" Grip, 1-5/32" Length, Drilled Head, Undrilled Shank, Steel Cad II Plating | EA |
| AN4H13A | Bolt, Airframe, 1/4-28 Thread, 15/16" Grip, 1-13/32" Length, Drilled Head, Undrilled Shank, Steel Cad II Plating | EA |
| AN4H14A | Bolt, Airframe, 1/4-28 Thread, 1-1/16" Grip, 1-17/32" Length, Drilled Head, Undrilled Shank, Steel Cad II Plating | EA |
| AN4H15A | Bolt, Airframe, 1/4-28 Thread, 1-3/16" Grip, 1-21/32" Length, Drilled Head, Undrilled Shank, Steel Cad II Plating | EA |
| AN4H17A | Bolt, Airframe, 1/4-28 Thread, 1-7/16" Grip, 1-29/32" Length, Drilled Head, Undrilled Shank, Steel Cad II Plating | EA |
| AN4H21 | Bolt, Airframe, 1/4-28 Thread, 1-11/16" Grip, 12-5/32" Length, Drilled Head, Drilled Shank, Steel Cad II Plating | EA |
| AN4H21A | Bolt, Airframe, 1/4-28 Thread, 1-11/16" Grip, 12-5/32" Length, Drilled Head, Undrilled Shank, Steel Cad II Plating | EA |

| Part Number | Part Description | Unit of Measure |
|--------------|---|-----------------|
| AN4H3A | Bolt, Airframe, 1/4-28 Thread, 1/16" Grip, 15/32" Length, Drilled Head, Undrilled Shank, Steel Cad II Plating | EA |
| AN4H4A | Bolt, Airframe, 1/4-28 Thread, 1/16" Grip, 17/32" Length, Drilled Head, Undrilled Shank, Steel Cad II Plating | EA |
| AN4H7A | Bolt, Airframe, 1/4-28 Thread, 7/16" Grip, 29/32" Length, Drilled Head, Undrilled Shank, Steel Cad II Plating | EA |
| AN500-416-12 | Screw, Pan Head, 1/4-28 Thread | EA |
| AN500B8-6 | Screw Compass, Brass | EA |
| AN502-10-12 | Screw, Fillister Head, Drilled, 10-32 Thread, 3/4" Length | EA |
| AN502-10-16 | Screw, Fillister Head, Drilled, 10-32 Thread, 1" Length | EA |
| AN502-10-22 | Screw, Fillister Head, Drilled, 10-32 Thread, 1-3/8" Length | EA |
| AN502-10-6 | Screw, Structural, Fillister Head | EA |
| AN502-10-8 | Screw, Fillister Head, Drilled, 10-32 Thread, 1/2" Length | EA |
| AN503-6-10 | Screw, Fillister Head, Drilled, 6-32 Thread, 5/8" Length | EA |
| AN503-6-8 | Screw, Fillister Head, Drilled, 6-32 Thread, 1/2" Length | EA |
| AN503-8-10 | Screw, Fillister Head, Drilled, 8-32 Thread, 5/8" Length | EA |
| AN503-8-12 | Screw, Fillister Head, Drilled, 8-32 Thread, 3/4" Length | EA |
| AN503-8-4 | Screw, Fillister Head, Drilled, 8-32 Thread, 1/4" Length | EA |
| AN503-8-6 | Screw, Fillister Head, Drilled, 8-32 Thread, 3/8" Length | EA |
| AN503-8-8 | Screw, Fillister Head, Drilled, 8-32 Thread, 1/2" Length | EA |
| AN506-416R12 | Screw, 100 Deg. Flat Head, 1/4-28 Thread, 1/4" Grip, 25/32" Length, Sturctural Machine Screw, Carbon Steel | EA |
| AN509-416R54 | Screw, 100 Deg. Flat Head, 1/4-28 Thread, 3-7/16" Grip, 3-" Length, Sturctural Machine Screw, Carbon Steel | EA |
| AN5-10 | Bolt, Airframe, 5/16-24 Thread, 9/16" Grip, 1-3/32" Length, Drilled Shank, Steel Cad II Plating | EA |
| AN5-10A | Bolt, Airframe, 5/16-24 Thread, 9/16" Grip, 1-3/32" Length, Undrilled Shank, Steel Cad II Plating | EA |
| AN5-11 | Bolt, Airframe, 5/16-24 Thread, 11/16" Grip, 1-7/32" Length, Drilled Shank, Steel Cad II Plating | EA |
| AN5-11A | Bolt, Airframe, 5/16-24 Thread, 11/16" Grip, 1-7/32" Length, Undrilled Shank, Steel Cad II Plating | EA |
| AN5-11A | Bolt, Airframe, 5/16-24 Thread, 11/16" Grip, 1-7/32" Length, Undrilled Shank, Steel Cad II Plating | EA |
| AN5-12 | Bolt, Airframe, 5/16-24 Thread, 13/16" Grip, 1-11/32" Length, Drilled Shank, Steel Cad II Plating | EA |
| AN5-12A | BOLT HEX HEAD ALLOY STEEL CAD 2 UNDRILLED, Thread size 5/16-24, Length +/- 1/64 - 1-11/32, Grip length 13/16 | EA |
| AN5-12A | BOLT HEX HEAD ALLOY STEEL CAD 2 UNDRILLED, Thread size 5/16-24, Length +/- 1/64 - 1-11/32, Grip length 13/16 | EA |
| AN5-13A | Bolt, Airframe, 5/16-24 Thread, 15/16" Grip, 1-15/32" Length, Undrilled Shank, Steel Cad II Plating | EA |
| AN5-14 | Bolt, Airframe, 5/16-24 Thread, 1-1/16" Grip, 1-19/32" Length, Drilled Shank, Steel Cad II Plating | EA |
| AN5-14A | Bolt, Airframe, 5/16-24 Thread, 1-1/16" Grip, 1-19/32" Length, Undrilled Shank, Steel Cad II Plating | EA |
| AN5-15 | Bolt, Airframe, 5/16-24 Thread, 1-3/16" Grip, 1-23/32" Length, Drilled Shank, Steel Cad II Plating | EA |
| AN5-15A | Bolt, Airframe, 5/16-24 Thread, 1-3/16" Grip, 1-23/32" Length, Undrilled Shank, Steel Cad II Plating | EA |
| AN5-16 | Bolt, Airframe, 5/16-24 Thread, 1-5/16" Grip, 1-27/32" Length, Drilled Shank, Steel Cad II Plating | EA |

| Part Number | Part Description | Unit of Measure |
|-------------|---|-----------------|
| AN5-16A | Bolt, Airframe, 5/16-24 Thread, 1-5/16" Grip, 1-27/32" Length, Undrilled Shank, Steel Cad II Plating | EA |
| AN5-17 | Bolt, Airframe, 5/16-24 Thread, 1-7/16" Grip, 1-31/32" Length, Drilled Shank, Steel Cad II Plating | EA |
| AN5-17A | Bolt, Airframe, 5/16-24 Thread, 1-7/16" Grip, 1-31/32" Length, Undrilled Shank, Steel Cad II Plating | EA |
| AN5-20 | Bolt, Airframe, 5/16-24 Thread, 1-9/16" Grip, 2-3/32" Length, Drilled Shank, Steel Cad II Plating | EA |
| AN520-10R22 | Screw, Pan Head Machine, 10-32 Thread, 1-3/8" Length, Non-Structural | EA |
| AN520-10R9 | Screw, Pan Head, Machine, Non-Structural, 10-32 Thread | EA |
| AN5-20A | Bolt, Airframe, 5/16-24 Thread, 1-9/16" Grip, 2-3/32" Length, Undrilled Shank, Steel Cad II Plating | EA |
| AN5-21 | Bolt, Airframe, 5/16-24 Thread, 1-11/16" Grip, 2-7/32" Length, Drilled Shank, Steel Cad II Plating | EA |
| AN5-21A | Bolt, Airframe, 5/16-24 Thread, 1-11/16" Grip, 2-7/32" Length, Undrilled Shank, Steel Cad II Plating | EA |
| AN5-22 | Bolt, Airframe, 5/16-24 Thread, 1-13/16" Grip, 2-11/32" Length, Drilled Shank, Steel Cad II Plating | EA |
| AN5-22A | Bolt, Airframe, 5/16-24 Thread, 1-13/16" Grip, 2-11/32" Length, Undrilled Shank, Steel Cad II Plating | EA |
| AN5-23 | Bolt, Airframe, 5/16-24 Thread, 1-15/16" Grip, 2-15/32" Length, Drilled Shank, Steel Cad II Plating | EA |
| AN5-23A | Bolt, 5/16-24 Thread, 1.938 Grip, 2-3/8" Length, Undrilled Shank | EA |
| AN5-24A | Bolt, Airframe, 5/16-24 Thread, 2-1/16" Grip, 2-19/32" Length, Undrilled Shank, Steel Cad II Plating | EA |
| AN5-25 | Bolt, Airframe, 5/16-24 Thread, 2-3/16" Grip, 2-23/32" Length, Drilled Shank, Steel Cad II Plating | EA |
| AN525-10R10 | Screw, Washer Head, 10-32 Thread, 7/32" Grip, 5/8" Length, Structural, Alloy Steel | EA |
| AN525-10R11 | Screw, Washer Head, 10-32 Thread, 9/32" Grip, 11/16" Length, Structural, Alloy Steel | EA |
| AN525-10R12 | Screw, Washer Head, 10-32 Thread, 11/32" Grip, 3/4" Length, Structural, Alloy Steel | EA |
| AN525-10R14 | Screw, Washer Head, 10-32 Thread, 15/32" Grip, 7/8" Length, Structural, Alloy Steel | EA |
| AN525-10R16 | Screw, Washer Head, 10-32 Thread, 19/32" Grip, 1" Length, Structural, Alloy Steel | EA |
| AN525-10R18 | Screw, Washer Head, 10-32 Thread, 23/32" Grip, 1-1/8" Length, Structural, Alloy Steel | EA |
| AN525-10R20 | Screw, Washer Head, 10-32 Thread, 27/32" Grip, 1-1/4" Length, Structural, Alloy Steel | EA |
| AN525-10R24 | Screw, Washer Head, 10-32 Thread, 1-3/32" Grip, 1-1/2" Length, Structural, Alloy Steel | EA |
| AN525-10R28 | Screw, Washer Head, 10-32 Thread, 1-11/32" Grip, 1-3/4" Length, Structural, Alloy Steel | EA |
| AN525-10R6 | Screw, Washer Head, 10-32 Thread, 1/32" Grip, 3/8" Length, Structural, Alloy Steel | EA |
| AN525-10R7 | Screw, Washer Head, 10-32 Thread, 1/16" Grip, 7/16" Length, Structural, Alloy Steel | EA |
| AN525-10R8 | Screw, Washer Head, 10-32 Thread, 1/8" Grip, 1/2" Length, Structural, Alloy Steel | EA |
| AN525-10R9 | Screw, Washer Head, 10-32 Thread, 5/32" Grip, 9/16" Length, Structural, Alloy Steel | EA |

| Part Number | Part Description | Unit of Measure |
|---------------|--|-----------------|
| AN525-416-18 | Screw, Washer Head, Structural, 1/4-28 Thread, 23/32 Grip | EA |
| AN525-416R10 | Screw, Washer Head, 1/4-28 Thread, 7/32" Grip, 5/8" Length, Sturctural, Alloy Steel | EA |
| AN525-416R16 | Screw, Washer Head, 1/4-28 Thread, 19/32" Grip, 1" Length, Sturctural, Alloy Steel | EA |
| AN525-416R18 | Screw, Washer Head, 1/4-28 Thread, 23/32" Grip, 1-1/8" Length, Sturctural, Alloy Steel | EA |
| AN525-416R20 | Screw, Washer Head, Structural, 1/4-28 Thread, 27/32 Grip | EA |
| AN525-416R24 | Screw, Washer Head, 1/4-28 Thread, 1-3/32" Grip, 1-1/2" Length, Sturctural, Alloy Steel | EA |
| AN525-416R28 | Screw, Washer Head, 1/4-28 Thread, 1-3/8" Grip, 1-3/4" Length, Sturctural, Alloy Steel | EA |
| AN525-416R8 | Screw, Washer Head, 1/4-28 Thread, 1/8" Grip, 1/2" Length, Sturctural, Alloy Steel | EA |
| AN525-416R9 | Screw, Washer Head, 1/4-28 Thread, 5/32" Grip, 9/16" Length, Sturctural, Alloy Steel | EA |
| AN525-832R10 | Screw, Washer Head, 8-32 Thread, 7/32" Grip, 5/8" Length, Sturctural, Alloy Steel | EA |
| AN525-832R12 | Screw, Washer Head, 8-32 Thread, 11/32" Grip, 3/4" Length, Sturctural, Alloy Steel | EA |
| AN525-832R16 | Screw, Washer Head, 8-32 Thread, 19/32" Grip, 1" Length, Sturctural, Alloy Steel | EA |
| AN525-832R22 | Screw, Washer Head, 8-32 Thread, 31/32" Grip, 1-3/8" Length, Sturctural, Alloy Steel | EA |
| AN525-832R24 | Screw, Washer Head, 8-32 Thread, 1-6/32" Grip, 1-1/2" Length, Sturctural, Alloy Steel | EA |
| AN525-832R6 | Screw, Washer Head, 8-32 Thread, 1/32" Grip, 3/8" Length, Sturctural, Alloy Steel | EA |
| AN525-832R7 | Screw, Washer Head, 8-32 Thread, 1/16" Grip, 7/16" Length, Sturctural, Alloy Steel | EA |
| AN525-832R8 | Screw, Washer Head, 8-32 Thread, 1/8" Grip, 1/2" Length, Sturctural, Alloy Steel | EA |
| AN525-832R9 | Screw, Washer Head, 8-32 Thread, 5/32" Grip, 9/16" Length, Sturctural, Alloy Steel | EA |
| AN525-836R12 | Screw, Washer Head, 8-36 Thread, 11/32" Grip, 3/4" Length, Sturctural, Alloy Steel | EA |
| AN525-8R11 | Screw, Washer Head, 8-32 Thread, 9/32" Grip, 11/16" Length, Sturctural, Alloy Steel | EA |
| AN525-8R14 | Screw, Washer Head, 8-32 Thread, 15/32" Grip, 7/8" Length, Sturctural, Alloy Steel | EA |
| AN5-25A | Bolt, 5/16-24 Thread, 2-3/16" Grip, 2.719" Overall Length | EA |
| AN5-26 | Bolt, Airframe, 5/16-24 Thread, 2-5/16" Grip, 2-27/32" Length, Drilled Shank, Steel Cad II Plating | EA |
| AN526-1032R10 | Screw, Truss Head Machine, 10-32 Thread, 5/8" Length, Non-Sturctural, Carbon Steel | EA |
| AN526-1032R12 | Screw, Truss Head, Non Structural, Cad 1, 10-32 3/4 CADMIUM | EA |
| AN526-1032R12 | Screw, Truss Head, Non Structural, Cad 1, 10-32 3/4 CADMIUM | EA |
| AN526-1032R14 | Screw, Truss Head Machine, 10-32 Thread, 7/8" Length, Non-Sturctural, Carbon Steel | EA |
| AN526-1032R16 | Screw, Truss Head Machine, 10-32 Thread, 1" Length, Non-Sturctural, Carbon Steel | EA |
| AN526-1032R28 | Screw, Truss Head Machine, 10-32 Thread, 1-3/4" Length, Non-Sturctural, Carbon Steel | EA |

| Part Number | Part Description | Unit of Measure |
|---------------|--|-----------------|
| AN526-1032R28 | Screw, Truss Head Machine, 10-32 Thread, 1-3/4" Length, Non-Structural, Carbon Steel | EA |
| AN526-1032R4 | Screw, Truss Head Machine, 10-32 Thread, 1/4" Length, Non-Structural, Carbon Steel | EA |
| AN526-1032R6 | Screw, Truss Head Machine, 10-32 Thread, 3/8" Length, Non-Structural, Carbon Steel | EA |
| AN526-1032R8 | Screw, Truss Head, Non Structural, Cad 1, Steel | EA |
| AN526-1032R8 | Screw, Truss Head, Non Structural, Cad 1, Steel | EA |
| AN526-428R8 | Screw, Truss Head Machine, 4-28 Thread, 1/2" Length, Non-Structural, Carbon Steel | EA |
| AN526-440R8 | Screw, Truss Head Machine, 4-40 Thread, 1/2" Length, Non-Structural, Carbon Steel | EA |
| AN526-632R10 | Screw, Truss Head Machine, 6-32 Thread, 5/8" Length, Non-Structural, Carbon Steel | EA |
| AN526-632R12 | Screw, Truss Head Machine, 6-32 Thread, 3/4" Length, Non-Structural, Carbon Steel | EA |
| AN526-632R14 | Screw, Truss Head Machine, 6-32 Thread, 7/8" Length, Non-Structural, Carbon Steel | EA |
| AN526-632R16 | Screw, Truss Head Machine, 6-32 Thread, 1" Length, Non-Structural, Carbon Steel | EA |
| AN526-632R20 | Screw, Truss Head Machine, 6-32 Thread, 1-1/4" Length, Non-Structural, Carbon Steel | EA |
| AN526-632R4 | Screw, Truss Head, Non Structural, Cad 1 | EA |
| AN526-632R4 | Screw, Truss Head, Non Structural, Cad 1 | EA |
| AN526-632R5 | Screw, Truss Head Machine, 6-32 Thread, 5/16" Length, Non-Structural, Carbon Steel | EA |
| AN526-632R6 | Screw Truss Head, Non Structural Cad 1 | EA |
| AN526-632R6 | Screw Truss Head, Non Structural Cad 1 | EA |
| AN526-632R7 | Screw, Truss Head Machine, 6-32 Thread, 7/16" Length, Non-Structural, Carbon Steel | EA |
| AN526-632R8 | Screw, Truss Head Machine, 6-32 Thread, 1/2" Length, Non-Structural, Carbon Steel | EA |
| AN526-832R10 | Screw, Truss Head, Non Structural, Cad 1, 8-32 5/8 CADMIUM | EA |
| AN526-832R10 | Screw, Truss Head, Non Structural, Cad 1, 8-32 5/8 CADMIUM | EA |
| AN526-832R10 | Screw, Truss Head, Non Structural, Cad 1, 8-32 5/8 CADMIUM | EA |
| AN526-832R12 | Screw, Truss Head, Non Structural, Cad 1, 8-32 3/4 CADMIUM | EA |
| AN526-832R12 | Screw, Truss Head, Non Structural, Cad 1, 8-32 3/4 CADMIUM | EA |
| AN526-832R12 | Screw, Truss Head, Non Structural, Cad 1, 8-32 3/4 CADMIUM | EA |
| AN526-832R14 | Screw, Truss Head Machine, 8-32 Thread, 7/8" Length, Non-Structural, Carbon Steel | EA |
| AN526-832R16 | Screw, Truss Head Machine, 8-32 Thread, 1" Length, Non-Structural, Carbon Steel | EA |
| AN526-832R24 | Screw, Truss Head Machine, 8-32 Thread, 1-1/26" Length, Non-Structural, Carbon Steel | EA |
| AN526-832R4 | Screw, Truss Head Machine, 8-32 Thread, 1/4" Length, Non-Structural, Carbon Steel | EA |
| AN526-832R6 | Screw, Truss Head, Non Structural, Cad 1, 8-32 3/8 CADMIUM | EA |
| AN526-832R6 | Screw, Truss Head, Non Structural, Cad 1, 8-32 3/8 CADMIUM | EA |
| AN526-832R8 | Screw, Washer Head, 8-32 Thread, 1/8" Grip, 1/2" Length, Structural, Alloy Steel | EA |
| AN526-832R8 | Screw, Washer Head, 8-32 Thread, 1/8" Grip, 1/2" Length, Structural, Alloy Steel | EA |

| Part Number | Part Description | Unit of Measure |
|---------------|--|-----------------|
| AN526-832R9 | Screw, Truss Head Machine, 8-32 Thread, 9/16" Length, Non-Sturctural, Carbon Steel | EA |
| AN5-26A | Bolt, Airframe, 5/16-24 Thread, 2-5/16" Grip, 2-27/32" Length, Undrilled Shank, Steel Cad II Plating | EA |
| AN526C1032R12 | Screw, Truss Head Machine, 10-32 Thread, 3/4" Length, Non-Sturctural, Corrosion Resistant | EA |
| AN526C1032R16 | Screw, Truss Head Machine, 10-32 Thread, 1" Length, Non-Sturctural, Corrosion Resistant | EA |
| AN526C1032R18 | Screw, Truss Head Machine, 10-32 Thread, 1-1/8" Length, Non-Sturctural, Corrosion Resistant | EA |
| AN526C1032R6 | Screw, Truss Head Machine, 10-32 Thread, 3/8" Length, Non-Sturctural, Corrosion Resistant | EA |
| AN526C1032R8 | Screw, Truss Head Machine, 10-32 Thread, 1/2" Length, Non-Sturctural, Corrosion Resistant | EA |
| AN526C632R10 | Screw, Truss Head Machine, 6-32 Thread, 5/8" Length, Non-Sturctural, Corrosion Resistant | EA |
| AN526C632R12 | Screw, Truss Head Machine, 6-32 Thread, 3/4" Length, Non-Sturctural, Corrosion Resistant | EA |
| AN526C632R14 | Screw, Truss Head Machine, 6-32 Thread, 7/8" Length, Non-Sturctural, Corrosion Resistant | EA |
| AN526C632R16 | Screw, Truss Head Machine, 6-32 Thread, 1" Length, Non-Sturctural, Corrosion Resistant | EA |
| AN526C632R24 | Screw, Truss Head Machine, 6-32 Thread, 3/4" Length, Non-Sturctural, Corrosion Resistant | EA |
| AN526C632R24 | Screw, Truss Head Machine, 6-32 Thread, 3/4" Length, Non-Sturctural, Corrosion Resistant | EA |
| AN526C632R4 | Screw, Truss Head Machine, 6-32 Thread, 1/4" Length, Non-Sturctural, Corrosion Resistant | EA |
| AN526C632R6 | Screw, Truss Head Machine, 6-32 Thread, 3/8" Length, Non-Sturctural, Corrosion Resistant | EA |
| AN526C632R8 | Screw, Truss Head Machine, 6-32 Thread, 1/2" Length, Non-Sturctural, Corrosion Resistant | EA |
| AN526C832R10 | Screw, Truss Head Machine, 6-32 Thread, 5/8" Length, Non-Sturctural, Corrosion Resistant | EA |
| AN526C832R12 | Screw, Truss Head Machine, 8-32 Thread, 3/4" Length, Non-Sturctural, Corrosion Resistant | EA |
| AN526C832R14 | Screw, Truss Head Machine, 8-32 Thread, 7/8" Length, Non-Sturctural, Corrosion Resistant | EA |
| AN526C832R16 | Screw, Truss Head Machine, 8-32 Thread, 1" Length, Non-Sturctural, Corrosion Resistant | EA |
| AN526C832R24 | Screw, Truss Head Machine, 8-32 Thread, 1-1/2" Length, Non-Sturctural, Corrosion Resistant | EA |
| AN526C832R8 | Screw, Truss Head Machine, 8-32 Thread, 1/2" Length, Non-Sturctural, Corrosion Resistant | EA |
| AN5-27A | Bolt, Airframe, 5/16-24 Thread, 2-7/16" Grip, 2-31/32" Length, Undrilled Shank, Steel Cad II Plating | EA |
| AN530-4R4 | Screw, Tapping, Pan Head, No. 4 DIA, 1/4" Length | EA |
| AN5-30A | Bolt, Airframe, 5/16-24 Thread, 2-9/16" Grip, 3-3/32" Length, Undrilled Shank, Steel Cad II Plating | EA |
| AN531-10R8 | Screw | EA |
| AN531-6R6 | Screw | EA |
| AN531-6R8 | Screw | EA |
| AN531-8R6 | Screw | EA |

| Part Number | Part Description | Unit of Measure |
|--------------|---|-----------------|
| AN531-8R8 | Screw | EA |
| AN5-31A | Bolt, Airframe, 5/16-24 Thread, 2-11/16" Grip, 3-7/32" Length, Undrilled Shank, Steel Cad II Plating | EA |
| AN5-32A | Bolt, Airframe, 5/16-24 Thread, 2-13/16" Grip, 3-11/32" Length, Undrilled Shank, Steel Cad II Plating | EA |
| AN5-33A | Bolt, Steel, 5/16-24 Thread, 2.938" Grip, 3.469" Overall Length, No Shank Hole | EA |
| AN5-34A | Bolt, Airframe, 5/16-24 Thread, 3-1/16" Grip, 3-19/32" Length, Undrilled Shank, Steel Cad II Plating | EA |
| AN5-35A | Bolt, Airframe, 5/16-24 Thread, 3-3/16" Grip, 3-23/32" Length, Undrilled Shank, Steel Cad II Plating | EA |
| AN5-35A | Bolt, Airframe, 5/16-24 Thread, 3-3/16" Grip, 3-23/32" Length, Undrilled Shank, Steel Cad II Plating | EA |
| AN5-36A | Bolt, Airframe, 5/16-24 Thread, 3-5/16" Grip, 3-27/32" Length, Undrilled Shank, Steel Cad II Plating | EA |
| AN5-37A | Bolt, Airframe, 5/16-24 Thread, 3-7/16" Grip, 3-31/32" Length, Undrilled Shank, Steel Cad II Plating | EA |
| AN5-4 | Bolt, Airframe, 5/16-24 Thread, 7/16" Grip, 31/32" Length, Drilled Shank, Steel Cad II Plating | EA |
| AN5-40A | Bolt, Airframe, 5/16-24 Thread, 3-9/16" Grip, 4-3/32" Length, Undrilled Shank, Steel Cad II Plating | EA |
| AN5-42A | Bolt, 5/16-24 Thread, 3.813" Grip, 4.344" Overall Length, No Hole Shank | EA |
| AN5-42A | Bolt, 5/16-24 Thread, 3.813" Grip, 4.344" Overall Length, No Hole Shank | EA |
| AN5-47A | Bolt | EA |
| AN5-4A | Bolt, Airframe, 5/16-24 Thread, 7/16" Grip, 31/32" Length, Undrilled Shank, Steel Cad II Plating | EA |
| AN5-5 | Bolt, Airframe, 5/16-24 Thread, 3/16" Grip, 23/32" Length, Drilled Shank, Steel Cad II Plating | EA |
| AN5-51A | Bolt | EA |
| AN5-5A | Bolt, Airframe, 5/16-24 Thread, 3/16" Grip, 23/32" Length, Undrilled Shank, Steel Cad II Plating | EA |
| AN5-6 | Bolt, Airframe, 5/16-24 Thread, 5/16" Grip, 27/32" Length, Drilled Shank, Steel Cad II Plating | EA |
| AN5-60A | Bolt, Airframe, 5/16-24 Thread, 5-9/16" Grip, 6-3/32" Length, Undrilled Shank, Steel Cad II Plating | EA |
| AN5-62A | Bolt, Airframe, 5/16-24 Thread, 5-13/16" Grip, 6-11/32" Length, Undrilled Shank, Steel Cad II Plating | EA |
| AN565B2H3 | Set Screw, Hexagon Socket Head, 1-16- Thread, 3/16" Length | EA |
| AN565B428H4 | Set Screw, Hexagon Socket Head, 1/4-28 Thread, 1/4" Length | EA |
| AN565D1032H6 | Set Screw, Hexagon Socket Head, 10-32 Thread, 3/8" Length, Cup Point | EA |
| AN565D832H5 | Set Screw, Hexagon Socket Head, 8-32 Thread, 5/16" Length, Cup Point | EA |
| AN565D8H2 | Set Screw, Hexagon Socket Head, 8-32 Thread, 1/8" Length, Cup Point | EA |
| AN5-6A | Bolt, Airframe, 5/16-24 Thread, 5/16" Grip, 27/32" Length, Undrilled Shank, Steel Cad II Plating | EA |
| AN5-7 | Bolt, Airframe, 5/16-24 Thread, 7/16" Grip, 31/32" Length, Drilled Shank, Steel Cad II Plating | EA |
| AN5-7A | Bolt, Airframe, 5/16-24 Thread, 7/16" Grip, 31/32" Length, Undrilled Shank, Steel Cad II Plating | EA |
| AN5C14A | Bolt, 0.31 - 24 X 1.59, Large, Stainless Steel | EA |
| AN5C21A | Bolt, Airframe, Corrosion Resistant, 5/16-24 Thread, 1-11/16" Grip, 2-7/32" Length, Undrilled Shank | EA |
| AN5H10A | Bolt, Airframe, 5/16-24 Thread, 9/16" Grip, 1-3/32" Length, Drilled Head, Undrilled Shank, Steel Cad II Plating | EA |

| Part Number | Part Description | Unit of Measure |
|-------------|---|-----------------|
| AN5H20A | Bolt, Airframe, 5/16-24 Thread, 1-9/16" Grip, 2-3/32" Length, Drilled Head, Undrilled Shank, Steel Cad II Plating | EA |
| AN5H22A | Bolt, Airframe, 5/16-24 Thread, 1-13/16" Grip, 2-11/32" Length, Drilled Head, Undrilled Shank, Steel Cad II Plating | EA |
| AN6-10 | Bolt, Airframe, 3/8-24 Thread, 7/16" Grip, 1-5/64" Length, Drilled Shank | EA |
| AN6-10A | Bolt, Airframe, 3/8-24 Thread, 7/16" Grip, 1-5/64" Length, Undrilled Shank | EA |
| AN6-11 | Bolt, Drilled Shank, 3/8-24 Thread, 1.49 Grip | EA |
| AN6-11A | BOLT HEX HEAD ALLOY STEEL CAD 2 DRILLED SHANK, Thread size 3/8-24, Length +/- 1/64 - 1-13/64, Grip length 9/16 | EA |
| AN6-11A | BOLT HEX HEAD ALLOY STEEL CAD 2 DRILLED SHANK, Thread size 3/8-24, Length +/- 1/64 - 1-13/64, Grip length 9/16 | EA |
| AN6-12A | Bolt, Airframe, 3/8-24 Thread, 11/16" Grip, 1-21/64" Length, Undrilled Shank | EA |
| AN6-13 | Bolt, Airframe, 3/8-24 Thread, 13/16" Grip, 1-29/64" Length, Drilled Shank | EA |
| AN6-13A | BOLT HEX HEAD ALLOY STEEL CAD 2 DRILLED SHANK, Thread size 3/8-24, Length +/- 1/64 - 1-29/64, Grip length 13/16 | EA |
| AN6-13A | BOLT HEX HEAD ALLOY STEEL CAD 2 DRILLED SHANK, Thread size 3/8-24, Length +/- 1/64 - 1-29/64, Grip length 13/16 | EA |
| AN6-14 | Bolt, Airframe, 3/8-24 Thread, 15/16" Grip, 1-37/64" Length, Drilled Shank | EA |
| AN6-14A | Bolt, Airframe, 3/8-24 Thread, 15/16" Grip, 1-37/64" Length, Undrilled Shank | EA |
| AN6-15 | Bolt, Airframe, 3/8-24 Thread, 1-1/16" Grip, 1-45/64" Length, Drilled Shank | EA |
| AN6-15A | Bolt, Airframe, 3/8-24 Thread, 1-1/16" Grip, 1-45/64" Length, Undrilled Shank | EA |
| AN6-16A | Bolt, Steel, 3/8-24 Thread, Grip 1.188", CAD 2 Plating, No Head or Shank Holes | EA |
| AN6-17 | Bolt, Airframe, 3/8-24 Thread, 1-5/16" Grip, 1-61/64" Length, Drilled Shank | EA |
| AN6-17A | Bolt, Airframe, 3/8-24 Thread, 1-5/16" Grip, 1-61/64" Length, Undrilled Shank | EA |
| AN6-20 | Bolt, Airframe, 3/8-24 Thread, 1-7/16" Grip, 2-5/64 Length, Drilled Shank | EA |
| AN6207-4 | Check Valve | EA |
| AN6-20A | Bolt, Airframe, 3/8-24 Thread, 1-7/16" Grip, 2-5/64 Length, Undrilled Shank | EA |
| AN6-21A | Bolt, Airframe, 3/8-24 Thread, 1-9/16" Grip, 2-13/64 Length, Undrilled Shank | EA |
| AN6-22 | Bolt, Airframe, 3/8-24 Thread, 1-11/16" Grip, 2-21/64" Length, Drilled Shank | EA |
| AN6-22A | Bolt, Airframe, 3/8-24 Thread, 1-11/16" Grip, 2-21/64" Length, Undrilled Shank | EA |
| AN6-23 | Bolt, Airframe, 3/8-24 Thread, 1-13/16" Grip, 2-29/64 Length, Drilled Shank | EA |
| AN6-23A | Bolt, Airframe, 3/8-24 Thread, 1-13/16" Grip, 2-29/64" Length, Undrilled Shank, Carbon Steel | EA |
| AN6-23A | Bolt, Airframe, 3/8-24 Thread, 1-13/16" Grip, 2-29/64" Length, Undrilled Shank, Carbon Steel | EA |
| AN6-24A | Bolt, Airframe, 3/8-24 Thread, 1-15/16" Grip, 2-37/64 Length, Undrilled Shank | EA |
| AN6-25 | Bolt, Airframe, 3/8-24 Thread, 2-1/16" Grip, 2-45/64 Length, Drilled Shank | EA |
| AN6-25A | Bolt, Airframe, 3/8-24 Thread, 2-1/16" Grip, 2-45/64 Length, Undrilled Shank | EA |
| AN6-26 | Bolt, Airframe, 3/8-24 Thread, 2-3/16" Grip, 2-53/64 Length, Drilled Shank | EA |
| AN6-26A | BOLT HEX HEAD ALLOY STEEL CAD 2 DRILLED SHANK, Thread size 3/8-24, Length +/- 1/64 - 2-53/64, Grip length 2-3/16 | EA |
| AN6-26A | BOLT HEX HEAD ALLOY STEEL CAD 2 DRILLED SHANK, Thread size 3/8-24, Length +/- 1/64 - 2-53/64, Grip length 2-3/16 | EA |
| AN6-27 | Bolt, Airframe, 3/8-24 Thread, 2-5/16" Grip, 2-61/64 Length, Drilled Shank | EA |
| AN6-27A | Bolt, Airframe, 3/8-24 Thread, 2-5/16" Grip, 2-61/64 Length, Undrilled Shank | EA |
| AN6287-1 | Valve, Air, Assmebly | EA |
| AN6289D8 | Nut | EA |
| AN6289J5 | Nut | EA |
| AN6-30 | Bolt, Drilled Shank, 3/8-24 Thread, 3.39 Grip | EA |
| AN6-30A | Bolt, Airframe, 3/8-24 Thread, 2-7/16" Grip, 3-5/64 Length, Undrilled Shank | EA |

| Part Number | Part Description | Unit of Measure |
|-------------|--|-----------------|
| AN6-31 | Bolt, Airframe, 3/8-24 Thread, 2-9/16" Grip, 3-13/64 Length, Drilled Shank | EA |
| AN6-31A | Bolt, Airframe, 3/8-24 Thread, 2-9/16" Grip, 3-13/64 Length, Undrilled Shank | EA |
| AN6-32 | Bolt, Airframe, 3/8-24 Thread, 2-11/16" Grip, 3-21/64 Length, Drilled Shank | EA |
| AN6-32A | Bolt, Airframe, 3/8-24 Thread, 2-11/16" Grip, 3-21/64 Length, Undrilled Shank | EA |
| AN6-33 | Bolt, Airframe, 3/8-24 Thread, 3-29/64 Length, 2-13/16 Grip, Drilled Shank | EA |
| AN6-33 | Bolt, Airframe, 3/8-24 Thread, 3-29/64 Length, 2-13/16 Grip, Drilled Shank | EA |
| AN6-33A | Bolt, Airframe, 3/8-24 Thread, 2-13/16" Grip, 3-29/64 Length, Undrilled Shank | EA |
| AN6-34A | Bolt, 3/8-24 Thread, Steel, 2.938" Grip, Hole in Head, Hole in Shank | EA |
| AN6-35A | Bolt, Airframe, 3/8-24 Thread, 3-1/16" Grip, 3-45/64 Length, Undrilled Shank | EA |
| AN6-35A | Bolt, Airframe, 3/8-24 Thread, 3-1/16" Grip, 3-45/64 Length, Undrilled Shank | EA |
| AN6-36A | Bolt, Airframe, 3/8-24 Thread, 3-3/16" Grip, 3-53/64 Length, Undrilled Shank | EA |
| AN6-37A | Bolt, Airframe, 3/8-24 Thread, 3-5/16" Grip, 3-61/64 Length, Undrilled Shank | EA |
| AN6-40A | Bolt, Airframe, 3/8-24 Thread, 3-7/16" Grip, 4-5/64" Length, Undrilled Shank, Carbon Steel | EA |
| AN6-40A | Bolt, Airframe, 3/8-24 Thread, 3-7/16" Grip, 4-5/64" Length, Undrilled Shank, Carbon Steel | EA |
| AN6-41A | Bolt, Airframe, 3/8-24 Thread, 3-9/16" Grip, 4-13/64 Length, Undrilled Shank | EA |
| AN6-42 | Bolt, Airframe, 3/8-24 Thread, 3-11/16" Grip, 4-21/64 Length, Drilled Shank | EA |
| AN6-42A | Bolt, Steel, 3/8-24 Thread, Grip 3.688", CAD 2 Plating, No Head or Shank Holes | EA |
| AN6-43A | Bolt, Airframe, 3/8-24 Thread, 3-13/16" Grip, 4-29/64 Length, Undrilled Shank | EA |
| AN6-44A | Bolt, Airframe, 3/8-24 Thread, 3-3/16" Grip, 3-53/64 Length, Undrilled Shank | EA |
| AN6-45A | Bolt, Airframe, 3/8-24 Thread, 3-15/16" Grip, 4-37/64 Length, Undrilled Shank | EA |
| AN6-46A | Bolt, Airframe, 3/8-24 Thread, 4-3/16" Grip, 4-53/64 Length, Undrilled Shank | EA |
| AN6-47A | Bolt, Airframe, 3/8-24 Thread, 4-5/16" Grip, 4-61/64 Length, Undrilled Shank | EA |
| AN6-4A | Bolt | EA |
| AN6-50 | Bolt, Airframe, 3/8-24 Thread, 4-7/16" Grip, 5-5/64 Length, Drilled Shank | EA |
| AN6-50A | Bolt, Airframe, 3/8-24 Thread, 4-7/16" Grip, 5-5/64 Length, Undrilled Shank | EA |
| AN6-51A | Bolt, Airframe, 3/8-24 Thread, 4-9/16" Grip, 5-13/64 Length, Undrilled Shank | EA |
| AN6-55A | Bolt, Airframe, 3/8-24 Thread, 5-1/16" Grip, 5-45/64 Length, Undrilled Shank | EA |
| AN6-56A | Bolt, Airframe, 3/8-24 Thread, 5-3/16" Grip, 5-53/64 Length, Undrilled Shank | EA |
| AN6-5A | Bolt, Airframe, 3/8-24 Thread, 1/16" Grip, 45/64" Length, Undrilled Shank | EA |
| AN6-6 | Bolt, Airframe, 3/8-24 Thread, 3/16" Grip, 53/64" Length, Drilled Shank | EA |
| AN665-115L | Tie Rod, Clevis, Thread 3/8-24, LH | EA |
| AN665-115LS | Tie Rod, Clevis, Thread 3/8-24, LH, Stainless Steel | EA |
| AN665-115R | Tie Rod, Clevis, Thread 3/8-24, RH | EA |
| AN665-115RS | Tie Rod, Clevis, Thread 3/8-24, RH, Stainless Steel | EA |
| AN665-155L | Tie Rod, Clevis, Thread 1/2-13, LH | EA |
| AN6-6A | Bolt, Airframe, 3/8-24 Thread, 3/16" Grip, 53/64" Length, Undrilled Shank | EA |
| AN6-7 | Bolt, Airframe, 3/8-24 Thread, 5/16" Grip, 61/64" Length, Drilled Shank | EA |
| AN6-7A | Bolt, Airframe, 3/8-24 Thread, 5/16" Grip, 61/64" Length, Undrilled Shank | EA |
| AN6C11A | Bolt, Airframe, Corrosion Resistant, 3/8-24 Thread, 9/16" Grip, 1-13/64" Length, Undrilled Shank | EA |
| AN6C12A | Bolt, Airframe, Corrosion Resistant, 3/8-24 Thread, 11/16" Grip, 1-21/64" Length, Undrilled Shank | EA |
| AN6C33A | Bolt, Airframe, Corrosion Resistant, 3/8-24 Thread, 2-13/16" Grip, 3-29/64 Length, Undrilled Shank | EA |
| AN6C36A | Bolt, Airframe, Corrosion Resistant, 3/8-24 Thread, 3-3/16" Grip, 3-53/64 Length, Undrilled Shank | EA |

| Part Number | Part Description | Unit of Measure |
|-------------|--|-----------------|
| AN6H15A | Bolt, Airframe, 3/8-24 Thread, 1-1/16" Grip, 1-45/32" Length, Drilled Head, Undrilled Shank, Steel Cad II Plating | EA |
| AN6H44A | Bolt, Airframe, 3/8-24 Thread, 3-15/16" Grip, 4-37/64" Length, Drilled Head, Undrilled Shank, Steel Cad II Plating | EA |
| AN7-10 | Bolt, Airframe, 7/16-20 Thread, 7/16" Grip, 1-3/32" Length, Drilled Shank | EA |
| AN7-10A | Bolt, Airframe, 7/16-20 Thread, 7/16" Grip, 1-3/32" Length, Undrilled Shank | EA |
| AN7-12 | Bolt, Airframe, 7/16-20 Thread, 11/16" Grip, 1-11/32" Length, Drilled Shank | EA |
| AN7-12A | Bolt, Airframe, 7/16-20 Thread, 11/16" Grip, 1-11/32" Length, Undrilled Shank | EA |
| AN7-13A | Bolt, Airframe, 7/16-20 Thread, 13/16" Grip, 1-15/32" Length, Undrilled Shank | EA |
| AN7-14 | Bolt, Airframe, 7/16-20 Thread, 15/16" Grip, 1-19/32" Length, Drilled Shank | EA |
| AN7-14A | Bolt, Airframe, 7/16-20 Thread, 15/16" Grip, 1-19/32" Length, Undrilled Shank | EA |
| AN7-16A | Bolt, Airframe, 7/16-20 Thread, 1-3/16" Grip, 1-27/32" Length, Undrilled Shank | EA |
| AN7-17A | Bolt, Airframe, 7/16-20 Thread, 1-5/16" Grip, 1-31/32" Length, Undrilled Shank | EA |
| AN7-20A | Bolt, Airframe, 7/16-20 Thread, 1-7/16" Grip, 2-3/32" Length, Undrilled Shank | EA |
| AN7-21 | Bolt, Airframe, 7/16-20 Thread, 1-9/16" Grip, 2-7/32" Length, Drilled Shank | EA |
| AN7-21A | Bolt, Airframe, 7/16-20 Thread, 1-9/16" Grip, 2-7/32" Length, Undrilled Shank | EA |
| AN7-22 | Bolt, Airframe, 7/16-20 Thread, 1-11/16" Grip, 2-11/32" Length, Drilled Shank | EA |
| AN7-22A | Bolt, Airframe, 7/16-20 Thread, 1-11/16" Grip, 2-11/32" Length, Undrilled Shank | EA |
| AN7-23A | Bolt, Airframe, 7/16-20 Thread, 1-13/16" Grip, 2-15/32" Length, Undrilled Shank | EA |
| AN7-24 | Bolt, Airframe, 7/16-20 Thread, 1-15/16" Grip, 2-19/32" Length, Drilled Shank | EA |
| AN7-24A | Bolt, Airframe, 7/16-20 Thread, 1-15/16" Grip, 2-19/32" Length, Undrilled Shank | EA |
| AN7-25A | Bolt, Airframe, 7/16-20 Thread, 2-1/16" Grip, 2-23/32" Length, Undrilled Shank | EA |
| AN7-26A | Bolt, Airframe, 7/16-20 Thread, 2-3/16" Grip, 2-27/32" Length, Undrilled Shank | EA |
| AN7-27 | Bolt, Airframe, 7/16-20 Thread, 2-5/16" Grip, 2-31/32" Length, Drilled Shank | EA |
| AN7-27A | Bolt, Airframe, 7/16-20 Thread, 2-5/16" Grip, 2-31/32" Length, Undrilled Shank | EA |
| AN7-30A | Bolt, Airframe, 7/16-20 Thread, 2-7/16" Grip, 3-3/32" Length, Undrilled Shank | EA |
| AN7-31A | Bolt, Airframe, 7/16-20 Thread, 2-9/16" Grip, 3-7/32" Length, Undrilled Shank | EA |
| AN7-32A | Bolt, Airframe, 7/16-20 Thread, 2-11/16" Grip, 3-11/32" Length, Undrilled Shank | EA |
| AN7-32A | Bolt, Airframe, 7/16-20 Thread, 2-11/16" Grip, 3-11/32" Length, Undrilled Shank | EA |
| AN7-33A | Bolt, Airframe, 7/16-20 Thread, 2-13/16" Grip, 3-15/32" Length, Undrilled Shank | EA |
| AN7-34A | Bolt, Airframe, 7/16-20 Thread, 2-15/16" Grip, 3-19/32" Length, Undrilled Shank | EA |
| AN7-35 | Bolt, Airframe, 7/16-20 Thread, 3-1/16" Grip, 3-23/32" Length, Drilled Shank | EA |
| AN7-35A | Bolt, Airframe, 7/16-20 Thread, 3-1/16" Grip, 3-23/32" Length, Undrilled Shank | EA |
| AN735D32 | Clamp | EA |
| AN735D36 | Clamp | EA |
| AN735D40 | Clamp | EA |
| AN7-36 | Bolt, Airframe, 7/16-20 Thread, 3-3/16" Grip, 3-27/32" Length, Drilled Shank | EA |

| Part Number | Part Description | Unit of Measure |
|-------------|---|-----------------|
| AN7-36A | Bolt, Airframe, 7/16-20 Thread, 3-3/16" Grip, 3-27/32" Length, Undrilled Shank | EA |
| AN7-37A | Bolt, Airframe, 7/16-20 Thread, 2-5/16" Grip, 2-31/32" Length, Undrilled Shank | EA |
| AN737TW22 | Hose Clamp, MIN DIA 7/16, MAX DIA 11/16 | EA |
| AN737TW91 | Hose Clamp, MIN DIA 2-13/32, MAX DIA 2-27/32, (AN737RM91) (U20-125-275SH) | EA |
| AN7-40A | Bolt, Airframe, 7/16-20 Thread, 3-7/16" Grip, 4-3/32" Length, Undrilled Shank | EA |
| AN7-41 | Bolt, Airframe, 7/16-20 Thread, 3-9/16" Grip, 4-7/32" Length, Drilled Shank | EA |
| AN7-42 | Bolt, Airframe, 7/16-20 Thread, 3-11/16" Grip, 4-11/32" Length, Drilled Shank | EA |
| AN742-10 | Clamp, Plain, Steel, To Fit 5/8" DIA | EA |
| AN742-12 | Clamp, Plain, Steel, To Fit 3/4" DIA | EA |
| AN742-16 | Clamp, Plain, Steel, To Fit 1" DIA | EA |
| AN742-8 | Clamp, Plain, Steel, To Fit 1/2" DIA | EA |
| AN742D10 | Clamp, Plain, Aluminum, To Fit 5/8" DIA | EA |
| AN742D11 | Clamp, Plain, Aluminum, To Fit 11/16" DIA | EA |
| AN742D11 | Clamp, Plain, Aluminum, To Fit 11/16" DIA | EA |
| AN742D12 | Clamp, Plain, Aluminum, To Fit 3/4" DIA | EA |
| AN742D12 | Clamp, Plain, Aluminum, To Fit 3/4" DIA | EA |
| AN742D3 | Clamp, Plain, To Fit DIA 3/16", Aluminum | EA |
| AN742D4 | Clamp, Plain, Aluminum, To Fit 1/4" DIA | EA |
| AN742D8 | Clamp, Plain, Aluminum, To Fit 1/2" DIA | EA |
| AN743-12 | Clamp, Plain, Steel, To Fit 3/4" DIA | EA |
| AN7-43A | Bolt, Airframe, 7/16-20 Thread, 3-13/16" Grip, 4-15/32" Length, Undrilled Shank | EA |
| AN7-44A | Bolt, Airframe, 7/16-20 Thread, 3-15/16" Grip, 4-19/32" Length, Undrilled Shank | EA |
| AN7-45A | Bolt, Airframe, 7/16-20 Thread, 4-1/16" Grip, 4-23/32" Length, Undrilled Shank | EA |
| AN7-46A | Bolt, Airframe, 7/16-20 Thread, 4-3/16" Grip, 4-27/32" Length, Undrilled Shank | EA |
| AN7-47A | Bolt, Airframe, 1/2-20 Thread, 4-3/16" Grip, 4-31/32" Length, Undrilled Shank | EA |
| AN7-50A | Bolt, Airframe, 1/2-20 Thread, 4-5/16" Grip, 5-3/32" Length, Undrilled Shank | EA |
| AN7-5A | Bolt, Airframe, 7/16-20 Thread, 1/16" Grip, 23/32" Length, Undrilled Shank | EA |
| AN7-6A | Bolt, 7/16-20 Thread, Steel, 0.188" Grip, 0.844" Overall Length, No Shank Hole | EA |
| AN7-6A | Bolt, 7/16-20 Thread, Steel, 0.188" Grip, 0.844" Overall Length, No Shank Hole | EA |
| AN7-7A | Bolt, Airframe, 7/16-20 Thread, 5/16" Grip, 31/32" Length, Undrilled Shank | EA |
| AN783-4 | Tee | EA |
| AN7C21A | Bolt (Maule M7) | EA |
| AN7H42A | Bolt, Airframe, 7/16-20 Thread, 3-11/16" Grip, 4-11/32" Length, Drilled Head, Undrilled Shank, Steel Cad II Plating | EA |
| AN804-6D | Tee, Flared Tube with Bulkhead on Run, 3/8" Tube DIA, 0.562-18 Thread, Aluminum | EA |
| AN805-2 | Nut | EA |
| AN806-6D | Plug, Flared Tube, 3/8" Tube DIA, 9/16-18 Thread, Aluminum | EA |
| AN806-8D | Plug, Flared Tube, 1/2" Tube DIA, 3/4-16 Thread, Aluminum | EA |
| AN807-8D | Adaptor, Straight, Tube to Hose, 1/2" Tube DIA, 3/4-16 Thread, Aluminum | EA |
| AN8-10 | Bolt, Airframe, 1/2-20 Thread, 5/16" Grip, 1-3/32" Length, Drilled Shank | EA |
| AN8-13A | Bolt, Airframe, 1/2-20 Thread, 11/16" Grip, 1-15/32" Length, Undrilled Shank | EA |
| AN8-14 | Bolt, Airframe, 1/2-20 Thread, 13/16" Grip, 1-19/32" Length, Drilled Shank | EA |
| AN814-16D | Plug | EA |

| Part Number | Part Description | Unit of Measure |
|-------------|---|-----------------|
| AN8-14A | Bolt, Airframe, 1/2-20 Thread, 13/16" Grip, 1-19/32" Length, Undrilled Shank | EA |
| AN815-10D | Union, Flared Tube, 5/8" Tube DIA, 7/8-14 Thread, Aluminum | EA |
| AN815-4 | Union, Flared Tube, 1/4" Tube DIA, 7/16-20 Thread, Steel | EA |
| AN815-8D | Union, Flared Tube, 1/2" Tube DIA, 3/4-16 Thread, Aluminum | EA |
| AN8-15A | Bolt, Airframe, 1/2-20 Thread, 15/16" Grip, 1-23/32" Length, Undrilled Shank | EA |
| AN816-10 | Nipple Adaptor, Straight, Pipe to Tube, 5/8" Tube DIA, 7/8-14 Tube Thread, 1/2-20 Pipe Thread, Aluminum | EA |
| AN816-2D | Adaptor, Nipple, Pipe to Tube, Aluminum, Tube OD 1/8 | EA |
| AN816-4 | Nipple Adaptor, Straight, Pipe to Tube, 1/4" Tube DIA, 7/16-20 Tube Thread, 1/4-28 Pipe Thread, Steel | EA |
| AN816-6 | Nipple Adaptor, Straight, Pipe to Tube, 3/8" Tube DIA, 0.5625 Tube Thread, 1/4-28 Pipe Thread, Steel | EA |
| AN816-6D | Nipple Adaptor, Straight, Pipe to Tube, 3/8" Tube DIA, 0.5625 Tube Thread, 1/4-28 Pipe Thread, Aluminum | EA |
| AN818-10 | Nut, Tube Coupling, 5/8" Tube DIA, 7/8-14 Thread, Short, Steel | EA |
| AN818-10D | Nut, Tube Coupling, 5/8" Tube DIA, 7/8-14 Thread, Short, Aluminum | EA |
| AN818-16 | Nut, Tube Coupling, 1" Tube DIA, 1.3125-12 Thread, Short, Steel | EA |
| AN818-2D | Nut, Tube Coupling, Aluminum, Tube OD 0.125 | EA |
| AN818-3D | Nut, Tube Coupling, Aluminum, Tube OD 0.188 | EA |
| AN818-4 | Nut, Tube Coupling, 1/4" Tube DIA, 7/16-20 Thread, Short, Steel | EA |
| AN818-4D | Nut, Tube Coupling, Aluminum, Tube OD 0.250 | EA |
| AN818-5D | Nut, Tube Coupling, 5/16" Tube DIA, 1/2-20 Thread, Short, Aluminum | EA |
| AN818-6 | Nut, Tube Coupling, 3/8" Tube DIA, 0.5625-18 Thread, Short, Steel | EA |
| AN818-6D | Nut, Tube Coupling, 3/8" Tube DIA, 0.5625-18 Thread, Short, Aluminum | EA |
| AN818-8D | Nut, Tube Coupling, 1/2" Tube DIA, 3/4-16 Thread, Short, Steel | EA |
| AN8-20 | Bolt, Airframe, 1/2-20 Thread, 1-5/16" Grip, 2-3/32" Length, Drilled Shank | EA |
| AN8-20A | Bolt, Airframe, 1/2-20 Thread, 1-5/16" Grip, 2-3/32" Length, Undrilled Shank | EA |
| AN821-8D | Elbow, Flared Tube 90 Deg, 1/2" Tube DIA, 3/4-16, Aluminum | EA |
| AN8-21A | Bolt, Airframe, 1/2-20 Thread, 1-7/16" Grip, 2-7/32" Length, Undrilled Shank | EA |
| AN8-21A | Bolt, Airframe, 1/2-20 Thread, 1-7/16" Grip, 2-7/32" Length, Undrilled Shank | EA |
| AN822-12D | Fitting, 90 Degree, Elbow | EA |
| AN8-22A | Bolt, Airframe, 1/2-20 Thread, 1-9/16" Grip, 2-11/32" Length, Undrilled Shank | EA |
| AN8-23A | Bolt, Airframe, 1/2-20 Thread, 1-11/16" Grip, 2-15/32" Length, Undrilled Shank | EA |
| AN824-6D | Tee, Flared Tube, 3/8" Tube DIA, 9/16-18 Thread, Aluminum | EA |
| AN8-24A | Bolt, Airframe, 1/2-20 Thread, 1-13/16" Grip, 2-19/32" Length, Undrilled Shank | EA |
| AN825-5D | Fitting, Tee | EA |
| AN8-25A | Bolt, Airframe, 1/2-20 Thread, 1-15/16" Grip, 2-23/32" Length, Undrilled Shank | EA |
| AN8-26 | Bolt, Airframe, 1/2-20 Thread, 2-1/16" Grip, 2-27/32" Length, Drilled Shank | EA |
| AN8-26A | Bolt, Airframe, 1/2-20 Thread, 2-1/16" Grip, 2-27/32" Length, Undrilled Shank | EA |
| AN827-5D | Cross Fitting, Flared Tube, 5/16" Tube, 1/2-20 Thread, Aluminum | EA |
| AN8-27A | Bolt, Airframe, 1/2-20 Thread, 2-3/16" Grip, 2-31/32" Length, Undrilled Shank | EA |
| AN8-30 | Bolt, Airframe, 1/2-20 Thread, 2-5/16" Grip, 3-3/32" Length, Drilled Shank | EA |
| AN8-30A | Bolt, Airframe, 1/2-20 Thread, 2-5/16" Grip, 3-3/32" Length, Drilled Shank | EA |
| AN8-31 | Bolt, Airframe, 1/2-20 Thread, 2-7/16" Grip, 3-7/32" Length, Drilled Shank | EA |
| AN8-31A | Bolt, Airframe, 1/2-20 Thread, 2-7/16" Grip, 3-7/32" Length, Undrilled Shank | EA |
| AN8-31A | Bolt, Airframe, 1/2-20 Thread, 2-7/16" Grip, 3-7/32" Length, Undrilled Shank | EA |
| AN8-32 | Bolt, Airframe, 1/2-20 Thread, 2-9/16" Grip, 3-11/32" Length, Drilled Shank | EA |
| AN832-4 | Union, Flared Tube, 3/8 Bulkhead and Universal, 1/4" Tube DIA, 7/16-20 Thread, Steel | EA |

| Part Number | Part Description | Unit of Measure |
|-------------|--|-----------------|
| AN832-5D | Union, Flared Tube, 3/8 Bulkhead and Universal, 5/16" Tube DIA, 1/2-20 Thread, Aluminum | EA |
| AN8-32A | Bolt, Airframe, 1/2-20 Thread, 2-9/16" Grip, 3-11/32" Length, Undrilled Shank | EA |
| AN8-32A | Bolt, Airframe, 1/2-20 Thread, 2-9/16" Grip, 3-11/32" Length, Undrilled Shank | EA |
| AN833-10D | Elbow, Flared Tube, Bulkhead Universal 90 Deg, 5/8" Tube DIA, 7/8-14 Thread, Aluminum | EA |
| AN833-12J | Ebow, 90 Degree SS | EA |
| AN833-6 | Elbow, Flared Tube, Bulkhead Universal 90 Deg, 3/8" Tube DIA, 9/16-18 Thread, Steel | EA |
| AN833-6D | Elbow, Flared Tube, Bulkhead Universal 90 Deg, 3/8" Tube DIA, 9/16-18 Thread, Aluminum | EA |
| AN833-8 | Elbow, Flared Tube, Bulkhead Universal 90 Deg, 1/2" Tube DIA, 3/4-16 Thread, Steel | EA |
| AN8-34A | Bolt, Airframe, 1/2-20 Thread, 2-13/16" Grip, 3-19/32" Length, Undrilled Shank | EA |
| AN8-36 | Bolt, Airframe, 1/2-20 Thread, 3-1/16" Grip, 3-27/32" Length, Drilled Shank | EA |
| AN8-36A | Bolt, Airframe, 1/2-20 Thread, 3-1/16" Grip, 3-27/32" Length, Undrilled Shank | EA |
| AN837-12J | Elbow, 135 Degree SS | EA |
| AN837-3D | Elbow, Flared Tube, Universal, 45 Deg, 3/16" Tube DIA, 3/8-24 Thread, Aluminum | EA |
| AN837-4 | Elbow, Bulkhead 135 Degree | EA |
| AN837-6 | Elbow, Flared Tube, Universal, 45 Deg, 3/8" Tube DIA, 9/16-18 Thread, Steel | EA |
| AN837-6D | Elbow, Flared Tube, Universal, 45 Deg, 3/8" Tube DIA, 9/16-18 Thread, Aluminum | EA |
| AN837-8 | Elbow, Flared Tube, Universal, 45 Deg, 1/2" Tube DIA, 3/4-16 Thread, Steel | EA |
| AN837-8D | Elbow, Flared Tube, Universal, 45 Deg, 1/2" Tube DIA, 3/4-16 Thread, Aluminum | EA |
| AN8-37A | Bolt, Airframe, 1/2-20 Thread, 3-3/16" Grip, 3-31/32" Length, Undrilled Shank | EA |
| AN840-10D | Adapter, Pipe to Hose, Aluminum, Hose ID 5/8, Pipe Thread 1/2 | EA |
| AN840-4D | Adapter, Pipe to Hose, Aluminum, Hose ID 1/4, Pipe Thread 1/8 | EA |
| AN840-6D | Adapter Fitting, Straight, Pipe to Hose, 3/8" Hose DIA, 1/4-28 Pipe Thread, Aluminum | EA |
| AN8-42A | Bolt, Airframe, 1/2-20 Thread, 3-9/16" Grip, 4-11/32" Length, Undrilled Shank | EA |
| AN8-44A | Bolt, Airframe, 1/2-20 Thread, 3-13/16" Grip, 4-19/32" Length, Undrilled Shank | EA |
| AN8-46A | Bolt, Airframe, 1/2-20 Thread, 4-1/16" Grip, 4-27/32" Length, Undrilled Shank | EA |
| AN8-53 | Bolt | EA |
| AN8-6 | Bolt, Airframe, 1/2-20 Thread, 1/16" Grip, 27/32" Length, Drilled Shank | EA |
| AN8-70A | Bolt, Airframe, 1/2-20 Thread, 6-5/16" Grip, 7-3/32" Length, Undrilled Shank | EA |
| AN8-70A | Bolt, Airframe, 1/2-20 Thread, 6-5/16" Grip, 7-3/32" Length, Undrilled Shank | EA |
| AN8H43A | Bolt, Airframe, 1/2-20 Thread, 3-11/16" Grip, 4-15/32" Length, Drilled Head, Undrilled Shank, Steel Cad II Plating | EA |
| AN901-4A | Gasket, Aluminum, 1/4" Tube Size | EA |
| AN901-4C | Washer, Gasket, 7/16" DIA | EA |
| AN901-5A | Gasket, Aluminum, 5/16" Tube Size | EA |
| AN901-6A | Gasket, Aluminum, 3/8" Tube Size | EA |
| AN901-8C | Gasket, Copper, 1/2" Tube Size | EA |
| AN902-4 | Gasket | EA |
| AN910-2D | Coupling, Pipe, 1/4-28 Pipe Thread, Aluminum | EA |
| AN910-3D | Coupling, Pipe, 3/8-24 Pipe Thread, Aluminum | EA |
| AN911-4D | Nipple, Pipe, 1/2-20 Pipe Thread, Aluminum | EA |
| AN911-6D | Nipple, Pipe, 3/4-16 Pipe Thread, Aluminum | EA |

| Part Number | Part Description | Unit of Measure |
|-------------|--|-----------------|
| AN912-4D | Bushing, Reducer Pipe, 1/2-20 External Thread, 3/8-24 Internal Thread, Aluminum | EA |
| AN912-5D | Bushing, Reducer Pipe, 1/2-20 External Thread, 1/4-28 Internal Thread, Aluminum | EA |
| AN912-7 | Bushing, Reducer Pipe, 3/4-16 External Thread, 1/2-20 Internal Thread, Steel | EA |
| AN912-8 | Bushing, Reducer Pipe, 3/4-16 External Thread, 3/8-24 Internal Thread, Steel | EA |
| AN912-9 | Bushing, Reducer Pipe, 3/4-16 External Thread, 1/4-28 Internal Thread, Steel | EA |
| AN914-3D | Elbow, Pipe Internal and External Thread, 90 Deg, 3/8-24 Thread, Aluminum | EA |
| AN914-4D | Elbow, Pipe Internal and External Thread, 90 Deg, 1/2-20 Thread, Aluminum | EA |
| AN915-1D | Elbow, Pipe 45 Deg, 5-44 Thread, 37/64" Pipe DIA, Aluminum | EA |
| AN916-4 | Elbow, Pipe Internal Thread, 90 Deg, 1/2-20 Pipe Thread, Aluminum | EA |
| AN917-2D | Tee, Pipe Internal Thread, 1/4-28 Pipe Thread, Aluminum | EA |
| AN919-15D | Reducer, External Thread, Flared Tube, 7/8-14 to 3/4-16 Thread, Aluminum | EA |
| AN919-1D | Reducer, Flared Tube, Aluminum, Tube OD 1/4, Thread 7/16-20 | EA |
| AN919-22 | Reducer, 1-1/2" to 3/4" | EA |
| AN919-23 | Reducer, External Thread, Flared Tube, 1 - 5/16-12 to 1 - 1/16-12 Thread, Steel | EA |
| AN919-3D | Reducer, External Thread, Flared Tube, 1/2-20 to 7/16-20 Thread, Aluminum | EA |
| AN919-4D | Reducer, External Thread, Flared Tube, 9/16-18 to 5/16-24 Thread, Aluminum | EA |
| AN919-6D | Reducer, External Thread, Flared Tube, 9/16-18 to 7/16-20 Thread, Aluminum | EA |
| AN919-7 | Reducer, External Thread, Flared Tube, 9/16-18 to 1/2-20 Thread, Steel | EA |
| AN9-22 | Bolt, Airframe, 9/16-18 Thread, 1-1/2" Grip, 2-7/16" Length, Drilled Shank | EA |
| AN9-22A | Bolt, Airframe, 9/16-18 Thread, 1-1/2" Grip, 2-7/16" Length, Undrilled Shank | EA |
| AN9-23A | Bolt, Airframe, 9/16-18 Thread, 1-5/8" Grip, 2-17/32" Length, Undrilled Shank | EA |
| AN924-10 | Nut, Tube, Bulkhead and Universal Fitting, 7/8-14 Thread, Steel | EA |
| AN924-10D | Nut, Tube, Bulkhead and Universal Fitting, 7/8-14 Thread, Aluminum | EA |
| AN924-12J | Nut, Tube, Bulkhead and Universal Fitting, 1 - 1/16-12 Thread, Corrosion Resistant | EA |
| AN924-16S | Nut, Tube, Bulkhead and Universal Fitting, 1 - 5/16-12 Thread, Steel | EA |
| AN924-3D | Nut, Tube, Bulkhead and Universal Fitting, 3/8-24 Thread, Aluminum | EA |
| AN924-4 | Nut, Tube, Bulkhead and Universal Fitting, 7/16-20 Thread, Steel | EA |
| AN924-4D | Nut, Tube, Bulkhead and Universal Fitting, 7/16-20 Thread, Aluminum | EA |
| AN924-5D | Nut, Tube, Bulkhead and Universal Fitting, 1/2-20 Thread, Aluminum | EA |
| AN924-5D | Nut, Tube, Bulkhead and Universal Fitting, 1/2-20 Thread, Aluminum | EA |
| AN924-6 | Nut, Tube, Bulkhead and Universal Fitting, 9/16-18 Thread, Steel | EA |
| AN924-6D | Nut, Tube, Bulkhead and Universal Fitting, 9/16-18 Thread, Aluminum | EA |
| AN924-8 | Nut, Tube, Bulkhead and Universal Fitting, 3/4-16 Thread, Steel | EA |
| AN924-8D | Nut, Tube, Bulkhead and Universal Fitting, 3/4-16 Thread, Aluminum | EA |
| AN929-10 | Cap Assembly, Pressure Seal, Flared Tube Fitting, 5/8" Tube DIA, Aluminum | EA |
| AN929-12 | Cap Assembly, Pressure Seal, Flared Tube Fitting, 3/4" Tube DIA, Aluminum | EA |
| AN929-2 | Cap Assembly, Pressure Seal, Flared Tube Fitting, 1/8" Tube DIA, Aluminum | EA |
| AN929-4D | Cap, Aluminum | EA |
| AN929-6 | Cap Assembly, Pressure Seal, Flared Tube Fitting, 3/8" Tube DIA, Aluminum | EA |

| Part Number | Part Description | Unit of Measure |
|-------------|---|-----------------|
| AN929-8 | Cap Assembly, Pressure Seal, Flared Tube Fitting, 1/2" Tube DIA, Aluminum | EA |
| AN9-30A | Bolt, Airframe, 9/16-18 Thread, 2-1/4" Grip, 5-32/32" Length, Undrilled Shank | EA |
| AN9-32A | Bolt, Airframe, 9/16-18 Thread, 2-1/2" Grip, 3-13/32" Length, Undrilled Shank | EA |
| AN9-34A | Bolt, Airframe, 9/16-18 Thread, 2-3/4" Grip, 3-21/32" Length, Undrilled Shank | EA |
| AN9-34A | Bolt, Airframe, 9/16-18 Thread, 2-3/4" Grip, 3-21/32" Length, Undrilled Shank | EA |
| AN9-35A | Bolt, Airframe, 9/16-18 Thread, 2-7/8" Grip, 3-25/32" Length, Undrilled Shank | EA |
| AN9-36A | Bolt, Airframe, 9/16-18 Thread, 3" Grip, 3-29/32" Length, Undrilled Shank | EA |
| AN936A3 | Washer, Lack, Internal Tooth, To Fit DIA #3, Carbon Steel | EA |
| AN938-4D | Tee, Tube, Internal Thread, 1/4" Tube DIA, 7/16-20 Thread, Aluminum | EA |
| AN938-6D | Tee, Tube, Internal Thread, 3/8" Tube DIA, 3/4-16 Thread, Aluminum | EA |
| AN960-1616L | Washer; 1.005 I.D. / 1.745 O.D. | EA |
| AN9-60A | Bolt, Airframe, 9/16-18 Thread, 5-1/4" Grip, 6-5/32" Length, Undrilled Shank | EA |
| AN970-10 | Washer | EA |
| AN970-3 | Washer, Large Area Flat, Size #10 | EA |
| AN970-4 | Washer, Large Area Flat, Size 1/4 | EA |
| AN970-5 | Washer, Large Area Flat, Size 5/16 | EA |
| AN970-6 | Washer, Large Area Flat, Size 3/8 | EA |
| AN970-8 | Washer, Large Area Flat, Size 1/2 | EA |
| AR15TYPE2 | Lock, Cylinder, Assembly, W/ Key | EA |
| AR292 | Nut, Cylinder, 1/4" | EA |
| AR-3520-2 | Fitting | EA |
| AS3209-010 | O Ring | EA |
| AS3209-013 | O Ring | EA |
| AS3209-111 | O Ring | EA |
| AS3209-138 | O Ring | EA |
| AS3209-213 | O Ring | EA |
| AS3570-010 | O Ring | EA |
| AS3570-223 | Packing | EA |
| AS3578-010 | O Ring | EA |
| AS3578-038 | O Ring | EA |
| AS3582-027 | O Ring | EA |
| AWC-5TG | Bearing, 5/8" DIA | EA |
| B1353-1 | Pin Assembly | EA |
| B145-78-7 | Stop, 5/16-24 Thread | EA |
| B30076 | Spacer, 4" DIA | EA |
| B30278-1 | Plate, Tourque | EA |
| B30278-2 | Plate, Tourque | EA |
| BB341-12 | Expander - Blind nut - SEE NOTE | EA |
| BLS4B-030S | Pins | EA |
| BN360-428-2 | Rivnut, Blind, DIA 1/4", w/Connector | EA |
| BN360-428-3 | Rivnut, Blind, DIA 1/4"- SEE NOTE | EA |
| C-21K | Kit, Compass Repair | EA |
| C2CF1513 | Washer, 3/8" DIA | EA |
| C2CF1709 | Valve, Hydraulic | EA |
| C2CF1931ND | Washer, 3/8" DIA | EA |
| C2CF3323 | Bolt, Special, 1/4" | EA |
| C2EC899 | Eye Bolt, 1/4" | EA |
| C2U185 | Bolt, 3/8", Medium Fluid Passage | EA |
| C2U189 | Bolt, 1/4", Small Fluid Passage | EA |
| C2U389-1 | Bolt Tie, 5/8" | EA |
| C2U467 | Bolt, 3/8", Medium Fluid Passage | EA |
| C2U489 | Washer, Thick Rubber, 3/4" DIA | EA |

| Part Number | Part Description | Unit of Measure |
|-------------|--|-----------------|
| C2UT203 | Bolt, 1/4" DIA | EA |
| C2UT291 | Washer, Ridged, 3/8" DIA | EA |
| C2UT399ND | Washer, Flat, 1/2" DIA | EA |
| C2UT401ND | Washer, Flat, 1/4" DIA | EA |
| C2UT513 | Bolt, 1/4" DIA, Long | EA |
| C2W495 | Bolt, Spar Attach Rear, 1/4" | EA |
| CAT-10 | Tubing, Black, 2-1/2" DIA | FT |
| CAT-12 | Tubing, Black, 3" DIA | FT |
| CAT-12 | Tubing, Black, 3" DIA | FT |
| CAT-14 | Tubing, Black, 3-1/2" DIA | FT |
| CAT-16 | Tubing, Black, 4" DIA | FT |
| CAT-16 | Tubing, Black, 4" DIA | FT |
| CAT-3 | Tubing, Black, 3/4" DIA | FT |
| CAT-4 | Tubing, Black, 1" DIA, 10' PC | FT |
| CAT-5 | Tubing, Black, 1-1/4" DIA | FT |
| CAT-6 | Tubing, Black, 1-1/2" DIA | FT |
| CAT-8 | Tubing, Black, 2" DIA | FT |
| CD-10 | Cap, Plastic #10, Red | EA |
| CD-3 | Cap, Plastic #3 | EA |
| CD-4 | Cap, Plastic #4, Red | EA |
| CD-4 | Cap, Plastic #4, Red | EA |
| CD-5 | Cap, Plastic #5, Red | EA |
| CD-6 | Cap, Plastic #6, Red | EA |
| CD-8 | Cap, Plastic #8, Red | EA |
| CM2954-6D1 | Bolt, 3/8-24 Thread, 3/4" Length, Hole in Head | EA |
| CORK-13 | Cork Strip 1/16 x 1/2 x 13" | EA |
| CORK-15 | Cork Strip 1/16 x 1/2 x 15" | EA |
| CORK-22 | Cork Strip 1/16 x 1/2 x 22" | EA |
| CR2249-4-2 | Rivet, Cherry Max, 9/64" DIA, 0.063-0.125" Grip Range, 100 Deg Flush Head, Alloy Steel Stem, Aluminum Sleeve | EA |
| CR3212-4-2 | Rivet, Cherry Max, 1/8" DIA, 0.063-0.125" Grip Range, 100 Deg Flush Head, Alloy Steel Stem, Aluminum Sleeve | EA |
| CR3212-4-3 | Rivet, Cherry Max, 1/8" DIA, 0.126-0.187" Grip Range, 100 Deg Flush Head, Alloy Steel Stem, Aluminum Sleeve | EA |
| CR3212-4-4 | Rivet, Cherry Max, 1/8" DIA, 0.188-0.25" Grip Range, 100 Deg Flush Head, Alloy Steel Stem, Aluminum Sleeve | EA |
| CR3212-4-5 | Rivet, Cherry Max, 1/8" DIA, 0.251-0.312" Grip Range, 100 Deg Flush Head, Alloy Steel Stem, Aluminum Sleeve | EA |
| CR3212-4-6 | Rivet, Cherry Max, 1/8" DIA, 0.313-0.375 Grip Range, 100 Deg Flush Head, Alloy Steel Stem, Aluminum Sleeve | EA |
| CR3212-4-7 | Rivet, Cherry Max, 1/8" DIA, 0.376-0.437" Grip Range, 100 Deg Flush Head, Alloy Steel Stem, Aluminum Sleeve | EA |
| CR3212-4-8 | Rivet, Cherry Max Do not buy | EA |
| CR3212-4-9 | Rivet, Cherry Max, 1/8" DIA, 0.501-0.562" Grip Range, 100 Deg Flush Head, Alloy Steel Stem, Aluminum Sleeve | EA |
| CR3212-5-4 | Rivet, Cherry Max, 5/32" DIA, 0.188-0.25" Grip Range, 100 Deg Flush Head, Alloy Steel Stem, Aluminum Sleeve | EA |
| CR3212-5-5 | Rivet, Cherry Max, 5/32" DIA, 0.251-0.312" Grip Range, 100 Deg Flush Head, Alloy Steel Stem, Aluminum Sleeve | EA |
| CR3212-5-6 | Rivet, Cherry Max, 5/32" DIA, 0.313-0.375" Grip Range, 100 Deg Flush Head, Alloy Steel Stem, Aluminum Sleeve | EA |
| CR3212-5-7 | Rivet, Cherry Max, 5/32" DIA, 0.376-0.437" Grip Range, 100 Deg Flush Head, Alloy Steel Stem, Aluminum Sleeve | EA |

| Part Number | Part Description | Unit of Measure |
|-------------|--|-----------------|
| CR3212-6-3 | Rivet, Cherry Max, Flush | EA |
| CR3212-6-5 | Rivet, Cherry Max, 3/16" DIA, 0.251-0.312" Grip Range, 100 Deg Flush Head, Alloy Steel Stem, Aluminum Sleeve | EA |
| CR3212-6-6 | Rivet, Cherry Max, 3/16" DIA, 0.313-0.375" Grip Range, 100 Deg Flush Head, Alloy Steel Stem, Aluminum Sleeve | EA |
| CR3212-6-7 | Rivet, Cherry Max, 3/16" DIA, 0.376-0.437" Grip Range, 100 Deg Flush Head, Alloy Steel Stem, Aluminum Sleeve | EA |
| CR3213-4-1 | Rivet, Cherry Max, 1/8" DIA, 0.025-0.062" Grip Range, Universal Head | EA |
| CR3213-4-2 | Rivet, Cherry Max, 1/8" DIA, 0.063-0.125" Grip Range, Universal Head | EA |
| CR3213-4-3 | Rivet, Cherry Max, 1/8" DIA, 0.126-0.187" Grip Range, Universal Head | EA |
| CR3213-4-4 | Rivet, Cherry Max, 1/8" DIA, 0.188-0.25" Grip Range, Universal Head, Alloy Steel Stem, Aluminum Sleeve | EA |
| CR3213-4-5 | Rivet, Cherry Max, 1/8" DIA, 0.251-0.312" Grip Range, Universal Head, Alloy Steel Stem, Aluminum Sleeve | EA |
| CR3213-4-6 | Rivet, Cherry Max, 1/8" DIA, 0.313-0.375" Grip Range, Universal Head, Alloy Steel Stem, Aluminum Sleeve | EA |
| CR3213-4-7 | Rivet, Cherry Max, 1/8" DIA, 0.376-0.437" Grip Range, Universal Head, Alloy Steel Stem, Aluminum Sleeve | EA |
| CR3213-5-1 | Rivet, Cherry Max, 5/32" DIA, 0.025-0.062" Grip Range, Universal Head, Alloy Steel Stem, Aluminum Sleeve | EA |
| CR3213-5-10 | Rivet, Cherry Max, 5/32" DIA, 0.563-0.625" Grip Range, Universal Head, Alloy Steel Stem, Aluminum Sleeve | EA |
| CR3213-5-11 | Rivet, Cherry Max, 5/32" DIA, 0.626-0.687" Grip Range, Universal Head, Alloy Steel Stem, Aluminum Sleeve | EA |
| CR3213-5-2 | Rivet, Cherry Max, 5/32" DIA, 0.063-0.125" Grip Range, Universal Head, Alloy Steel Stem, Aluminum Sleeve | EA |
| CR3213-5-3 | Rivet, Cherry Max, 5/32" DIA, 0.126-0.187" Grip Range, Universal Head, Alloy Steel Stem, Aluminum Sleeve | EA |
| CR3213-5-4 | Rivet, Cherry Max, 5/32" DIA, 0.188-0.25" Grip Range, Universal Head, Alloy Steel Stem, Aluminum Sleeve | EA |
| CR3213-5-5 | Rivet, Cherry Max, 5/32" DIA, 0.251-0.312" Grip Range, Universal Head, Alloy Steel Stem, Aluminum Sleeve | EA |
| CR3213-5-6 | Rivet, Cherry Max, 5/32" DIA, 0.313-0.375" Grip Range, Universal Head, Alloy Steel Stem, Aluminum Sleeve | EA |
| CR3213-5-7 | Rivet, Cherry Max, 5/32" DIA, 0.376-0.437" Grip Range, Universal Head, Alloy Steel Stem, Aluminum Sleeve | EA |
| CR3213-5-8 | Rivet, Cherry Max, 5/32" DIA, 0.438-0.5" Grip Range, Universal Head, Alloy Steel Stem, Aluminum Sleeve | EA |
| CR3213-6-12 | Rivet, Cherry Max, 3/16" DIA, 0.688"+ Grip Range, Universal Head, Alloy Steel Stem, Aluminum Sleeve | EA |
| CR3213-6-3 | Rivet, Cherry Max, 3/16" DIA, 0.126-0.187" Grip Range, Universal Head, Alloy Steel Stem, Aluminum Sleeve | EA |
| CR3213-6-4 | Rivet, Cherry Max, 3/16" DIA, 0.188-0.25" Grip Range, Universal Head, Alloy Steel Stem, Aluminum Sleeve | EA |
| CR3213-6-5 | Rivet, Cherry Max, 3/16" DIA, 0.251-0.312" Grip Range, Universal Head, Alloy Steel Stem, Aluminum Sleeve | EA |
| CR3213-6-6 | Rivet, Cherry Max, 3/16" DIA, 0.313-0.375" Grip Range, Universal Head, Alloy Steel Stem, Aluminum Sleeve | EA |
| CR3213-6-7 | Rivet, Cherry Max, 3/16" DIA, 0.376-0.437" Grip Range, Universal Head, Alloy Steel Stem, Aluminum Sleeve | EA |
| CR3213-8-5 | Rivet, Cherry Max, 1/4" DIA, 0.251-0.312" Grip Range, Universal Head, Alloy Steel Stem, Aluminum Sleeve | EA |
| CR3214-4-2 | Rivet, Cherry Max | EA |

| Part Number | Part Description | Unit of Measure |
|-------------|---|-----------------|
| CR3214-4-3 | Rivet, Cherry Max | EA |
| CR3214-4-5 | Rivet, Cherry Max | EA |
| CR3242-4-1 | Rivet, Cherry Max, OVERSIZE DIA, 9/64" DIA, 0.025-0.062" Grip Range, 100 Deg Flush Head | EA |
| CR3242-4-2 | Rivet, Cherry Max, 9/64" DIA, 0.063-0.125" Grip Range, 100 Deg Flush Head, Alloy Steel Stem, Aluminum Sleeve | EA |
| CR3242-4-3 | Rivet, Cherry Max, 9/64" DIA, 0.126-0.187" Grip Range, 100 Deg Flush Head, Alloy Steel Stem, Aluminum Sleeve | EA |
| CR3242-4-4 | Rivet, Cherry Max, 9/64" DIA, 0.188-0.25" Grip Range, 100 Deg Flush Head, Alloy Steel Stem, Aluminum Sleeve | EA |
| CR3242-4-5 | Rivet, Cherry Max, 9/64" DIA, 0.251-0.312" Grip Range, 100 Deg Flush Head, Alloy Steel Stem, Aluminum Sleeve | EA |
| CR3242-5-2 | Rivet, Cherry Max, 11/64" DIA, 0.063-0.125" Grip Range, 100 Deg Flush Head, Alloy Steel Stem, Aluminum Sleeve | EA |
| CR3242-5-3 | Rivet, Cherry Max, 11/64" DIA, 0.126-0.187" Grip Range, 100 Deg Flush Head, Alloy Steel Stem, Aluminum Sleeve | EA |
| CR3242-5-4 | Rivet, Cherry Max, 11/64" DIA, 0.188-0.25" Grip Range, 100 Deg Flush Head, Alloy Steel Stem, Aluminum Sleeve | EA |
| CR3242-5-5 | Rivet, Cherry Max, 11/64" DIA, 0.251-0.312" Grip Range, 100 Deg Flush Head, Alloy Steel Stem, Aluminum Sleeve | EA |
| CR3242-5-6 | Rivet, Cherry Max, 11/64" DIA, 0.313-0.375" Grip Range, 100 Deg Flush Head, Alloy Steel Stem, Aluminum Sleeve | EA |
| CR3242-5-7 | Rivet, Cherry Max, 11/64" DIA, 0.376-0.437" Grip Range, 100 Deg Flush Head, Alloy Steel Stem, Aluminum Sleeve | EA |
| CR3242-5-8 | Rivet, Cherry Max, 11/64" DIA, 0.438-0.5" Grip Range, 100 Deg Flush Head, Alloy Steel Stem, Aluminum Sleeve | EA |
| CR3242-6-3 | Rivet, Cherry Max, 13/64" DIA, 0.126-0.187" Grip Range, 100 Deg Flush Head, Alloy Steel Stem, Aluminum Sleeve | EA |
| CR3242-6-4 | Rivet, Cherry Max, 13/64" DIA, 0.188-0.250" Grip Range, 100 Deg Flush Head, Alloy Steel Stem, Aluminum Sleeve | EA |
| CR3243-4-1 | Rivet, Cherry Max, 9/64" DIA, 0.025-0.062" Grip Range, Universal Head, Alloy Steel Stem, Aluminum Sleeve | EA |
| CR3243-4-2 | Rivet, Cherry Max | EA |
| CR3243-4-3 | Rivet, Cherry Max, 9/64" DIA, 0.126-0.187" Grip Range, Universal Head, Alloy Steel Stem, Aluminum Sleeve | EA |
| CR3243-4-4 | Rivet, Cherry Max, 9/64" DIA, 0.188-0.25" Grip Range, Universal Head, Alloy Steel Stem, Aluminum Sleeve | EA |
| CR3243-4-5 | Rivet, Cherry Max, 9/64" DIA, 0.251-0.312" Grip Range, Universal Head, Alloy Steel Stem, Aluminum Sleeve | EA |
| CR3243-4-6 | Rivet, Cherry Max, 9/64" DIA, 0.313-0.375" Grip Range, Universal Head, Alloy Steel Stem, Aluminum Sleeve | EA |
| CR3243-4-7 | Rivet, Cherry Max, 9/64" DIA, 0.376-0.437" Grip Range, Universal Head, Alloy Steel Stem, Aluminum Sleeve | EA |
| CR3243-5-1 | Rivet, Cherry Max, 11/64" DIA, 0.025-0.062" Grip Range, Universal Head, Alloy Steel Stem, Aluminum Sleeve | EA |
| CR3243-5-11 | Rivet, Cherry Max, 11/64" DIA, 0.501-0.562" Grip Range, Universal Head, Alloy Steel Stem, Aluminum Sleeve | EA |
| CR3243-5-2 | Rivet, Cherry Max, 11/64" DIA, 0.063-0.125" Grip Range, Universal Head, Alloy Steel Stem, Aluminum Sleeve | EA |
| CR3243-5-3 | Rivet, Cherry Max, 11/64" DIA, 0.126-0.187" Grip Range, Universal Head, Alloy Steel Stem, Aluminum Sleeve | EA |
| CR3243-5-4 | Rivet, Cherry Max, 11/64" DIA, 0.188-0.25" Grip Range, Universal Head, Alloy Steel Stem, Aluminum Sleeve | EA |

| Part Number | Part Description | Unit of Measure |
|-------------|---|-----------------|
| CR3243-5-5 | Rivet, Cherry Max, 11/64" DIA, 0.251-0.2312" Grip Range, Universal Head, Alloy Steel Stem, Aluminum Sleeve | EA |
| CR3243-5-6 | Rivet, Cherry Max, 11/64" DIA, 0.313-0.375" Grip Range, Universal Head, Alloy Steel Stem, Aluminum Sleeve | EA |
| CR3243-5-7 | Rivet, Cherry Max, 11/64" DIA, 0.376-0.437" Grip Range, Universal Head, Alloy Steel Stem, Aluminum Sleeve | EA |
| CR3243-5-8 | Rivet, Cherry Max, 11/64" DIA, 0.438-0.5" Grip Range, Universal Head, Alloy Steel Stem, Aluminum Sleeve | EA |
| CR3243-6-2 | Rivet, Cherry Max, 13/64" DIA, 0.063-0.152" Grip Range, Universal Head, Alloy Steel Stem, Aluminum Sleeve | EA |
| CR3243-6-3 | Rivet, Cherry Max, 13/64" DIA, 0.126-0.187" Grip Range, Universal Head, Alloy Steel Stem, Aluminum Sleeve | EA |
| CR3243-6-4 | Rivet, Cherry Max, 13/64" DIA, 0.188-0.25" Grip Range, Universal Head, Alloy Steel Stem, Aluminum Sleeve | EA |
| CR3243-6-5 | Rivet, Cherry Max, 13/64" DIA, 0.251-0.312" Grip Range, Universal Head, Alloy Steel Stem, Aluminum Sleeve | EA |
| CR3243-6-6 | Rivet, Cherry Max, 13/64" DIA, 0.313-0.375" Grip Range, Universal Head, Alloy Steel Stem, Aluminum Sleeve | EA |
| CR3523-4-2 | Rivet, Cherry Max, 1/8" DIA, 0.063-0.125" Grip Range, Universal Head, Corrosion Resistant Stem, Monel Sleeve | EA |
| CR3523-4-3 | Rivet, Cherry Max | EA |
| CR3523-4-4 | Rivet, Cherry Max, 1/8" DIA, 0.188-0.25" Grip Range, Universal Head, Corrosion Resistant Stem, Monel Sleeve | EA |
| CR3523-4-5 | Rivet, Cherry Max, 1/8" DIA, 0.251-0.312" Grip Range, Universal Head, Corrosion Resistant Stem, Monel Sleeve | EA |
| CR3523-4-6 | Rivet, Cherry Max, 1/8" DIA, 0.313-0.375" Grip Range, Universal Head, Corrosion Resistant Stem, Monel Sleeve | EA |
| CR3523-4-7 | Rivet, Cherry Max, 1/8" DIA, 0.376-0.437" Grip Range, Universal Head, Corrosion Resistant Stem, Monel Sleeve | EA |
| CR3523-5-2 | Rivet, Cherry Max, 5/32" DIA, 0.063-0.125" Grip Range, Universal Head, Corrosion Resistant Stem, Monel Sleeve | EA |
| CR3523-5-5 | Rivet, Cherry Max, OVERSIZED, 11/64" DIA, 0.126-0.187" Grip Range, Universal Head, Corrosion Resistant Stem, Monel Sleeve | EA |
| CR3523-5-6 | Rivet, Cherry Max, OVERSIZED, 11/64" DIA, 0.313-0.375" Grip Range, Universal Head, Corrosion Resistant Stem, Monel Sleeve | EA |
| CR3523-6-5 | Rivet, Cherry Max | EA |
| CR3523-6-6 | Rivet, Cherry Max, OVERSIZED, 13/64" DIA, 0.313-0.375" Grip Range, 100 Deg Flush Head, Corrosion Resistant Stem, Monel Sleeve | EA |
| CR3552-4-3 | Rivet, Cherry Max, OVERSIZED, 9/64" DIA, 0.126-0.187" Grip Range, 100 Deg Flush Head, Corrosion Resistant Stem, Monel Sleeve | EA |
| CR3552-4-4 | Rivet, Cherry Max, OVERSIZED, 9/64" DIA, 0.188-0.25" Grip Range, 100 Deg Flush Head, Corrosion Resistant Stem, Monel Sleeve | EA |
| CR3552-4-5 | Rivet, Cherry Max, OVERSIZED, 9/64" DIA, 0.251-0.312" Grip Range, 100 Deg Flush Head, Corrosion Resistant Stem, Monel Sleeve | EA |
| CR3552-5-3 | Rivet, Cherry Max, OVERSIZED, 11/64" DIA, 0.126-0.187" Grip Range, Universal Head, Corrosion Resistant Stem, Monel Sleeve | EA |
| CR3552-5-4 | Rivet, Cherry Max, OVERSIZED, 11/64" DIA, 0.188-0.25" Grip Range, Universal Head, Corrosion Resistant Stem, Monel Sleeve | EA |
| CR3552-5-5 | Rivet, Cherry Max, OVERSIZED, 11/64" DIA, 0.251-0.312" Grip Range, Universal Head, Corrosion Resistant Stem, Monel Sleeve | EA |
| CR3553-4-2 | Rivet, Cherry Max, OVERSIZED, 9/64" DIA, 0.063-0.125" Grip Range, Universal Head, Corrosion Resistant Stem, Monel Sleeve | EA |

| Part Number | Part Description | Unit of Measure |
|-------------|---|-----------------|
| CR3553-4-3 | Rivet, Cherry Max, OVERSIZED, 9/64" DIA, 0.126-0.187" Grip Range, Universal Head, Corrosion Resistant Stem, Monel Sleeve | EA |
| CR3553-4-4 | Rivet, Cherry Max, OVERSIZED, 9/64" DIA, 0.188-0.25" Grip Range, Universal Head, Corrosion Resistant Stem, Monel Sleeve | EA |
| CR3553-4-5 | Rivet, Cherry Max, OVERSIZED, 9/64" DIA, 0.251-0.312" Grip Range, Universal Head, Corrosion Resistant Stem, Monel Sleeve | EA |
| CR3553-4-6 | Rivet, Cherry Max, OVERSIZED, 9/64" DIA, 0.313-0.375" Grip Range, Universal Head, Corrosion Resistant Stem, Monel Sleeve | EA |
| CR3553-4-7 | Rivet, Cherry Max, OVERSIZED, 9/64" DIA, 0.376-0.437" Grip Range, Universal Head, Corrosion Resistant Stem, Monel Sleeve | EA |
| CR3553-5-2 | Rivet, Cherry Max, OVERSIZED, 11/64" DIA, 0.063-0.125" Grip Range, Universal Head, Corrosion Resistant Stem, Monel Sleeve | EA |
| CR3553-5-3 | Rivet, Cherry Max, OVERSIZED, 11/64" DIA, 0.126-0.187" Grip Range, Universal Head, Corrosion Resistant Stem, Monel Sleeve | EA |
| CR3553-5-4 | Rivet, Cherry Max, OVERSIZED, 11/64" DIA, 0.188-0.25" Grip Range, Universal Head, Corrosion Resistant Stem, Monel Sleeve | EA |
| CR3553-5-5 | Rivet, Cherry Max, OVERSIZED, 11/64" DIA, 0.126-0.187" Grip Range, 100 Deg Flush Head, Corrosion Resistant Stem, Monel Sleeve | EA |
| CR3553-5-6 | Rivet, Cherry Max, OVERSIZED, 11/64" DIA, 0.313-0.375" Grip Range, 100 Deg Flush Head, Corrosion Resistant Stem, Monel Sleeve | EA |
| CR3553-5-7 | Rivet, Cherry Max, OVERSIZED, 11/64" DIA, 0.376-0.437" Grip Range, 100 Deg Flush Head, Corrosion Resistant Stem, Monel Sleeve | EA |
| CR3553-6-4 | Rivet, Cherry Max, OVERSIZED, 13/64" DIA, 0.188-0.25" Grip Range, 100 Deg Flush Head, Corrosion Resistant Stem, Monel Sleeve | EA |
| CR9163-4-1 | Rivet, Cherry Max, 1/8" DIA, 0.025-0.062" Grip Range, Universal Head, Self-Plugging, Serrated Stem, Aluminum Stem & Sleeve | EA |
| CR9163-4-2 | Rivet, Cherry Max, OVERSIZED, 9/64" DIA, 0.063-0.125" Grip Range, 100 Deg Flush Head, Corrosion Resistant Stem, Monel Sleeve | EA |
| CR9163-4-3 | Rivet, Cherry Max, 1/8" DIA, 0.126-0.187" Grip Range, Universal Head, Self-Plugging, Serrated Stem, Aluminum Stem & Sleeve | EA |
| CR9163-5-1 | Rivet, Cherry Max, 5/32" DIA, 0.025-0.062" Grip Range, Universal Head, Self-Plugging, Serrated Stem, Aluminum Stem & Sleeve | EA |
| CR9163-5-2 | Rivet, Cherry Max, OVERSIZED, 11/64" DIA, 0.063-0.125" Grip Range, 100 Deg Flush Head, Corrosion Resistant Stem, Monel Sleeve | EA |
| CR9163-5-3 | Rivet, Cherry Max, OVERSIZED, 11/64" DIA, 0.126-0.187" Grip Range, 100 Deg Flush Head, Corrosion Resistant Stem, Monel Sleeve | EA |
| CR9163-5-4 | Rivet, Cherry Max, 5/32" DIA, 0.063-0.125" Grip Range, Universal Head, Self-Plugging, Serrated Stem, Aluminum Stem & Sleeve | EA |
| CR9179-4-2 | Rivet, Cherry Max | EA |
| CR9179-4-3 | Rivet, Cherry Max | EA |
| CR9179-4-4 | Rivet, Cherry Max | EA |
| CT2N1083-27 | Bolt, 1/4" DIA, W/ Staff Hook | EA |
| D366X1/4 | Screw, Compass, 5-44 Thread, Round Head | EA |
| D4023X3/8 | Stud, 5-44 Thread, Round Head | EA |
| DB1/4-3 | 3" Drill bit 1/4 fraction | EA |
| DB1/8-3 | 3" Drill bit 1/8 fraction | EA |
| DB15/32-3 | 3" Drill bit 15/32 fraction | EA |
| DB15/64-3 | 3" Drill bit 15/64 fraction | EA |
| DB17/64-3 | 3" Drill bit 17/64 fraction | EA |
| DB25/64-3 | 3" Drill bit 25/64 fraction | EA |
| DB27/64-3 | 3" Drill bit 27/64 fraction | EA |
| DB29/64-3 | 3" Drill bit 29/64 fraction | EA |
| DB3/16-3 | 3" Drill bit 3/16 fraction | EA |

| Part Number | Part Description | Unit of Measure |
|---------------------|--|-----------------|
| DB3/8-3 | 3" Drill bit 3/8 fraction | EA |
| DB5/16-3 | 3" Drill bit 5/16 fraction | EA |
| DIFF10A396AA | Bolt, 5-44 Thread | EA |
| ELA16-8 | Bearing, Ball, Flap Pump, 1/4" | EA |
| ELECTRICAL-TAPE-BLK | Tape, Electrical Black (Vinyl) | EA |
| EP40 | Plug | EA |
| ES4243 | Bolt, Long, 1/8" | EA |
| F1204 | Bearing, Rudder Pedal, 1" DIA | EA |
| F2452-080 | Nut, Barrel, 3/8-24 Thread | EA |
| F4W19 | Rod End Bearing, Bore 3/8", Thread 3/8-24, Female | EA |
| FL34-14M | Rod End Bearing, Bore 3/16", Thread 1/4-28 | EA |
| FL44-14M | Rod End Bearing, Bore 1/4", Thread 1/4-28 | EA |
| FL45-19M | Rod End Bearing, Bore 3/16", Thread 1/4-28 | EA |
| H559-3-1 | Grommet | EA |
| H559-4-1 | Grommet | EA |
| HF-4M | Rod End, Bore 1/4", Thread 1/4-28, Female | EA |
| HFL-4M | Rod End, Bore 1/4", Thread 1/4-28, Female | EA |
| HL18PB6-18 | Hi-Lok Pin, Protruding Shear Head, 3/16 Nom DIA, 10-32 Thread, 1-1/8" Max Grip, 160000-180000 PSI, Tensile Strength, Alloy Steel | EA |
| HL18PB6-4 | Hi-Lok Pin, Protruding Shear Head, 3/16 Nom DIA, 10-32 Thread, 7/16" Max Grip, 160000-180000 PSI, Tensile Strength, Alloy Steel | EA |
| HL18PB6-5 | Hi-Lok Pin, Protruding Shear Head, 3/16 Nom DIA, 10-32 Thread, 5/16" Max Grip, 160000-180000 PSI, Tensile Strength, Alloy Steel | EA |
| HL18PB6-6 | Hi-Lok Pin, Protruding Shear Head, 3/16 Nom DIA, 10-32 Thread, 3/8" Max Grip, 160000-180000 PSI, Tensile Strength, Alloy Steel | EA |
| HL18PB6-7 | Hi-Lok Pin, Protruding Shear Head, 3/16 Nom DIA, 10-32 Thread, 7/16" Max Grip, 160000-180000 PSI, Tensile Strength, Alloy Steel | EA |
| HL18PB6-8 | Hi-Lok Pin, Protruding Shear Head, 3/16 Nom DIA, 10-32 Thread, 1/2" Max Grip, 160000-180000 PSI, Tensile Strength, Alloy Steel | EA |
| HL18PB6-9 | Hi-Lok Pin, Protruding Shear Head, 3/16 Nom DIA, 10-32 Thread, 9/16" Max Grip, 160000-180000 PSI, Tensile Strength, Alloy Steel | EA |
| HL19PB6-10 | Hi-Lok Pin, 100 Deg Flush Shear Head, 3/16 Nom DIA, 10-32 Thread, 5/8" Max Grip, 160000-180000 PSI, Tensile Strength, Alloy Steel | EA |
| HL19PB6-11 | Hi-Lok Pin, 100 Deg Flush Shear Head, 3/16 Nom DIA, 10-32 Thread, 11/16" Max Grip, 160000-180000 PSI, Tensile Strength, Alloy Steel | EA |
| HL19PB6-7 | Hi-Lok Pin, 100 Deg Flush Shear Head, 3/16 Nom DIA, 10-32 Thread, 7/16" Max Grip, 160000-180000 PSI, Tensile Strength, Alloy Steel | EA |
| HL19PB6-9 | Hi-Lok Pin, 100 Deg Flush Shear Head, 3/16 Nom DIA, 10-32 Thread, 9/16" Max Grip, 160000-180000 PSI, Tensile Strength, Alloy Steel | EA |
| HL62PB6-4 | Hi-Lok Pin, Protruding Shear Head, OVERSIZE, 3/16 Nom DIA, 10-32 Thread, 1/4" Max Grip, 160000-180000 PSI, Tensile Strength, Alloy Steel | EA |
| HL62PB6-5 | Hi-Lok Pin, Protruding Shear Head, OVERSIZE, 3/16 Nom DIA, 10-32 Thread, 5/16" Max Grip, 160000-180000 PSI, Tensile Strength, Alloy Steel | EA |
| HL62PB6-7 | Hi-Lok Pin, Protruding Shear Head, OVERSIZE, 3/16 Nom DIA, 10-32 Thread, 7/16" Max Grip, 160000-180000 PSI, Tensile Strength, Alloy Steel | EA |
| HL62PB6-8 | Hi-Lok Pin, Protruding Shear Head, OVERSIZE, 3/16 Nom DIA, 10-32 Thread, 1/2" Max Grip, 160000-180000 PSI, Tensile Strength, Alloy Steel | EA |
| HL70-5 | Hi-Lok Collar, Shear Application, 5/32" Pin Nom DIA, 8-32 UNJF-3B Thread, Aluminum Alloy | EA |
| HL82-6APBW | Hi-Lok Collar, Shear Application, Self-Aligning Collar Assembly, 3/16" Pin Nom DIA, 10-32 UNJF-3B Thread, Collar Washer Combination CAD II Plated Washer | EA |

| Part Number | Part Description | Unit of Measure |
|----------------------|---|-----------------|
| HM4 | Bearing, 1/4" DIA, with screw, 1/4-28 | EA |
| HM-8G | Heim Rod End Bearing, 1/2" Bore | EA |
| HMX10G | Bearing, Screw End, 5/8" | EA |
| HMX12G | Bearing, Screw End, 3/4" | EA |
| HN5P54-1-1 | Plunger, Fastener, 1" Length | EA |
| IT18R9C2 | Cable Tie, ID Label, Natural, 18lb, 4" (100pcs/pkg) | EA |
| K1625B | Valve, Fuel Drain | EA |
| LH3849-048 | Nut | EA |
| LH3849-054 | Nut (same as H16-5) | EA |
| LP22F40P8 | Screw | EA |
| LP526-632R6 | Screw, Spreader Bar Fairing (6000/6100) | EA |
| LP526-632R6 | Screw, Spreader Bar Fairing (6000/6100) | EA |
| LP526-632R8 | Screw - Float Spreader Bar (8000) | EA |
| LW31SSH0.88 | Bolt, 1/4-28 Thread, Head Holes | EA |
| M3331 | Seal, Oil | EA |
| M83248/1-011 | O Ring | EA |
| M83248/1-014 | O Ring | EA |
| M83248/1-016 | O Ring | EA |
| M83248/1-020 | O Ring | EA |
| M83248/1-024 | O Ring | EA |
| M83248/1-113 | O Ring | EA |
| M83248/1-116 | O Ring | EA |
| M83248/1-130 | O Ring | EA |
| M83248/1-137 | O Ring | EA |
| M83248/1-212 | O Ring | EA |
| M83248/1-903 | O Ring | EA |
| M83248/1-904 | O Ring | EA |
| M83248/1-906 | O Ring | EA |
| M83248/1-912 | O Ring | EA |
| M83248/2-904 | O Ring | EA |
| M83248/2-905 | O Ring | EA |
| M83248/2-906 | O Ring | EA |
| M83248/2-908 | O Ring | EA |
| MB100881-A | Washer, 3/8" DIA | EA |
| MB100881-B | Washer, 3/8" DIA | EA |
| MB100888-B | Stud, Engine Flexible Mount, Manufactured & Plated | EA |
| MB100891-A | Washer, 1" DIA | EA |
| MB100891-B | Washer, 1" DIA | EA |
| MB100892 | Washer, 1-1/2" DIA | EA |
| MB108794-A | Washer, 3/8" DIA | EA |
| MB108794-B | Washer, 3/8" DIA | EA |
| MB56C902-5 | Brushes, 12V Motor | EA |
| MIL-H6000 1 1/2IN | Hose, Black Rubber, 1-1/2", ALT # mildtl6000c1-12 | FT |
| MIL-H6000 1 1/4IN | Hose, Black Rubber, 1-1/4" | FT |
| MIL-H6000 1/2IN | Hose, Black Rubber, 1/2" | FT |
| MIL-H6000 1/4IN | Hose, Black Rubber, 1/4" | FT |
| MIL-H6000 1IN | Hose, Black Rubber, 1", ALT # mildtl6000c1 | FT |
| MIL-H6000 2IN | Hose 2" / atl # mildtl6000c2 | FT |
| MIL-H6000 3/4IN | Hose, Black Rubber, 3/4" | FT |
| MIL-H6000 3/8IN | Hose, Black Rubber, 3/8", ALT # mildtl6000c38 | FT |

| Part Number | Part Description | Unit of Measure |
|------------------|--|-----------------|
| MIL-H6000 5/16IN | Hose, Black Rubber, 5/16", ALT # mildtl6000516 | FT |
| MIL-H6000 5/8IN | Hose, Black Rubber, 5/8" | FT |
| MIL-H6000 7/8IN | Hose, Black Rubber, 7/8" | FT |
| MK172-76-02 | Washer, Fiction Cone, Cable Craft Installation, 3/8" DIA | EA |
| MK182-76-01 | Washer, Fiction Cone, Cable Craft Installation, 3/8" DIA | EA |
| MK206-76-01 | Washer, Fiction Cone, Cable Craft Installation, 3/8" DIA | EA |
| MS15002-1 | Fitting, Grease, Straight, 33/64" Length, 5/32" Hexagon | EA |
| MS16562-15 | Pin, Spring, Tubular, 0.078" DIA, 1/2" Nominal Size Length, Slotted, Carbon Steel | EA |
| MS16562-195 | Pin, Spring, Tubular, 0.062" DIA, 0.562" Nominal Size Length, Slotted, Corrosion Resistant Steel | EA |
| MS16562-75 | Pin, Spring, Tubular, Slotted | EA |
| MS16624-1025 | Retaining Ring, Basic Inverted | EA |
| MS16624-1037 | Retaining Ring, Basic Inverted | EA |
| MS16624-1040 | Retaining Ring, Basic Inverted | EA |
| MS16624-1043 | Retaining Ring, Basic Inverted | EA |
| MS16624-1050 | Retaining Ring, Basic Inverted | EA |
| MS16624-1062 | Retaining Ring, Basic Inverted | EA |
| MS16624-1075 | Retaining Ring, Basic Inverted | EA |
| MS16624-1087 | Retaining Ring, Basic Inverted | EA |
| MS16624-1262 | Retaining Ring, Basic Inverted | EA |
| MS16625-1090 | Retaining Ring, Basic Internal | EA |
| MS16625-1118 | Retaining Ring, Basic Internal | EA |
| MS16995-11 | Screw, Indented Hex Head S/S | EA |
| MS16995-25 | Screw - SS 8.32 x 3/8 | EA |
| MS16995-26 | Screw | EA |
| MS16995-36 | Screw | EA |
| MS16995-48 | Screw | EA |
| MS16996-10 | Cap Screw (SS 1032x1/2) | EA |
| MS16996-11 | Cap Screw (SS 1032x5/8) | EA |
| MS16996-12 | Cap Screw (SS 1032x3/4) | EA |
| MS16997-105 | Bolt | EA |
| MS16997-26 | Bolt | EA |
| MS16997-38 | Bolt | EA |
| MS16997-44 | Bolt | EA |
| MS16997-50 | Bolt | EA |
| MS16997-60 | Bolt | EA |
| MS16997-66 | Bolt | EA |
| MS16997-77 | Bolt | EA |
| MS16997-80 | Bolt | EA |
| MS16997-83 | Bolt | EA |
| MS16997-88 | Bolt | EA |
| MS16997-99 | Bolt | EA |
| MS16998-26 | Bolt | EA |
| MS16998-40 | Bolt | EA |
| MS17825-10 | Nut, SelfLocking Castellated, 5/8-18 Thread, Nonmetallic Insert | EA |
| MS17825-3 | Nut, SelfLocking Castellated, 10-32 Thread, Nonmetallic Insert | EA |
| MS17825-4 | Nut, SelfLocking Castellated, 1/4-28 Thread, Nonmetallic Insert | EA |
| MS17825-5 | Nut, SelfLocking Castellated, 5/16-24 Thread, Nonmetallic Insert | EA |
| MS17825-6 | Nut, SelfLocking Castellated, 3/8-24 Thread, Nonmetallic Insert | EA |
| MS17826-12 | Nut, SelfLocking Castellated, 3/4-16 Thread, Low Height, Nonmetallic | EA |
| MS17826-3 | Nut, SelfLocking Castellated, 10-32 Thread, Low Height, Nonmetallic Insert | EA |

| Part Number | Part Description | Unit of Measure |
|-----------------|---|-----------------|
| MS17826-5 | Nut, SelfLocking Castellated, 5/16-24 Thread, Low Height, Nonmetallic Insert | EA |
| MS17826-6 | Nut, SelfLocking Castellated, 3/8-24 Thread, Low Height, Nonmetallic Insert | EA |
| MS20002-14 | Washer, High Strength, To Fit DIA 7/8", Plain | EA |
| MS20002-16 | Washer, High Strength, To Fit DIA 1", Plain | EA |
| MS20002-18 | Washer, High Strength, To Fit DIA 1-1/8", Plain | EA |
| MS20002-4 | Washer, High Strength, To Fit DIA 1/4", Plain | EA |
| MS20002-5 | Washer, High Strength, To Fit DIA 5/16", Plain | EA |
| MS20002-6 | Washer, High Strength, To Fit DIA 3/8", Plain | EA |
| MS20002C10 | Washer, High Strength, To Fit DIA 5/8", Countersunk | EA |
| MS20002C4 | Washer, High Strength, To Fit DIA 1/4", Countersunk | EA |
| MS20002C5 | Washer, High Strength, To Fit DIA 5/16", Countersunk | EA |
| MS20002C6 | Washer, High Strength, To Fit DIA 3/8", Countersunk | EA |
| MS20002C7 | Washer, High Strength, To Fit DIA 7/16", Countersunk | EA |
| MS20002C8 | Washer, High Strength, To Fit DIA 1/2", Countersunk | EA |
| MS20002C9 | Washer, High Strength, To Fit DIA 9/16", Countersunk | EA |
| MS20004-16 | Bolt- .250-28 UNF, 1.500 Lg, Grip 1.000, Stl | EA |
| MS20004-4 | Bolt, Internal Wrenching, 1/2-28 Thread, 0.25 Grip | EA |
| MS20004H8 | Bolt, Internal Wrenching, 1/4-28 Thread, 1/2" Grip, 1" Length, Hole in Head | EA |
| MS20005-37 | Bolt, Internal Wrenching, 5/16-24 Thread, 2-5/16" Grip | EA |
| MS20005-38 | Bolt, Internal Wrenching, 5/16-24 Thread, 2-3/8" Grip | EA |
| MS20005-44 | Bolt, Internal Wrenching, 5/16-24 Thread | EA |
| MS20005-50 | Bolt, Internal Wrenching, 5/16-24 Thread, 3-1/8" Grip | EA |
| MS20006-20 | Bolt, Internal Wrenching, 3/8-24 Thread, 1-1/4" Grip | EA |
| MS20006-20 | Bolt, Internal Wrenching, 3/8-24 Thread, 1-1/4" Grip | EA |
| MS20006-24 | Bolt | EA |
| MS20006-30 | Bolt, Internal Wrenching, 3/8-24 Thread, 1-7/8" Grip | EA |
| MS20006-36 | Bolt, Internal Wrenching, 3/8-24 Thread, 2-1/8" Grip | EA |
| MS20006-38 | Bolt, Internal Wrenching, 3/8-24 Thread, 2-3/8" Grip | EA |
| MS20006-44 | Bolt, Internal Wrenching, 3/8-24 Thread, 2-3/4" Grip | EA |
| MS20006-50 | Bolt, Internal Wrenching, 3/8-24 Thread, 3-1/8" Grip | EA |
| MS20006-8 | Bolt | EA |
| MS20007-13 | Bolt | EA |
| MS20007-16 | Bolt | EA |
| MS20007-27 | Bolt | EA |
| MS20007-28 | Bolt | EA |
| MS20007-30 | Block | EA |
| MS20007-36 | Bolt | EA |
| MS20008-15 | Bolt | EA |
| MS20034-1 | Bolt | EA |
| MS20036-5 | Bolt | EA |
| MS20074-03-03 | Bolt, Drilled Head, Coarse Thread, 10-24 Thread, 0.469" Length, 1/16" Grip | EA |
| MS20074-03-05 | Bolt, Drilled Head, Coarse Thread, 10-24 Thread, 0.657" Length, 1/8" Grip | EA |
| MS20074-04-03 | Bolt, Drilled Head, Coarse Thread, 1/4-20 Thread, 0.469" Length, 1/16" Grip | EA |
| MS20074-04-06 | Bolt, Drilled Head, Coarse Thread, 1/4-20 Thread, 0.781" Length, 1/4" Grip | EA |
| MS20074-06-05 | Bolt, Drilled Head, Coarse Thread, 3/8-24 Thread, 0.657" Length, 1/8" Grip | EA |
| MS20115F2 | Shackle, Wire Rope | EA |
| MS20220-1 | Pulley, For Cable Size 1/8, 5/32 & 3/16, High Pressure Laminated Phenolic | EA |
| MS20220-2 | Pulley, For Cable Size 1/8, 5/32 & 3/16, 3.005" Outside DIA, High Pressure Laminated Phenolic | EA |
| MS20257-C4-7200 | Piano Hinge SS 6ft length | FT |

| Part Number | Part Description | Unit of Measure |
|---------------|--|-----------------|
| MS20365-720A | Nut, SelfLocking, 7/16-20 Thread, Corrosion Resistant, Low Height, Nylon Insert, 250 Deg | EA |
| MS20392-10C41 | Pin, Clevis, 1.281" Grip Length, 1/8" DIA | EA |
| MS20392-10C41 | Pin, Clevis, 1.281" Grip Length, 1/8" DIA | EA |
| MS20392-1C11 | Pin, Clevis, 1/8" DIA, 11/32" Grip, Alloy Steel | EA |
| MS20392-1C13 | Pin, Clevis, 1/8" DIA, 13/32" Grip, Alloy Steel | EA |
| MS20392-1C15 | Pin, Clevis, 1/8" DIA, 15/32" Grip, Alloy Steel | EA |
| MS20392-1C33 | Pin, Clevis, 1/8" DIA, 1-1/32" Grip, Alloy Steel | EA |
| MS20392-1C35 | Pin, Clevis, 1/8" DIA, 1-3/32" Grip, Alloy Steel | EA |
| MS20392-1C41 | Pin, Clevis, 1/8" DIA, 1-9/32" Grip, Alloy Steel | EA |
| MS20392-1C53 | Pin, Clevis, 1/8" DIA, 1-21/32" Grip, Alloy Steel | EA |
| MS20392-1C57 | Pin, Clevis, 1/8" DIA, 1-25/32" Grip, Alloy Steel | EA |
| MS20392-1C9 | Pin, Clevis, 1/8" DIA, 9/32" Grip, Alloy Steel | EA |
| MS20392-2C11 | Pin, Clevis, 3/16" DIA, 11/32" Grip, Alloy Steel | EA |
| MS20392-2C13 | Pin, Clevis, 3/16" DIA, 13/32" Grip, Alloy Steel | EA |
| MS20392-2C15 | Pin, Clevis, 3/16" DIA, 15/32" Grip, Alloy Steel | EA |
| MS20392-2C17 | Pin, Clevis, 3/16" DIA, 17/32" Grip, Alloy Steel | EA |
| MS20392-2C19 | Pin, Clevis, 3/16" DIA, 19/32" Grip, Alloy Steel | EA |
| MS20392-2C29 | Pin, Clevis, 3/16" DIA, 29/32" Grip, Alloy Steel | EA |
| MS20392-2C35 | Pin, Clevis, 3/16" DIA, 1-3/32" Grip, Alloy Steel | EA |
| MS20392-2C41 | Pin, Clevis, 3/16" DIA, 1-9/32" Grip, Alloy Steel | EA |
| MS20392-2C49 | Pin, Clevis, 3/16" DIA, 1-17/32" Grip, Alloy Steel | EA |
| MS20392-2C51 | Pin, Clevis, 3/16" DIA, 1-19/32" Grip, Alloy Steel | EA |
| MS20392-2C57 | Pin, Clevis, 3/16" DIA, 1-25/32" Grip, Alloy Steel | EA |
| MS20392-2C65 | Pin, Clevis, 3/16" DIA, 2-1/32" Grip, Alloy Steel | EA |
| MS20392-2C7 | Pin, Clevis, 3/16" DIA, 7/32" Grip, Alloy Steel | EA |
| MS20392-2C83 | Pin, Clevis, 3/16" DIA, 2-19/32" Grip, Alloy Steel | EA |
| MS20392-2C9 | Pin, Clevis, 3/16" DIA, 9/32" Grip, Alloy Steel | EA |
| MS20392-3C11 | Pin, Clevis, 1/4" DIA, 11/32" Grip, Alloy Steel | EA |
| MS20392-3C13 | Pin, Clevis, 1/4" DIA, 13/32" Grip, Alloy Steel | EA |
| MS20392-3C15 | Pin, Clevis, 1/4" DIA, 15/32" Grip, Alloy Steel | EA |
| MS20392-3C17 | Pin, Clevis, 1/4" DIA, 17/32" Grip, Alloy Steel | EA |
| MS20392-3C23 | Pin, Clevis, 1/4" DIA, 23/32" Grip, Alloy Steel | EA |
| MS20392-3C25 | Pin, Clevis, 1/4" DIA, 25/32" Grip, Alloy Steel | EA |
| MS20392-3C41 | Pin, Clevis, 1/4" DIA, 1-9/32" Grip, Alloy Steel | EA |
| MS20392-3C45 | Pin, Clevis, 1/4" DIA, 1-11/32" Grip, Alloy Steel | EA |
| MS20392-3C51 | Pin, Clevis, 1/4" DIA, 1.59" Grip | EA |
| MS20392-3C55 | Pin, Clevis, 1/4" DIA, 1-21/32" Grip, Alloy Steel | EA |
| MS20392-3C65 | Pin, Clevis, 1/4" DIA, 2-1/32" Grip, Alloy Steel | EA |
| MS20392-4C17 | Pin, Clevis, 3/8" DIA, 17/32" Grip, Alloy Steel | EA |
| MS20392-4C25 | Pin, Clevis, 3/8" DIA, 25/32" Grip, Alloy Steel | EA |
| MS20392-4C33 | Pin, Clevis, 3/8" DIA, 1-1/32" Grip, Alloy Steel | EA |
| MS20392-4C47 | Pin, Clevis, 5/16" DIA, 1-15/32" Grip, Alloy Steel | EA |
| MS20392-5C19 | Pin, Clevis, 3/8" DIA, 19/32" Grip, Alloy Steel | EA |
| MS20392-5C21 | Pin, Clevis, 3/8" DIA, 21/32" Grip, Alloy Steel | EA |
| MS20392-5C25 | Pin, Clevis, 3/8" DIA, 25/32" Grip, Alloy Steel | EA |
| MS20392-6C21 | Pin, Clevis, 1/2" DIA, 21/32" Grip, Alloy Steel | EA |
| MS20392-6C25 | Pin, Clevis, 1/2" DIA, 25/32" Grip, Alloy Steel | EA |
| MS20392-7C27 | Pin, Clevis, 1/2" DIA, 27/32" Grip, Alloy Steel | EA |
| MS20392-8C31 | Pin, Clevis, 9/16" DIA, 31/32" Grip, Alloy Steel | EA |
| MS20392-9C33 | Pin, Clevis, 5/8" DIA, 1-1/32" Grip, Alloy Steel | EA |
| MS20426AD3-3 | Rivet, Flush,3/32Dia, 3/16Lg, 2117 | LB |

| Part Number | Part Description | Unit of Measure |
|----------------|---|-----------------|
| MS20426AD4-6.5 | Rivet, Flush | LB |
| MS20426AD4-7 | Rivet, Flush | LB |
| MS20426AD6-6 | Rivet | EA |
| MS20427M4-10 | Rivet, Monel | EA |
| MS20427M4-7 | Rivet | EA |
| MS20427M4-8 | Rivet | EA |
| MS20427M4-9 | Rivet | EA |
| MS20470AD5-10 | Rivet 1 lb | BG |
| MS20470AD5-10 | Rivet 1 lb | BG |
| MS20613-4P10 | Rivet Solid, Carbon Steel, 1/8" DIA, 5/8" Length, Universal Head | EA |
| MS20613-4P4 | Rivet Solid, Carbon Steel, 1/8" DIA, 1/4" Length, Universal Head | EA |
| MS20613-4P6 | Rivet Solid, Carbon Steel, 1/8" DIA, 3/8" Length, Universal Head | EA |
| MS20613-4P7 | Rivet Solid, Carbon Steel, 1/8" DIA, 7/16" Length, Universal Head | EA |
| MS20615-4M10 | Rivet Monel, Universal Head, 1/8" DIA, 5/8" Length | EA |
| MS20615-4M4 | Rivet, Monel | EA |
| MS20615-4M5 | Rivet, Monel | EA |
| MS20615-4M6 | Rivet Monel, Universal Head, 1/8" DIA, 3/8" Length | EA |
| MS20615-4M7 | Rivet Monel, Universal Head, 1/8" DIA, 7/16" Length | EA |
| MS20615-4M8 | Rivet, Monel | EA |
| MS20664C2 | Ball & Shank, Cable End, Cable DIA 1/16", Minimum Breaking Strength 400 | EA |
| MS20664C3 | Ball & Shank, Cable End, Cable DIA 3/32", Minimum Breaking Strength 920 | EA |
| MS20664C4 | Ball & Shank, Cable End, Cable DIA 1/8", Minimum Breaking Strength 2000 | EA |
| MS20664C5 | Ball & Shank, Cable End, Cable DIA 5/32", Minimum Breaking Strength 2800 | EA |
| MS20667-2 | Fork End, Swageable Ball and Double Shank, Cable DIA 1/16", Stainless Steel | EA |
| MS20667-3 | Fork End, Swageable Ball and Double Shank, Cable DIA 3/32", Stainless Steel | EA |
| MS20667-4 | Fork End, Swageable Ball and Double Shank, Cable DIA 1/8", Stainless Steel | EA |
| MS20667-5 | Fork End, Swageable Ball and Double Shank, Cable DIA 5/32", Stainless Steel | EA |
| MS20668-2 | Eye End, Swageable, Cable DIA 1/16", Stainless Steel | EA |
| MS20668-3 | Eye End, 2.16" Length, 3/32" Cable DIA | EA |
| MS20668-4 | Eye End, 2.6" Length, 1/8" Cable DIA | EA |
| MS20819-10 | Sleeve, Flared Tube Fitting, 5/8" Tube DIA, Steel | EA |
| MS20819-10D | Sleeve, Flared Tube Fitting, 5/8" Tube DIA, Aluminum | EA |
| MS20819-16 | Sleeve, Flared Tube Fitting, 1" Tube DIA, Steel | EA |
| MS20819-2D | Sleeve, Flared Tube Fitting, 1/8" Tube DIA, Aluminum | EA |
| MS20819-3D | Sleeve, Flared Tube Fitting, 3/16" Tube DIA, Aluminum | EA |
| MS20819-4 | Sleeve, Flared Tube Fitting, 1/4" Tube DIA, Steel | EA |
| MS20819-4D | Sleeve, Flared Tube Fitting, 1/4" Tube DIA, Aluminum | EA |
| MS20819-5D | Sleeve, Flared Tube Fitting, 5/16" Tube DIA, Aluminum | EA |
| MS20819-6 | Sleeve, Flared Tube Fitting, 3/8" Tube DIA, Steel | EA |
| MS20819-6D | Sleeve, Flared Tube Fitting, 3/8" Tube DIA, Aluminum | EA |
| MS20819-8D | Sleeve, Flared Tube Fitting, 1/2" Tube DIA, Aluminum | EA |
| MS20822-10D | Elbow, Flared Tube and Pipe Threads, 90 Deg, 7/8-14 Tube Thread, 1/2-20 Pipe Thread, Aluminum | EA |
| MS20822-2D | Elbow, Flared Tube and Pipe Threads, 90 Deg, 5/16-24 Tube Thread, 5-44 Pipe Thread, Aluminum | EA |
| MS20822-3D | Elbow, Flared Tube and Pipe Threads, 90 Deg, 3/8-24 Tube Thread, 5-44 Pipe Thread, Aluminum | EA |

| Part Number | Part Description | Unit of Measure |
|--------------|--|-----------------|
| MS20822-4 | Elbow, 90 Deg, Flared Tube to Pipe Thread, 1/4" Tube Size, 1/8" Pipe Thread | EA |
| MS20822-4-4 | Elbow Fitting, Flared Tube and Pipe Threads, 90 Deg, 7/16-20 Tube Thread, 1/4-28 Pipe Thread, Steel | EA |
| MS20822-4-4D | Elbow, Flared Tube and Pipe Threads, 90 Deg, 7/16-20 Tube Thread, 1/4-28 Pipe Thread, Aluminum | EA |
| MS20822-4D | Elbow Fitting, Flared Tube and Pipe Threads, 90 Deg, 7/16-20 Tube Thread, 5-44 Pipe Thread, Aluminum | EA |
| MS20822-5-4D | Elbow, Flared Tube and Pipe Threads, 90 Deg, 1/2-20 Tube Thread, 1/4-28 Pipe Thread, Aluminum | EA |
| MS20822-5D | Elbow, Flared Tube and Pipe Threads, 90 Deg, 1/2-20 Tube Thread, 5-44 Pipe Thread, Steel | EA |
| MS20822-6 | Elbow, Flared Tube and Pipe Threads, 90 Deg, 9/16-18 Tube Thread, 1/4-28 Pipe Thread, Steel | EA |
| MS20822-6D | Elbow, Flared Tube and Pipe Threads, 90 Deg, 9/16-18 Tube Thread, 1/4-28 Pipe Thread, Aluminum | EA |
| MS20822-8D | Elbow, Flared Tube and Pipe Threads, 90 Deg, 3/4-16 Tube Thread, 3/8-24 Pipe Thread, Aluminum | EA |
| MS20823-3D | Elbow, Pipe to Flared Tube, 45 Deg, 3/8-24 Tube Thread, 5-44 Pipe Thread, Aluminum | EA |
| MS20823-4 | Elbow, Pipe to Flared Tube, 45 Deg, 7/16-20 Tube Thread, 5-44 Pipe Thread, Steel | EA |
| MS20823-4D | Elbow, Pipe to Flared Tube, 45 Deg, 7/16-20 Tube Thread, 5-44 Pipe Thread, Aluminum | EA |
| MS20823-5D | Elbow, Pipe to Flared Tube, 45 Deg, 1/2-20 Tube Thread, 5-44 Pipe Thread, Aluminum | EA |
| MS20823-6 | Elbow, Pipe to Flared Tube, 45 Deg, Steel, Thread 9/16-18, Tube OD 3/8 | EA |
| MS20823-6D | Elbow, Pipe to Flared Tube, 45 Deg, 9/16-18 Tube Thread, 1/4-28 Pipe Thread, Steel | EA |
| MS20823-8 | Elbow, Pipe to Flared Tube, 45 Deg, 3/4-16 Tube Thread, 3/8-24 Pipe Thread, Steel | EA |
| MS20823-8D | Elbow, Pipe to Flared Tube, 45 Deg, 3/4-16 Tube Thread, 3/8-24 Pipe Thread, Aluminum | EA |
| MS20825-4D | Tee, Pipe to Tube, Pipe Thread on Side, 7/16-20 Tube Thread, 5-44 Pipe Thread, Aluminum | EA |
| MS20825-6D | Tee, Pipe to Tube, Pipe Thread on Side, 9/16-18 Tube Thread, 1/4-28 Pipe Thread, Aluminum | EA |
| MS20826-10D | Tee, Pipe to Tube, Pipe Thread on Run, 7/8-14 Tube Thread, 1/2-20 Pipe Thread, Aluminum | EA |
| MS20826-2D | Tee, Pipe to Tube, Pipe Thread on Run, 5/16-24 Tube Thread, 5-44 Pipe Thread, Aluminum | EA |
| MS20826-3D | Tee, Pipe to Tube, Pipe Thread on Run, 3/8-24 Tube Thread, 5-44 Pipe Thread, Aluminum | EA |
| MS20826-4D | Tee, Pipe to Tube, Pipe Thread on Run, 7/16-20 Tube Thread, 5-44 Pipe Thread, Aluminum | EA |
| MS20826-5D | Tee, Pipe to Tube, Pipe Thread on Run, 1/2-20 Tube Thread, 5-44 Pipe Thread, Aluminum | EA |
| MS20826-6D | Tee, Pipe to Tube, Pipe Thread on Run, 9/16-18 Tube Thread, 1/4-28 Pipe Thread, Aluminum | EA |
| MS20913-1D | Plug | EA |
| MS20913-2D | Plug | EA |
| MS20995C25 | Safety Wire, 0.025" DIA | EA |
| MS20995C32 | Safety Wire, 0.032" DIA | EA |

| Part Number | Part Description | Unit of Measure |
|-------------|---|-----------------|
| MS20995C41 | Safety Wire, 0.041" DIA | EA |
| MS20995C51 | Safety Wire, 0.051" DIA | EA |
| MS21025-16 | Nut, Axle, Hex, Castellated, 1" | EA |
| MS21025-20 | Nut, Axle | EA |
| MS21025-24 | Nut, Axle | EA |
| MS21042-04 | Nut SelfLocking, Reduced Hexagon, 4-40 Thread, Reduced Height | EA |
| MS21042-06 | Nut SelfLocking, Reduced Hexagon, 6-32 Thread, Reduced Height | EA |
| MS21042-08 | Nut SelfLocking, Reduced Hexagon, 8-32 Thread, Reduced Height | EA |
| MS21042-3 | Nut SelfLocking, Reduced Hexagon, 10-32 Thread, Reduced Height | EA |
| MS21042-4 | Nut SelfLocking, Reduced Hexagon, 1/4-28 Thread, Reduced Height | EA |
| MS21042-5 | Nut SelfLocking, Reduced Hexagon, 5/16-24 Thread, Reduced Height | EA |
| MS21042-6 | Nut SelfLocking, Reduced Hexagon, 13/8-24 Thread, Reduced Height | EA |
| MS21042L06 | Nut SelfLocking, Reduced Hexagon, 6-32 Thread, Reduced Height, With Dry Film Lube | EA |
| MS21042L08 | Nut SelfLocking, Reduced Hexagon, 8-32 Thread, Reduced Height, With Dry Film Lube | EA |
| MS21042L3 | Nut SelfLocking, Reduced Hexagon, 10-32 Thread, Reduced Height, With Dry Film Lube | EA |
| MS21044C06 | Nut SelfLocking, Corrosion Resistant, 3/8-24 Thread, Regular Height, Nylon Insert, 250 Deg. | EA |
| MS21044C08 | Nut, Self Lock, (250 Deg), Nylon Insert, Corrosion Resistant, 8-32 | EA |
| MS21044C3 | Nut, Self Lock, (250 Deg), Nylon Insert, Corrosion Resistant, 10-32 | EA |
| MS21044C4 | Nut SelfLocking, Corrosion Resistant, 1/4-28 Thread, Regular Height, Nylon Insert, 250 Deg. | EA |
| MS21044C5 | Nut, Self-Locking, Regular Height, Nylon Insert, 250 Deg., Non-Metallic Insert, Corrosion Resistant Steel, Thread 0.3125-24 | EA |
| MS21044N04 | Nut, Self Lock, (250 Deg), Nylon Insert, Carbon Steel, 4-40 | EA |
| MS21044N10 | Nut SelfLocking, 5/8-18 Thread, Steel, Regular Height, Nylon Insert, 250 Deg, Non-Metallic | EA |
| MS21044N12 | Nut SelfLocking, 3/4-16 Thread, Steel, Regular Height, Nylon Insert, 250 Deg, Non-Metallic | EA |
| MS21044N18 | Nut SelfLocking, 1-1/8 - 12 Thread, Steel, Regular Height, Nylon Insert, 250 Deg, Non-Metallic | EA |
| MS21044N3 | NUT HEX LOCKING NYLON INSERT STEEL CAD 2, 10-32 | EA |
| MS21044N3 | NUT HEX LOCKING NYLON INSERT STEEL CAD 2, 10-32 | EA |
| MS21044N3 | NUT HEX LOCKING NYLON INSERT STEEL CAD 2, 10-32 | EA |
| MS21044N4 | NUT HEX LOCKING NYLON INSERT STEEL CAD 2, 1/4-28 | EA |
| MS21044N4 | NUT HEX LOCKING NYLON INSERT STEEL CAD 2, 1/4-28 | EA |
| MS21044N4 | NUT HEX LOCKING NYLON INSERT STEEL CAD 2, 1/4-28 | EA |
| MS21044N5 | NUT HEX LOCKING NYLON INSERT STEEL CAD 2, 5/16-24 | EA |
| MS21044N5 | NUT HEX LOCKING NYLON INSERT STEEL CAD 2, 5/16-24 | EA |
| MS21044N5 | NUT HEX LOCKING NYLON INSERT STEEL CAD 2, 5/16-24 | EA |
| MS21044N6 | Nut,Self Locking, Nylon Insert, 250 Deg, Steel, 0.375-24 Thread | EA |
| MS21044N6 | Nut,Self Locking, Nylon Insert, 250 Deg, Steel, 0.375-24 Thread | EA |
| MS21044N8 | Nut, SelfLocking, 1/2-20 Thread, Regular Height, Nylon Insert, 250 Deg. | EA |
| MS21044N8 | Nut, SelfLocking, 1/2-20 Thread, Regular Height, Nylon Insert, 250 Deg. | EA |
| MS21044N9 | Nut SelfLocking, 9/16-18 Thread, Steel, Regular Height, Nylon Insert, 250 Deg, Non-Metallic | EA |
| MS21045-06 | Nut SelfLocking, 3/8-24 Thread, Steel, Regular Height, All Metal, 450 Deg, Non-Dry Lub | EA |
| MS21045-08 | Nut SelfLocking, 1/2-20 Thread, Steel, Regular Height, All Metal, 450 Deg, Non-Dry Lub | EA |

| Part Number | Part Description | Unit of Measure |
|-------------|---|-----------------|
| MS21045-10 | Nut SelfLocking, 5/8-18 Thread, Steel, Regular Height, All Metal, 450 Deg, Non-Dry Lub | EA |
| MS21045-3 | Nut, Self Lock, Steel, 10-32 SEGMENTED | EA |
| MS21045-4 | Nut, Self Lock, Steel, 1/4-28 SEGMENTED | EA |
| MS21045-5 | Nut SelfLocking, 5/16-24 Thread, Steel, Regular Height, All Metal, 450 Deg, Non-Dry Lub | EA |
| MS21045-6 | Nut, Self Lock, Steel, 3/8-24 SEGMENTED | EA |
| MS21045-6 | Nut, Self Lock, Steel, 3/8-24 SEGMENTED | EA |
| MS21045-8 | Nut SelfLocking, 1/2-20 Thread, Steel, Regular Height, All Metal, 450 Deg, Non-Dry Lub | EA |
| MS21045-8 | Nut SelfLocking, 1/2-20 Thread, Steel, Regular Height, All Metal, 450 Deg, Non-Dry Lub | EA |
| MS21045C3 | Nut | EA |
| MS21045C4 | NUT, SELF LOCKING, 450 Deg, Thread Size 1/4-28 | EA |
| MS21045L08 | Nut SelfLocking, 0.164-32 Thread, Steel, Regular Height, All Metal, 450 Deg, Dry Lub | EA |
| MS21045L6 | Nut SelfLocking, 3/8-24 Thread, Steel, Regular Height, All Metal, 450 Deg, Dry Lub | EA |
| MS21047L06 | Nutplate, Two Lug, 6-32 Thread, Low Height | EA |
| MS21047L06K | Nutplate | EA |
| MS21047L08 | Nutplate, Two Lug, 8-32 Thread, Low Height | EA |
| MS21047L08 | Nutplate, Two Lug, 8-32 Thread, Low Height | EA |
| MS21047L08K | Nutplate, Two Lug, 8-32 Thread, Low Height, Countersunk Riveting Holes | EA |
| MS21047L3 | Nut Plate, Steal, Self locking, Std Spacing, Fixed, Two Lug 10-32 | EA |
| MS21047L3 | Nut Plate, Steal, Self locking, Std Spacing, Fixed, Two Lug 10-32 | EA |
| MS21047L3 | Nut Plate, Steal, Self locking, Std Spacing, Fixed, Two Lug 10-32 | EA |
| MS21047L3K | Nutplate, Two Lug, 10-32 Thread, Low Height, Countersunk Riveting Holes | EA |
| MS21047L4 | Nutplate, Two Lug, 1/4-28 Thread, Low Height | EA |
| MS21047L5 | Nutplate, Two Lug, 5/16-24 Thread, Low Height | EA |
| MS21047L6 | Nutplate, Two Lug, 3/8-24 Thread, Low Height | EA |
| MS21049L08 | Nutplate, Two Lug, Low Height 100 Deg. Countersunk, 8-32 Thread | EA |
| MS21049L08K | Nutplate, Two Lug, 8-32 Thread, Low Height, 100 Deg Countersunk Riveting Holes | EA |
| MS21049L3K | Nutplate, Two Lug, 10-32 Thread, Low Height, 100 Deg Countersunk Riveting Holes | EA |
| MS21051L08 | Nutplate, One Lug, 8-32 Thread | EA |
| MS21051L3 | Nutplate, One Lug, 10-32 Thread | EA |
| MS21051L3K | Nutplate, One Lug, 10-32 Thread, Countersunk Riveting Holes | EA |
| MS21051L4 | Nutplate, One Lug, 1/4-28 Thread | EA |
| MS21053L3 | Nutplate | EA |
| MS21055L08 | Nutplate, Corner, All Metal to 450 Deg, Size #8-32, Rivet Spacing 0.486" | EA |
| MS21055L3 | Nutplate, Corner, 10-32 Thread | EA |
| MS21059L08 | Nutplate, Two Lug, 8-32 Thread, Low Height, Floating | EA |
| MS21059L3 | Nutplate, Two Lug, 10-32 Thread, Low Height, Floating | EA |
| MS21059L3K | Nutplate, Two Lug, 10-32 Thread, Low Height, Floating, Countersunk Riveting Holes | EA |
| MS21059L4 | Nutplate, Two Lug, 1/4-28 Thread, Low Height, Floating | EA |
| MS21059L5 | Nutplate, Two Lug, 5/16-24 Thread, Low Height, Floating | EA |
| MS21060L3 | Anchor Nut | EA |
| MS21061L08 | Nutplate, One Lug, 8-32 Thread, Floating | EA |
| MS21061L3 | Nutplate, One Lug, 10-32 Thread, Floating | EA |
| MS21069L06 | Nutplate, Two Lug, 6-32 Thread, Low Height, Miniature | EA |

| Part Number | Part Description | Unit of Measure |
|---------------|---|-----------------|
| MS21069L08K | Nutplate, Two Lug, 8-32 Thread, Low Height, Miniature, Countersunk Riveting Holes | EA |
| MS21069L3 | Nutplate, Two Lug, 10-32 Thread, Low Height, Miniature | EA |
| MS21069L3K | Nutplate, Two Lug, 10-32 Thread, Low Height, Miniature, Countersunk Riveting Holes | EA |
| MS21071L06 | Nutplate, One Lug, 6-32 Thread, Low Height, Miniature | EA |
| MS21071L08 | Nutplate, One Lug, 8-32 Thread, Low Height, Miniature | EA |
| MS21071L3 | Nutplate, One Lug, 10-32 Thread, Low Height, Miniature | EA |
| MS21071L6 | Nutplate, One Lug, 3/8-24 Thread, Low Height, Miniature | EA |
| MS21073L08K | Nutplate, One Lug, Corner, 8-32 Thread, Low Height, Miniature, Countersunk Riveting Holes | EA |
| MS21073L3 | Nutplate, One Lug, Corner, 10-32 Thread, Low Height, Miniature | EA |
| MS21075-5N | Nutplate, Two Lug, 5/16-24 Thread, Low Height, Miniature, Floating | EA |
| MS21075L4N | Nutplate, Two Lug, 1/4-28 Thread, Low Height, Miniature, Floating | EA |
| MS21077-3K | Nutplate | EA |
| MS21078-08 | Nutplate, Two Lug, 10-32 Thread, Nylon Instart | EA |
| MS21078-3 | Nutplate, Two Lug, 8-32 Thread, Nylon Instart | EA |
| MS21078-4 | Nutplate, Two Lug, 1/4-28 Thread, Nylon Instart | EA |
| MS21080-3 | Nutplate, One Lug, 10-32 Thread, Nylon Instart | EA |
| MS21083N04 | Nut, SelfLocking, 4-40 Thread, Low Height, Steel, Nylon Insert, 250 Deg. | EA |
| MS21083N06 | Nut, SelfLocking, 6-32 Thread, Low Height, Steel, Nylon Insert, 250 Deg. | EA |
| MS21083N08 | Nut, SelfLocking, 8-32 Thread, Low Height, Steel, Nylon Insert, 250 Deg. | EA |
| MS21083N10 | Nut Selflocking, 5/8-18 Thread, Steel, Low Height, Nylon Insert, 250 Deg. | EA |
| MS21083N12 | Nut Selflocking, 3/4-16 Thread, Steel, Low Height, Nylon Insert, 250 Deg. | EA |
| MS21083N4 | NUT HEX LOCKING NYLON INSERT STL CAD 2, 1/4-28 | EA |
| MS21083N4 | NUT HEX LOCKING NYLON INSERT STL CAD 2, 1/4-28 | EA |
| MS21083N5 | Nut, SelfLocking, 5/16-24 Thread, Low Height, Steel, Nylon Insert, 250 Deg. | EA |
| MS21083N6 | NUT HEX LOCKING NYLON INSERT STL CAD 2, 3/8-24 | EA |
| MS21083N6 | NUT HEX LOCKING NYLON INSERT STL CAD 2, 3/8-24 | EA |
| MS21083N7 | Nut, SelfLocking, 7/16-20 Thread, Low Height, Nylon Insert, 250 Deg. | EA |
| MS21083N7 | Nut, SelfLocking, 7/16-20 Thread, Low Height, Nylon Insert, 250 Deg. | EA |
| MS21083N8 | Nut, SelfLocking, 1/2-20 Thread, Low Height, Steel, Nylon Insert, 250 Deg. | EA |
| MS21083N9 | Nut, SelfLocking, 9/16-18 Thread, Low Height, Steel, Nylon Insert, 250 Deg. | EA |
| MS21086L08 | Nutplate, Reduced Rivet Spacing, Side By Side, 8-32 Thread | EA |
| MS21086L3 | Nutplate, Reduced Rivet Spacing, Side By Side, 10-32 Thread | EA |
| MS21245L8 | Nut | EA |
| MS21250-05DIR | Bolt, External Wrenching, 3/4-16 Thread, 1/4" Grip, Flanged | EA |
| MS21250H04026 | Bolt, External Wrenching, 10-32 Thread, 1-1/2" Grip, Drilled Head, Flanged | EA |
| MS21251B2L | Turnbuckle, Barrel, 6-40 Thread, 4" Length | EA |
| MS21251B2S | Turnbuckle, Barrel, 6-40 Thread, 2-1/4" Length | EA |
| MS21251B3L | Turnbuckle, Barrel, 10-32 Thread, 4" Length | EA |
| MS21251B3S | Turnbuckle, Barrel, 10-32 Thread, 4" Length | EA |
| MS21251B3S | Turnbuckle, Barrel, 10-32 Thread, 4" Length | EA |
| MS21251B5L | Turnbuckle, Barrel, 1/4-28 Thread, 4" Length | EA |
| MS21251B5S | Turnbuckle, Barrel, 1/4-28 Thread, 1-1/4" Length | EA |
| MS21252-3LS | Turnbuckle Fork, Threaded Left Short, 10-32 Thread, 3/32 Cable Size | EA |
| MS21252-3RL | Turnbuckle Fork, Threaded Right Long, 10-32 Thread, 3/32 Cable Size | EA |
| MS21252-3RS | Turnbuckle Fork, Threaded Right Short, 10-32 Thread, 3/32 Cable Size | EA |
| MS21252-4LL | Turnbuckle Fork, Threaded Left Long, 1/4-28 Thread, 1/8 Cable Size | EA |
| MS21252-4RL | Turnbuckle Fork, Threaded Right Long, 1/4-28 Thread, 1/8 Cable Size | EA |
| MS21252-4RS | Turnbuckle Fork, Threaded Right Short, 1/4-28 Thread, 1/8 Cable Size | EA |
| MS21252-5LL | Turnbuckle Fork, Threaded Left Long, 1/4-28 Thread, 5/32 Cable Size | EA |
| MS21252-5LS | Turnbuckle Fork, Threaded Left Short, 1/4-28 Thread, 5/32 Cable Size | EA |

| Part Number | Part Description | Unit of Measure |
|--------------|---|-----------------|
| MS21252-5RL | Turnbuckle Fork, Threaded Right Long, 1/4-28 Thread, 5/32 Cable Size | EA |
| MS21252-5RS | Turnbuckle Fork, Threaded Right Short, 1/4-28 Thread, 5/32 Cable Size | EA |
| MS21254-3LS | Turnbuckle Pin Eye, Left Short, 10-32 Thread, 3/32" Cable Size, 1-5/8" Length | EA |
| MS21254-3RS | Turnbuckle Pin Eye, Right Short, 10-32 Thread, 3/32" Cable Size, 1-5/8" Length | EA |
| MS21254-5RL | Pin Eye, 1/4" DIA, Thread 1/4-28 | EA |
| MS21255-3LS | Turnbuckle Cable Eye, Left Short, 10-32 Thread, 3/32" Cable Size, 1-5/8" Length | EA |
| MS21255-3RS | Turnbuckle Cable Eye, Right Short, 10-32 Thread, 3/32" Cable Size, 1-5/8" Length | EA |
| MS21260L3LH | Stud Terminal, Long End, Left Hand, 10-32 Thread, 3/32" Cable Size, Wire Rope, Stainless Steel | EA |
| MS21260L3RH | Stud Terminal, Long End, Right Hand, 10-32 Thread, 3/32" Cable Size, Wire Rope, Stainless Steel | EA |
| MS21260L4LH | Stud Terminal, Long End, Left Hand, 1/4-28 Thread, 1/8" Cable Size, Wire Rope, Stainless Steel | EA |
| MS21260L4RH | Stud Terminal, Long End, Right Hand, 1/4-28 Thread, 1/8" Cable Size, Wire Rope, Stainless Steel | EA |
| MS21260L5LH | Stud Terminal, Long End, Left Hand, 1/4-28 Thread, 5/32" Cable Size, Wire Rope, Stainless Steel | EA |
| MS21260L5RH | Stud Terminal, Long End, Right Hand, 1/4-28 Thread, 5/32" Cable Size, Wire Rope, Stainless Steel | EA |
| MS21260S2LH | Stud Terminal, Short End, Left Hand, 6-40 Thread, 1/16" Cable Size, Wire Rope, Stainless Steel | EA |
| MS21260S2RH | Stud Terminal, Short End, Right Hand, 6-40 Thread, 1/16" Cable Size, Wire Rope, Stainless Steel | EA |
| MS21260S3LH | Stud Terminal, Short End, Left Hand, 10-32 Thread, 3/32" Cable Size, Wire Rope, Stainless Steel | EA |
| MS21260S3RH | Stud Terminal, Short End, Right Hand, 10-32 Thread, 3/32" Cable Size, Wire Rope, Stainless Steel | EA |
| MS21260S4LH | Stud Terminal, Short End, Left Hand, 1/4-28 Thread, 1/8" Cable Size, Wire Rope, Stainless Steel | EA |
| MS21260S4RH | Stud Terminal, Short End, Right Hand, 1/4-28 Thread, 1/8" Cable Size, Wire Rope, Stainless Steel | EA |
| MS21260S5LH | Stud Terminal, Short End, Left Hand, 1/4-28 Thread, 5/32" Cable Size, Wire Rope, Stainless Steel | EA |
| MS21260S5RH | Stud Terminal, Short End, Right Hand, 1/4-28 Thread, 5/32" Cable Size, Wire Rope, Stainless Steel | EA |
| MS21266-1N | Grommet Edging, 1 Ft. Length, 0.150 Width, and 0.056 Width | EA |
| MS21266-3N | Grommet Edging, 1 Ft. Width, 0.220 Length and 0.131 Width | EA |
| MS21919DG10 | Clamp, Loop | EA |
| MS21919DG56 | Clamp, Loop | EA |
| MS21919DG9 | Clamp, Loop | EA |
| MS21919WCG42 | Adel Clamp, High Heat | EA |
| MS21919WDG10 | Clamp, To Fit DIA 5/8", Aluminum Band, Chloroprene Cushion | EA |
| MS21919WDG11 | Clamp, To Fit DIA 11/16", Aluminum Band, Chloroprene Cushion | EA |
| MS21919WDG12 | Clamp, To Fit DIA 3/4", Aluminum Band, Chloroprene Cushion | EA |

| Part Number | Part Description | Unit of Measure |
|--------------|---|-----------------|
| MS21919WDG12 | Clamp, To Fit DIA 3/4", Aluminum Band, Chloroprene Cushion | EA |
| MS21919WDG13 | Clamp, To Fit DIA 13/16", Aluminum Band, Chloroprene Cushion | EA |
| MS21919WDG14 | Clamp, To Fit DIA 7/8", Aluminum Band, Chloroprene Cushion | EA |
| MS21919WDG14 | Clamp, To Fit DIA 7/8", Aluminum Band, Chloroprene Cushion | EA |
| MS21919WDG15 | Clamp, To Fit DIA 15/16", Aluminum Band, Chloroprene Cushion | EA |
| MS21919WDG16 | Clamp, To Fit DIA 1", Aluminum Band, Chloroprene Cushion | EA |
| MS21919WDG17 | Clamp, To Fit DIA 1-1/16", Aluminum Band, Chloroprene Cushion | EA |
| MS21919WDG18 | Clamp, To Fit DIA 1-1/8", Aluminum Band, Chloroprene Cushion | EA |
| ms21919wdg19 | Clamp, To Fit DIA 1-3/16", Aluminum Band, Chloroprene Cushion | EA |
| MS21919WDG2 | Clamp, To Fit DIA 1/8", Aluminum Band, Chloroprene Cushion | EA |
| MS21919WDG20 | Clamp, To Fit DIA 1-1/4", Aluminum Band, Chloroprene Cushion | EA |
| MS21919WDG21 | Clamp, To Fit DIA 1-5/16", Aluminum Band, Chloroprene Cushion | EA |
| MS21919WDG22 | Clamp, To Fit DIA 1-3/8", Aluminum Band, Chloroprene Cushion | EA |
| MS21919WDG23 | Clamp, To Fit DIA 1-7/16", Aluminum Band, Chloroprene Cushion | EA |
| MS21919WDG24 | Clamp-1.500 OD, ALU | EA |
| MS21919WDG24 | Clamp-1.500 OD, ALU | EA |
| MS21919WDG26 | Clamp, To Fit DIA 1-5/8", Aluminum Band, Chloroprene Cushion | EA |
| MS21919WDG28 | Clamp, to fit 1-3/4" Dia. | EA |
| MS21919WDG3 | Clamp, To Fit DIA 3/16", Aluminum Band, Chloroprene Cushion | EA |
| MS21919WDG32 | Clamp, To Fit DIA 2", Aluminum Band, Chloroprene Cushion | EA |
| MS21919WDG34 | Clamp, To Fit DIA 2-1/8", Aluminum Band, Chloroprene Cushion | EA |
| MS21919WDG36 | Clamp, To Fit DIA 2- 1/4", Aluminum Band, Chloroprene Cushion | EA |
| MS21919WDG4 | Clamp, To Fit DIA 1/4", Aluminum Band, Chloroprene Cushion | EA |
| MS21919WDG48 | Clamp, To Fit DIA 3", Aluminum Band, Chloroprene Cushion | EA |
| MS21919WDG5 | Clamp, To Fit DIA 5/16", Aluminum Band, Chloroprene Cushion | EA |
| MS21919WDG5 | Clamp, To Fit DIA 5/16", Aluminum Band, Chloroprene Cushion | EA |
| MS21919WDG6 | Clamp, To Fit DIA 3/8", Aluminum Band, Chloroprene Cushion | EA |
| MS21919WDG7 | Clamp, To Fit DIA 7/16", Aluminum Band, Chloroprene Cushion | EA |
| MS21919WDG8 | Clamp | EA |
| MS21919WDG9 | Clamp, To Fit DIA 9/16", Aluminum Band, Chloroprene Cushion | EA |
| MS21919WDG9 | Clamp, To Fit DIA 9/16", Aluminum Band, Chloroprene Cushion | EA |
| MS21919WH3 | Clamp, Cushion, High Temperature, 3/16" | EA |
| MS24587-6 | Hose Fitting, Adapter, Straight, 3/4" to 1/2" | EA |

| Part Number | Part Description | Unit of Measure |
|--------------|---|-----------------|
| MS24665-1012 | Pin, Cotter, 1/16" DIA, 3/8" Length, Corrosion Resistant Steel | EA |
| MS24665-132 | Pin, Cotter, 1/16" DIA, 1/2" Length, Cadmium Plated | EA |
| MS24665-134 | Pin, Cotter, 1/16" DIA, 3/4" Length, Carbon Steel | EA |
| MS24665-136 | Pin, Cotter, 1/16 X 1" CAD STEEL, AN380-2-4 CAD II Cotter | EA |
| MS24665-136 | Pin, Cotter, 1/16 X 1" CAD STEEL, AN380-2-4 CAD II Cotter | EA |
| MS24665-140 | Pin, Cotter, 1/16" DIA, 1-1/2" Length, Carbon Steel | EA |
| MS24665-143 | Pin, Cotter, 1/16" DIA, 2" Length, Carbon Steel | EA |
| MS24665-149 | Pin, Cotter | EA |
| MS24665-151 | Pin, Cotter, 1/16" DIA, 1/2" Length, Corrosion Resistant Steel | EA |
| MS24665-155 | Pin, Cotter, 1/16" DIA, 1" Length, Corrosion Resistant Steel | EA |
| MS24665-157 | Pin, Cotter, 1/16" DIA, 1-1/4" Length, Corrosion Resistant Steel | EA |
| MS24665-159 | Pin, Cotter, 1/16" DIA, 1-1/2" Length, Corrosion Resistant Steel | EA |
| MS24665-229 | Pin, Cotter, 5/64" DIA, 3/4" Length, Corrosion Resistant Steel, -Will Work For Most AN831-25-10 | EA |
| MS24665-281 | Pin, Cotter, 3/32" DIA, 1/2" Length, Carbon Steel | EA |
| MS24665-283 | Pin, Cotter, 3/32" DIA, 3/4" Length, Carbon Steel | EA |
| MS24665-285 | Pin, Cotter, 3/32" DIA, 1" Length, Carbon Steel | EA |
| MS24665-287 | Pin, Cotter, 3/32" DIA, 1-1/4" Length, Carbon Steel | EA |
| MS24665-289 | Pin, Cotter, 3/32" DIA, 1-1/2" Length, Carbon Steel | EA |
| MS24665-292 | Pin, Cotter, 3/32" DIA, 2" Length, Carbon Steel | EA |
| MS24665-294 | Pin, Cotter, 3/32" DIA, 2-1/2" Length, Carbon Steel | EA |
| MS24665-294 | Pin, Cotter, 3/32" DIA, 2-1/2" Length, Carbon Steel | EA |
| MS24665-295 | Pin, Cotter, 3/32" DIA, 3" Length, Carbon Steel | EA |
| MS24665-298 | Pin, Cotter, 3/32" DIA, 1/2" Length, Corrosion Resistant Steel | EA |
| MS24665-300 | Pin, Cotter, 3/32" DIA, 3/4" Length, Corrosion Resistant Steel | EA |
| MS24665-302 | Pin, Cotter, 1/32" DIA, 1" Length, Carbon Steel | EA |
| MS24665-304 | Pin, Cotter, 3/32" DIA, 1-1/4" Length, Corrosion Resistant Steel | EA |
| MS24665-306 | Pin, Cotter, 3/32" DIA, 1-1/2" Length, Corrosion Resistant Steel | EA |
| MS24665-309 | Pin, Cotter, 3/32" DIA, 2" Length, Corrosion Resistant Steel | EA |
| MS24665-349 | Pin, Cotter, 1/8" DIA, 1/2" Length, Carbon Steel | EA |
| MS24665-351 | Pin, Cotter, 1/8" DIA, 3/4" Length, Carbon Steel | EA |
| MS24665-353 | Pin, Cotter, 1/8" DIA, 1" Length, Carbon Steel | EA |
| MS24665-357 | Pin, Cotter, 1/8" DIA, 1-1/2" Length, Carbon Steel | EA |
| MS24665-359 | Pin, Cotter, 3/32" DIA, 1" Length, Corrosion Resistant Steel | EA |
| MS24665-360 | Pin, Cotter, 1/8" DIA, 2" Length, Carbon Steel | EA |
| MS24665-368 | Pin, Cotter, 1/8" DIA, 3/4" Length, Corrosion Resistant Steel | EA |
| MS24665-370 | Pin, Cotter, 1/8" DIA, 1" Length, Corrosion Resistant Steel | EA |
| MS24665-376 | Pin, Cotter, 5/32" DIA, 1" Length, Stainless Steel | EA |
| MS24665-377 | Pin, Cotter, 1/8" DIA, 2" Length, Corrosion Resistant Steel | EA |
| MS24665-379 | Pin, Cotter, 1/8" DIA, 2-1/2" Length, Corrosion Resistant Steel | EA |
| MS24665-419 | Pin, Cotter, 5/32" DIA, 1" Length, Cadmium Plated | EA |
| MS24665-435 | Pin, Cotter | EA |
| MS24665-436 | Pin, Cotter | EA |
| MS24665-437 | Pin, Cotter | EA |
| MS24665-5 | Pin, Cotter, 1/32" DIA, 1/2" Length, Carbon Steel | EA |
| MS24665-9 | Pin, Cotter, 1/32" DIA, 1" Length, Carbon Steel | EA |
| MS24667-40 | Bolt, CSK | EA |
| MS24693BB29 | Screw, Machine Flat Head (100 Deg), Crossed-Recessed, Black Brass | EA |
| MS24693BB32 | Screw, Instrument Brass Flat Head | EA |
| MS24693BB50 | Screw, Flat Head, Black Brass Instrument, 8-32 Thread, 1/2" Length | EA |
| MS24693BB52 | Screw, Flat Head, Black Brass Instrument, 8-32 Thread, 3/4" Length | EA |
| MS24693BB53 | Screw, Flat Head, Black Brass Instrument, 8-32 Thread, 7/8" Length | EA |
| MS24693BB54 | Screw, Flat Head, Black Brass Instrument, 8-32 Thread, 1" Length | EA |

| Part Number | Part Description | Unit of Measure |
|-------------|---|-----------------|
| MS24693BB56 | Screw, Flat Head, Black Brass Instrument, 8-32 Thread, 1-1/4" Length | EA |
| MS24693C26 | Screw, Machine Flat Head (100 Deg), Corrosion Resistant, 6-32, 3/8" | EA |
| MS24693C270 | Screw, Machine, Flat Head (100 Deg), Corrosion Resistant, 10-32 Thread, 3/8" Length | EA |
| MS24693C271 | Screw, Machine, Flat Head (100 Deg), Corrosion Resistant, 10-32 Thread, 7/16" Length | EA |
| MS24693C272 | Screw, Machine, Flat Head (100 Deg), Corrosion Resistant, 10-32 Thread, 1/2" Length | EA |
| MS24693C273 | Screw, Machine, Flat Head (100 Deg), Corrosion Resistant, 10-32 Thread, 5/8" Length | EA |
| MS24693C274 | Screw, Machine, Flat Head (100 Deg), Corrosion Resistant, 10-32 Thread, 3/4" Length | EA |
| MS24693C275 | Screw, Machine, Flat Head (100 Deg), Corrosion Resistant, 10-32 Thread, 7/8" Length | EA |
| MS24693C276 | Screw, Machine, Flat Head (100 Deg), Corrosion Resistant, 10-32 Thread, 1" Length | EA |
| MS24693C278 | Screw, Machine, Flat Head (100 Deg), Corrosion Resistant, 10-32 Thread, 1-1/4" Length | EA |
| MS24693C29 | Screw, Machine, Flat Head (100 Deg), Corrosion Resistant, 6-32 Thread, 5/8" Length | EA |
| MS24693C30 | Screw, Machine Flat Head (100 Deg), Corrosion Resistant, 6-32, 3/4" | EA |
| MS24693C31 | Screw, Machine, Flat Head (100 Deg), Corrosion Resistant, 6-32 Thread, 7/8" Length | EA |
| MS24693C4 | Screw, Machine Flat Head (100 Deg), Corrosion Resistant, 4-40, 3/8" | EA |
| MS24693C48 | Screw, Machine, Flat Head (100 Deg), Corrosion Resistant, 8-32 Thread, 3/8" Length | EA |
| MS24693C50 | Screw, Machine, Flat Head (100 Deg), Corrosion Resistant, 8-32 Thread, 1/2" Length | EA |
| MS24693C51 | Screw, Machine Flat Head (100 Deg), Corrosion Resistant, 8-32, 5/8" | EA |
| MS24693C52 | Screw, Machine, Flat Head (100 Deg), Corrosion Resistant, 8-32 Thread, 3/4" Length | EA |
| MS24693C53 | Screw, Machine, Flat Head (100 Deg), Corrosion Resistant, 8-32 Thread, 7/8" Length | EA |
| MS24693C54 | Screw, Machine, Flat Head (100 Deg), Corrosion Resistant, 8-32 Thread, 1" Length | EA |
| MS24693C6 | Screw, Machine, Flat Head (100 Deg), Corrosion Resistant, 4-40 Thread, 1/2" Length | EA |
| MS24693S10 | Screw, Machine, Flat Head (100 Deg), Carbon Steel, 4-40 Thread, 1" Length | EA |
| MS24693S224 | Screw, Machine, Flat Head (100 Deg), Carbon Steel, 6-32 Thread, 3/8" Length | EA |
| MS24693S25 | Screw, Machine, Flat Head (100 Deg), Carbon Steel, 6-32 Thread, 3/8" Length | EA |
| MS24693S26 | Screw, Machine Flat Head (100 Deg), Carbon Steel, 6-32, 3/8" | EA |
| MS24693S270 | Screw, Machine, Flat Head (100 Deg), Carbon Steel, 10-32 Thread, 3/8" Length | EA |
| MS24693S271 | Screw, Machine, Flat Head (100 Deg), Carbon Steel, 10-32 Thread, 7/16" Length | EA |
| MS24693S273 | Screw, Machine, Flat Head (100 Deg), Carbon Steel, 10-32 Thread, 5/8" Length | EA |
| MS24693S274 | Screw, Machine, Flat Head (100 Deg), Carbon Steel, 10-32 Thread, 3/4" Length | EA |
| MS24693S275 | Screw, Machine, Flat Head (100 Deg), Carbon Steel, 10-32 Thread, 7/32" Length | EA |

| Part Number | Part Description | Unit of Measure |
|-------------|---|-----------------|
| MS24693S276 | Screw, Machine, Flat Head (100 Deg), Carbon Steel, 10-32 Thread, 1" Length | EA |
| MS24693S278 | Screw, Machine, Flat Head (100 Deg), Carbon Steel, 10-32 Thread, 11/8" Length | EA |
| MS24693S28 | Screw, Machine, Flat Head (100 Deg), Carbon Steel, 6-32 Thread, 1/2" Length | EA |
| MS24693S29 | Screw, Machine, Flat Head (100 Deg), Carbon Steel, 6-32 Thread, 5/8" Length | EA |
| MS24693S30 | Screw, Machine, Flat Head (100 Deg), Carbon Steel, 6-32 Thread, 3/4" Length | EA |
| MS24693S31 | Screw, Machine, Flat Head (100 Deg), Carbon Steel, 6-32 Thread, 7/8" Length | EA |
| MS24693S48 | Screw, Machine, Flat Head (100 Deg), Carbon Steel, 8-32 Thread, 3/8" Length | EA |
| MS24693S49 | Screw, Machine, Flat Head (100 Deg), Carbon Steel, 8-32 Thread, 7/16" Length | EA |
| MS24693S51 | Screw, Machine, Flat Head (100 Deg), Carbon Steel, 8-32 Thread, 5/8" Length | EA |
| MS24693S52 | Screw, Machine Flat Head (100 Deg), Carbon Steel, 8-32, 3/4" | EA |
| MS24693S53 | Screw, Machine Flat Head (100 Deg), Carbon Steel, 8-32, 7/8" | EA |
| MS24693S54 | Screw, Machine, Flat Head (100 Deg), Carbon Steel, 8-32 Thread, 1" Length | EA |
| MS24693S6 | Screw, Machine, Flat Head (100 Deg), Carbon Steel, 4-40 Thread, 3/8" Length | EA |
| MS24694S100 | Screw, Flat Head (100 Deg), Structural Machine, Carbon Steel, 1/4-28 Thread, 27/32" Length, 5/16" Grip | EA |
| MS24694S101 | Screw, 100 Deg, Flat Head, Structural Machine Screw, 1/4-28 Thread, 3/8" Grip | EA |
| MS24694S102 | Screw, Flat Head (100 Deg), Structural Machine, Carbon Steel, 1/4-28 Thread, 31/32" Length, 7/16" Grip | EA |
| MS24694S103 | Screw, Flat Head (100 Deg), Structural Machine, Carbon Steel, 1/4-28 Thread, 1-1/32" Length, 1/2" Grip | EA |
| MS24694S107 | Screw, Machine Flat Head, Structural, 100 Deg, 1/4-28 DIA, 3/4" Grip | EA |
| MS24694S11 | Screw, Flat Head (100 Deg), Structural Machine, Carbon Steel, 8-32 Thread, 29/32" Length, 15/32" Grip | EA |
| MS24694S111 | Screw, Flat Head (100 Deg), Structural Machine, Carbon Steel, 1/4-28 Thread, 1-17/32" Length, 1" Grip | EA |
| MS24694S135 | Screw, Flat Head (100 Deg), Structural Machine, Carbon Steel | EA |
| MS24694S17 | Screw, Flat Head (100 Deg), Structural Machine, Carbon Steel, 8-32 Thread, 1-9/32" Length, 27/32" Grip | EA |
| MS24694S2 | Screw, Flat Head (100 Deg), Structural Machine, Carbon Steel, 8-32 Thread, 11/32" Length, 3/32" Grip | EA |
| MS24694S27 | Screw, Flat Head (100 Deg), Structural Machine, Carbon Steel, 8-32 Thread, 1-7/8" Overall Length, 1.469" Grip | EA |
| MS24694S4 | Screw, Flat Head (100 Deg), Structural Machine, Carbon Steel, 8-32 Thread, 15/32" Length, 3/32" Grip | EA |
| MS24694S4 | Screw, Flat Head (100 Deg), Structural Machine, Carbon Steel, 8-32 Thread, 15/32" Length, 3/32" Grip | EA |
| MS24694S47 | Screw, Flat Head (100 Deg), Structural Machine, Carbon Steel, 10-32 Thread, 11/32" Length, 7/64" Grip | EA |
| MS24694S48 | Screw, Flat Head (100 Deg), Structural Machine, Carbon Steel, 10-32 Thread, 13/32" Length, 7/64" Grip | EA |
| MS24694S49 | Screw, Flat Head (100 Deg), Structural Machine, Carbon Steel, 10-32 Thread, 15/32" Length, 7/64" Grip | EA |

| Part Number | Part Description | Unit of Measure |
|--------------|--|-----------------|
| MS24694S5 | Screw, Flat Head (100 Deg), Structural Machine, Carbon Steel, 8-32 Thread, 11/32" Length, 3/32" Grip | EA |
| MS24694S50 | Screw, Flat Head (100 Deg), Structural Machine, Carbon Steel, 10-32 Thread, 17/32" Length, 7/64" Grip | EA |
| MS24694S51 | Screw, Flat Head (100 Deg), Structural Machine, Carbon Steel, 10-32 Thread, 19/32" Length, 7/64" Grip | EA |
| MS24694S52 | Screw, Flat Head (100 Deg), Structural Machine, Carbon Steel, 10-32 Thread, 21/32" Length, 3/16" Grip | EA |
| MS24694S53 | Screw, Flat Head (100 Deg), Structural Machine, Carbon Steel, 10-32 Thread, 23/32" Length, 1/4" Grip | EA |
| MS24694S54 | Screw, Flat Head (100 Deg), Structural Machine, Carbon Steel, 10-32 Thread, 25/32" Length, 5/16" Grip | EA |
| MS24694S55 | Screw, Flat Head (100 Deg), Structural Machine, Carbon Steel, 10-32 Thread, 27/32" Length, 3/8" Grip | EA |
| MS24694S56 | Screw, Flat Head (100 Deg), Structural Machine, Carbon Steel, 10-32 Thread, 29/32" Length, 7/16" Grip | EA |
| MS24694S57 | Screw, Flat Head (100 Deg), Structural Machine, Carbon Steel, 1/4-28 Thread, 25/32" Length, 1/4" Grip | EA |
| MS24694S58 | Screw, Flat Head (100 Deg), Structural Machine, Carbon Steel, 1/4-28 Thread, 25/32" Length, 1/4" Grip | EA |
| MS24694S60 | Screw, Flat Head (100 Deg), Structural Machine, Carbon Steel, 1/4-28 Thread, 25/32" Length, 1/4" Grip | EA |
| MS24694S62 | Screw-Mach Flt Hd Struc,10-32X1.250,100Deg | EA |
| MS24694S64 | Screw, Flat Head (100 Deg), Structural Machine, Carbon Steel, 1/4-28 Thread, 25/32" Length, 1/4" Grip | EA |
| MS24694S65 | Screw, Flat Head (100 Deg), Structural Machine, Carbon Steel, 1/4-28 Thread, 25/32" Length, 1/4" Grip | EA |
| MS24694S7 | Screw, Flat Head (100 Deg), Structural Machine, Carbon Steel, 8-32 Thread, 21/32" Length, 7/32" Grip | EA |
| ms24694s8 | Screw, Flat Head (100 Deg), Structural Machine, Carbon Steel, 8-32 Thread, 23/32" Length, 9/32" Grip | EA |
| MS24694S9 | Screw, Flat Head (100 Deg), Structural Machine, Carbon Steel, 8-32 Thread, 25/32" Length, 11/32" Grip | EA |
| MS24694S95 | Screw, Flat Head (100 Deg), Structural Machine, Carbon Steel, 1/4-28 Thread, 17/32" Length, 9/64" Grip | EA |
| MS24694S99 | Screw, Flat Head (100 Deg), Structural Machine, Carbon Steel, 1/4-28 Thread, 25/32" Length, 1/4" Grip | EA |
| MS25082B2 | Nut, Hexagon, Thin Electrical, 0.1640-32 Thread | EA |
| MS27039-0806 | Screw, Structural Machine, Pan Head, 8-32 Thread, 0.406" Length | EA |
| MS27039-0807 | Screw, Structural Machine, Pan Head, 8-32 Thread, 0.469" Length | EA |
| MS27039-0809 | Screw, Structural Machine, Pan Head, 8-32 Thread, 0.594" Length , 0.156" Grip | EA |
| MS27039-0811 | Screw, Structural Machine, Pan Head, 8-32 Thread, 0.719" Length , 0.281" Grip | EA |
| MS27039-0813 | Screw, Structural Machine, Pan Head, 8-32 Thread, 0.844" Length , 0.406" Grip | EA |
| MS27039-0814 | Screw, Machine, Crossed-Recessed, 8-32, 0.906" | EA |
| MS27039-0816 | Screw, Structural Machine, Pan Head, 8-32 Thread, 1.031" Length , 0.594" Grip | EA |
| MS27039-0818 | Screw, Structural Machine, Pan Head, 8-32 Thread, 1.156" Length , 0.719" Grip | EA |
| MS27039-0820 | Screw, Structural Machine, Pan Head, 8-32 Thread, 1.281" Length , 0.844" Grip | EA |

| Part Number | Part Description | Unit of Measure |
|--------------|--|-----------------|
| MS27039-0822 | Screw, Structural Machine, Pan Head, 8-32 Thread, 1.406" Length , 0.969" Grip | EA |
| MS27039-0823 | Screw, Structural Machine, Pan Head | EA |
| MS27039-1-06 | Screw, Structural Machine, Pan Head, 10-32 Thread, 0.406" Length | EA |
| MS27039-1-10 | Screw, Structural Machine, Pan Head, 10-32 Thread, 0.656" Length, 0.188" Grip | EA |
| MS27039-1-14 | Screw, Structural Machine, Pan Head, 10-32 Thread, 0.906" Length, 0.438" Grip | EA |
| MS27039-1-15 | Screw, Structural Machine, Pan Head, 10-32 Thread, 0.969" Length, 1/2" Grip | EA |
| MS27039-4-10 | Screw, Structural Machine, Pan Head, 1/4-28 Thread, 0.656" Length, 0.125" Grip | EA |
| MS27039-4-19 | Screw, Structural Machine, Pan Head | EA |
| MS27039-4-28 | Screw, Machine Pan Head Structural, 1/4-28 Thread | EA |
| MS27039C0808 | Screw, Pan Head, 8-32 X .500 Lg, SS | EA |
| MS27039C0813 | Screw, Machine, Corrosion Resistant, 8-32, 0.844" | EA |
| MS27130A13 | Rivnut, Countersunk Head, internal Thread, Unkeyed, 8-32 Thread, 0.01-0.08" Grip | EA |
| MS27130A13K | Rivnut, Countersunk Head, Internal Thread, Keyed, 8-32 Thread, 0.01-0.075" Grip | EA |
| MS27130A14 | Rivnut, Countersunk Head, internal Thread, Unkeyed, 8-32 Thread, 0.075-0.12" Grip | EA |
| MS27130A25 | Rivnut, Countersunk Head, internal Thread, Unkeyed, 10-32 Thread, 0.01-0.08" Grip | EA |
| MS27130A25K | Rivnut, Countersunk Head, Internal Thread, Keyed, 10-32 Thread, 0.01-0.08" Grip | EA |
| MS27130A7 | Rivnut, Countersunk Head, internal Thread, Unkeyed, 6-32 Thread, 0.01-0.075" Grip | EA |
| MS27130A7K | Rivnut, Countersunk Head, internal Thread, Keyed, 6-32 Thread, 0.01-0.075" Grip | EA |
| MS27130A87 | Rivnut, Countersunk Head, internal Thread, Unkeyed, 6-32 Thread, 0.065-0.106" Grip | EA |
| MS27405-10P | Clamp | EA |
| MS27405-11P | Clamp | EA |
| MS27405-18P | Clamp | EA |
| MS27405-5 | Clamp | EA |
| MS27405-8P | Clamp | EA |
| MS27405-9P | Clamp | EA |
| MS27641-4 | Bearing, Airframe, Antifriction Intermediate Duty, 1/4" Bore, can also use KP4A | EA |
| MS27645-4 | Bearing, Airframe, Antifriction, Self-Aligning, 1/4" Bore | EA |
| MS27769-2 | Plug, Hex, NPT Size 1/8, Steel | EA |
| MS27769-3 | Plug, Hex, NPT Size 1/4, Steel | EA |
| MS27769D1 | Plug, Hex, NPT Size 1/16, Aluminum | EA |
| MS27769D2 | Plug, Hex, NPT Size 1/8, Aluminum | EA |
| MS27769D3 | Plug, Hex, NPT Size 1/4, Aluminum | EA |
| MS27769D5 | Plug, Hex, NPT Size 1/2, Aluminum | EA |
| MS27975-1 | Rod End, Clevis, Wide Fork, 1/4" DIA, Ultimate Axial Load 3800 lbs. | EA |
| MS28042-1A | Clamp | EA |
| MS28773-05 | Back Up Ring, 5/16" Nom. Tube Outside DIA | EA |
| MS28774-129 | Back Up Retainer, O Ring, Thickness 0.045-0.052" | EA |
| MS28774-222 | O Ring, 1' DIA, White Plastic | EA |
| MS28775-003 | O Ring, DIA 0.0625 | EA |

| Part Number | Part Description | Unit of Measure |
|-------------|------------------------------|-----------------|
| MS28775-004 | O Ring, DIA 0.07 | EA |
| MS28775-006 | O Ring, DIA 0.113 | EA |
| MS28775-006 | O Ring, DIA 0.113 | EA |
| MS28775-007 | O Ring, DIA 0.145, AN6227-2 | EA |
| MS28775-008 | O Ring, DIA 0.176 | EA |
| MS28775-008 | O Ring, DIA 0.176 | EA |
| MS28775-008 | O Ring, DIA 0.176 | EA |
| MS28775-009 | O Ring, DIA .0208 | EA |
| MS28775-010 | O Ring, DIA 0.239 | EA |
| MS28775-010 | O Ring, DIA 0.239 | EA |
| MS28775-013 | O Ring, DIA 0.426 | EA |
| MS28775-013 | O Ring, DIA 0.426 | EA |
| MS28775-015 | O Ring, DIA 0.551 | EA |
| MS28775-016 | O Ring, DIA 0.614 | EA |
| MS28775-017 | O Ring, DIA 0.676 | EA |
| MS28775-017 | O Ring, DIA 0.676 | EA |
| MS28775-018 | O Ring, DIA 0.739 | EA |
| MS28775-019 | O Ring, DIA 0.801 | EA |
| MS28775-022 | O Ring, DIA 0.989 | EA |
| MS28775-111 | O Ring, DIA 0.424, AN6227-9 | EA |
| MS28775-114 | O Ring, 0.612, AN6227-12 | EA |
| MS28775-115 | O Ring, DIA 0.674 | EA |
| MS28775-115 | O Ring, DIA 0.674 | EA |
| MS28775-116 | O Ring, DIA 0.737, AN6227-14 | EA |
| MS28775-117 | O Ring, DIA 0.799 | EA |
| MS28775-117 | O Ring, DIA 0.799 | EA |
| MS28775-119 | O Ring, DIA 0.924 | EA |
| MS28775-129 | O Ring, DIA 1.549 | EA |
| MS28775-135 | O Ring, DIA 1.925 | EA |
| MS28775-210 | O Ring, DIA 0.734, AN6227-15 | EA |
| MS28775-211 | O Ring, DIA 0.796 | EA |
| MS28775-212 | O Ring, DIA 0.859 | EA |
| MS28775-212 | O Ring, DIA 0.859 | EA |
| MS28775-212 | O Ring, DIA 0.859 | EA |
| MS28775-214 | O Ring, DIA 0.984 | EA |
| MS28775-214 | O Ring, DIA 0.984 | EA |
| MS28775-215 | O Ring, DIA 1.046 | EA |
| MS28775-215 | O Ring, DIA 1.046 | EA |
| MS28775-216 | O Ring, DIA 1.109, AN6227-21 | EA |
| MS28775-217 | O Ring, DIA 1.171 | EA |
| MS28775-218 | O Ring, DIA 1.234, AN6227-23 | EA |
| MS28775-219 | O Ring, DIA 1.296, AN6227-24 | EA |
| MS28775-219 | O Ring, DIA 1.296, AN6227-24 | EA |
| MS28775-220 | O Ring, DIA 1.359, AN6227-25 | EA |
| MS28775-221 | O Ring, DIA 1.421 | EA |
| MS28775-221 | O Ring, DIA 1.421 | EA |
| MS28775-222 | O Ring, DIA 1.484, AN6227-27 | EA |
| MS28775-222 | O Ring, DIA 1.484, AN6227-27 | EA |
| MS28775-225 | O Ring, DIA 1.85, AN6230-3 | EA |
| MS28775-226 | O Ring, DIA 1.98 | EA |
| MS28775-227 | O Ring, DIA 2.11 | EA |
| MS28775-228 | O Ring, DIA 2.334 | EA |
| MS28775-228 | O Ring, DIA 2.334 | EA |

| Part Number | Part Description | Unit of Measure |
|-------------|--|-----------------|
| MS28775-229 | O Ring, DIA 2.359 | EA |
| MS28775-229 | O Ring, DIA 2.359 | EA |
| MS28775-231 | O Ring, DIA 2.609, AN6230-9 | EA |
| MS28775-232 | O Ring, DIA 2.734 | EA |
| MS28775-233 | O Ring, DIA 2.859 | EA |
| MS28775-234 | O Ring , DIA 2.984, AN6230-12 | EA |
| MS28775-235 | O Ring, DIA 3.109, AN6227-38 | EA |
| MS28775-237 | Oring Do not buy | EA |
| MS28775-314 | O Ring | EA |
| MS28775-316 | O Ring, DIA 0.875 | EA |
| MS28775-316 | O Ring, DIA 0.875 | EA |
| MS28775-325 | O Ring, DIA 1.425 | EA |
| MS28775-325 | O Ring, DIA 1.425 | EA |
| MS28775-326 | O Ring, DIA 1.6, AN6227-25 | EA |
| MS28775-327 | O Ring, DIA 1.725 | EA |
| MS28775-327 | O Ring, DIA 1.725 | EA |
| MS28775-328 | O Ring, DIA 1.85 | EA |
| MS28775-329 | O Ring, DIA 1.975 | EA |
| MS28775-330 | O Ring, DIA 2.1 | EA |
| MS28775-330 | O Ring, DIA 2.1 | EA |
| MS28775-333 | O Ring, DIA 2.475 | EA |
| MS28775-334 | O Ring, DIA 2.6, AN6227-37 | EA |
| MS28775-336 | O Ring, DIA 2.855, AN6227-39 | EA |
| MS28775-337 | O Ring, DIA 2.975 | EA |
| MS28775-337 | O Ring, DIA 2.975 | EA |
| MS28775-340 | O Ring, DIA 3.35 | EA |
| MS28775-340 | O Ring, DIA 3.35 | EA |
| MS28776-17 | Scraper, 1-1/2" DIA | EA |
| MS28776M2-5 | Scraper, Piston Rod, 3/4" Rod DIA, 1" Scrapper DIA | EA |
| MS28778-10 | O Ring, Packing, 0.097" Thickness, 5/8" Outside DIA | EA |
| MS28778-12 | O Ring, Packing, 0.116" Thickness, 3/4" Outside DIA | EA |
| MS28778-2 | O Ring, Packing, 0.064" Thickness, 1/8" Outside DIA | EA |
| MS28778-5 | O Ring, Packing, 0.072" Thickness, 5/16" Outside DIA | EA |
| MS28778-8 | O Ring, Packing, 0.087" Thickness, 1/2" Outside DIA | EA |
| MS28778-8 | O Ring, Packing, 0.087" Thickness, 1/2" Outside DIA | EA |
| MS28782-12 | Back-Up Ring | EA |
| MS28782-12 | Back-Up Ring | EA |
| MS28782-22 | Ring | EA |
| MS28782-27 | Back-Up Ring | EA |
| MS28889-2 | Air Valve, High Pressure Charging, 5000 PSI | EA |
| MS29512-04 | O Ring, Packing, 0.072" Thickness, 1/4" Outside DIA | EA |
| MS29512-05 | O Ring, Packing, 0.072" Thickness, 5/16" Outside DIA | EA |
| MS29512-06 | O Ring, Packing, 0.078" Thickness, 3/8" Outside DIA | EA |
| MS29512-08 | O Ring, Packing, 0.087" Thickness, 1/2" Outside DIA | EA |
| MS29512-10 | O-Ring | EA |
| MS29512-12 | O Ring, Packing, 0.116" Thickness, 3/4" Outside DIA | EA |
| MS29513-006 | O Ring, 0.114" DIA, 0.07" Thickness | EA |
| MS29513-008 | O Ring, 0.176" DIA, 0.07" Thickness | EA |
| MS29513-010 | O Ring, 0.239" DIA, 0.07" Thickness | EA |
| MS29513-011 | O Ring, 0.301" DIA, 0.07" Thickness | EA |
| MS29513-011 | O Ring, 0.301" DIA, 0.07" Thickness | EA |
| MS29513-012 | O Ring, 0.364" DIA, 0.07" Thickness | EA |
| MS29513-013 | O Ring, 0.426" DIA, 0.07" Thickness | EA |

| Part Number | Part Description | Unit of Measure |
|-------------|--|-----------------|
| MS29513-014 | O Ring, 0.551" DIA, 0.07" Thickness | EA |
| MS29513-015 | O Ring, 0.551" DIA, 0.07" Thickness | EA |
| MS29513-016 | O Ring | EA |
| MS29513-021 | O Ring, 0.926" DIA, 0.07" Thickness | EA |
| MS29513-022 | O Ring, 0.986" DIA, 0.07" Thickness | EA |
| MS29513-024 | O Ring, 1.114" DIA, 0.07" Thickness | EA |
| MS29513-025 | O Ring, 1.176" DIA, 0.07" Thickness | EA |
| MS29513-111 | O Ring, 0.424" DIA, 0.103" Thickness | EA |
| MS29513-112 | O Ring, 0.487" DIA, 0.103" Thickness | EA |
| MS29513-114 | O Ring, 0.612" DIA, 0.103" Thickness | EA |
| MS29513-116 | O Ring | EA |
| MS29513-136 | O Ring, 1.987" DIA, 0.103" Thickness | EA |
| MS29513-137 | O Ring, 2.050" DIA, 0.103" Thickness | EA |
| MS29513-138 | O Ring, 2.112" DIA, 0.103" Thickness | EA |
| MS29513-211 | O Ring, 0.8" DIA, 0.139" Thickness | EA |
| MS29513-212 | O Ring, 0.859" DIA, 0.139" Thickness | EA |
| MS29513-214 | O Ring, 0.984" DIA, 0.139" Thickness | EA |
| MS29513-337 | O Ring, 3" DIA, 0.21" Thickness | EA |
| MS29513-338 | O Ring, 3.1" DIA, 0.21" Thickness | EA |
| MS29561-011 | O Ring, 0.301" DIA, 0.07" Thickness | EA |
| MS29561-012 | O Ring, 0.364" DIA, 0.07" Thickness | EA |
| MS29561-013 | O Ring, 0.426" DIA, 0.07" Thickness | EA |
| MS29561-022 | O Ring, 0.989" DIA, 0.07" Thickness | EA |
| MS29561-226 | O Ring, 2" DIA, 0.139" Thick | EA |
| MS33737-10C | Nut, Instrument Mounting, Panel Range 0.093 | EA |
| MS33737-11C | Nut, 1/8", 6-32, Instrument, Mounting Clip | EA |
| MS33737-12C | Nut, 0.187", 6/32, Instrument, Mounting Clip | EA |
| MS33737-13C | Nut, 1/4", 6-32, Instrument, Mounting Clip | EA |
| MS33737-14C | Nut, 0.312", 6/32, Instrument, Mounting Clip | EA |
| MS33737-16C | Nut, 3/8"+ Mounting Clip, Instrument | EA |
| MS33737-1C | Nut, Instrument Mounting | EA |
| MS3417-14C | Clamp, (2 used on one Float Installation) | EA |
| MS3420-4 | Bushing, 1/4" DIA, Black Rubber, (1 used on one Float Installation) | EA |
| MS35190-223 | Screw, Machine, 82 Flat Head, Carbon Steel, 4-40 Thread, 0.375" Length | EA |
| MS35199-16 | Screw, Machine Flat | EA |
| MS35206-208 | Screw, Machine, Pan Head, 2-56 Thread, 5/8" Length | EA |
| MS35206-212 | Screw, Pan head | EA |
| MS35206-213 | SCREW, PAN HEAD, STL. CAD 2, 4-40, 1/4" | EA |
| MS35206-214 | Screw, Machine, Pan Head, 4-40 Thread, 5/16" Length | EA |
| MS35206-215 | SCREW, PAN HEAD, STL. CAD 2, 4-40, 3/8" | EA |
| MS35206-219 | Screw, Machine, Pan Head, 4-40 Thread, 3/4" Length | EA |
| MS35206-226 | Screw, Machine, Pan Head, 6-32 Thread, 1/4" Length | EA |
| MS35206-227 | Screw, Machine, Pan Head, 6-32 Thread, 5/16" Length | EA |
| MS35206-228 | SCREW, PAN HEAD, STL. CAD 2, 6-32, 3/8" | EA |
| MS35206-230 | SCREW, PAN HEAD, STL. CAD 2, 6-32, 1/2" | EA |
| MS35206-231 | Screw, Machine, Pan Head, 6-32 Thread, 5/8" Length | EA |
| MS35206-232 | Screw, Machine, Pan Head, 6-32 Thread, 3/4" Length | EA |
| MS35206-233 | Screw, Machine, Pan Head, 6-32 Thread, 7/8" Length | EA |
| MS35206-238 | Screw, Machine, Pan Head, 6-32 Thread, 2" Length | EA |
| MS35206-240 | Screw, Machine, Pan Head, 8-32 Thread, 3/16" Length | EA |
| MS35206-243 | Screw, Machine, Pan Head, 8-32 Thread, 3/8" Length | EA |
| MS35206-244 | Screw, Machine, Pan Head, 8-32 Thread, 7/16" Length | EA |
| MS35206-246 | Screw, Machine, Pan Head, 8-32 Thread, 5/8" Length | EA |

| Part Number | Part Description | Unit of Measure |
|-------------|--|-----------------|
| MS35206-247 | SCREW, PAN HEAD, STL. CAD 2, 8-32, 3/4" | EA |
| MS35206-251 | Screw, Machine, Pan Head, 8-32 Thread, 1-1/2" Length | EA |
| MS35206-253 | Screw, Machine, Pan Head, 8-32 Thread, 2" Length | EA |
| MS35206-263 | Screw, Machine, Pan Head, 10-24 Thread, 1/2" Length | EA |
| MS35206-265 | Screw, Machine, Pan Head, 10-24 Thread, 3/4" Length | EA |
| MS35206-279 | Screw, Machine, Pan Head | EA |
| MS35206-280 | Screw, Machine, Pan Head | EA |
| MS35207-226 | Screw, Machine, Pan Head, Non-Structural, 6-40 Thread, 1/4" Length | EA |
| MS35207-245 | Screw, Machine, Pan Head, Non-Structural, 8-36 Thread, 1/2" Length | EA |
| MS35207-261 | Screw, Machine, Pan Head, Non-Structural, 10-32 Thread, 3/8" Length | EA |
| MS35207-262 | Screw, Machine, Pan Head, Non-Structural, 10-32 Thread, 7/16" Length | EA |
| MS35207-263 | Screw, Machine, Pan Head, Non-Structural, 10-32 Thread, 1/2" Length | EA |
| MS35207-264 | Screw, Machine, Pan Head, Non-Structural, 10-32 Thread, 5/8" Length | EA |
| MS35207-266 | Screw, Machine, Pan Head, Non-Structural, 10-32 Thread, 7/8" Length | EA |
| MS35207-267 | Screw, Machine, Pan Head, Non-Structural, 10-32 Thread, 1" Length | EA |
| MS35207-268 | Screw, Machine, Pan Head, Non-Structural, 10-32 Thread, 1-1/4" Length | EA |
| MS35207-269 | Screw, Machine, Pan Head, Non-Structural, 10-32 Thread, 1-1/2" Length | EA |
| MS35207-272 | Screw, Machine, Pan Head, Non-Structural, 10-32 Thread, 2-1/4" Length | EA |
| MS35207-283 | Screw, Machine, Pan Head, Non-Structural, 1/4-28 Thread, 1" Length | EA |
| MS35214-14 | Screw, Pan Head, Black Brass Instrument, 4-40, 3/8" | EA |
| MS35214-16 | Screw, Pan Head, Black Brass Instrument, 4-40 Thread, 1/2" Length | EA |
| MS35214-25 | Screw, Pan Head, Black Brass Instrument, 6-32 Thread, 3/8" Length | EA |
| MS35214-26 | Screw, Pan Head, Black Brass Instrument, 6-32, 7/16" | EA |
| MS35214-27 | Screw, Pan Head, Black Brass Instrument, 6-32, 1/2" | EA |
| MS35214-28 | Screw, Pan Head, Black Brass Instrument, 6-32, 5/8" | EA |
| MS35214-29 | Screw, Pan Head, Black Brass Instrument, 6-32, 3/4" | EA |
| MS35214-30 | Screw, Pan Head, Black Brass Instrument, 6-32, 7/8" | EA |
| MS35214-31 | Screw, Pan Head, Black Brass Instrument, 6-32, 1" | EA |
| MS35214-32 | Screw, Pan Head, Black Brass Instrument, 6-32, 1-1/4" | EA |
| MS35214-42 | Screw, Pan Head, Black Brass Instrument, 8-32 Thread, 1/2" Length | EA |
| MS35214-59 | Screw, Pan Head, Black Brass Instrument, 10-32 Thread, 1" Length | EA |
| MS35215-56 | Screw, Pan Head, Black Brass Instrument, 10-32 Thread, 5/8" Length | EA |
| MS35219-73 | Screw | EA |
| MS35265-14 | Screw, Machine, Fillister head, Drilled, Slotted, Thread 4-40, Length 5/16" | EA |
| MS35265-31 | Screw, Machine, Fillister head, Drilled, Slotted, Thread 6-32, Length 5/8" | EA |
| MS35265-41 | Screw, Machine, Fillister head, Drilled, Slotted, Thread 8-32, Length 1/4" | EA |
| MS35265-43 | Screw, Machine, Fillister head, Drilled, Slotted, Thread 8-32, Length 3/8" | EA |
| MS35265-44 | Screw, Machine, Fillister head, Drilled, Slotted, Thread 8-32, Length 7/16" | EA |
| MS35265-63 | Screw, Machine, Fillister head, Drilled, Slotted, Thread 10-24, Length 1/2" | EA |
| MS35265-80 | Screw, Machine, Fillister head, Drilled, Slotted | EA |
| MS35266-67 | Screw, Machine, Fillister head, Drilled, Slotted, Thread 10-32, Length 1" | EA |
| MS35266-73 | Screw, Machine, Fillister Head, Drilled, Slotted, Oil Cooler Attach, 0.190-32 X 2.50 | EA |
| MS35266-77 | Screw, Machine, Fillister head, Drilled, Slotted | EA |
| MS35266-87 | Screw, Machine, Fillister head, Drilled, Slotted | EA |
| MS35333-36 | Lockwasher, Internal Tooth, To Fit DIA #4, Carbon Steel | EA |
| MS35333-37 | Washer, Internal Star, AN936A6 | EA |
| MS35333-37 | Washer, Internal Star, AN936A6 | EA |
| MS35333-38 | Lockwasher, Internal Tooth, To Fit DIA #8, Carbon Steel | EA |
| MS35333-39 | Lockwasher, Internal Tooth, To Fit DIA #10, Carbon Steel | EA |
| MS35333-42 | Lockwasher, Internal Tooth, To Fit DIA 3/8", Carbon Steel | EA |
| MS35333-43 | Lockwasher, Internal Tooth, To Fit DIA 7/16", Carbon Steel | EA |
| MS35333-44 | Lockwasher, Internal Tooth, To Fit DIA 1/4", Carbon Steel | EA |

| Part Number | Part Description | Unit of Measure |
|--------------|--|-----------------|
| MS35333-71 | Lockwasher, Internal Tooth, To Fit DIA #6, Corrosion Resistant | EA |
| MS35333-72 | Lockwasher, Internal Tooth, To Fit DIA #8, Corrosion Resistant | EA |
| MS35333-73 | Lockwasher, Internal Tooth, To Fit DIA #10, Corrosion Resistant | EA |
| MS35333-74 | Lockwasher, Internal Tooth, To Fit DIA 1/4", Corrosion Resistant | EA |
| MS35335-38 | Lockwasher, Internal Tooth, To Fit DIA #4, Carbon Steel | EA |
| MS35338-40 | Washer, Split, Carbon Steel | EA |
| MS35338-41 | Washer, Split, Carbon Steel | EA |
| MS35338-42 | Washer, Split, Carbon Steel | EA |
| MS35338-43 | Washer, Split, Carbon Steel | EA |
| MS35338-44 | Washer, Split, Carbon Steel | EA |
| MS35338-45 | Washer, Split, Carbon Steel | EA |
| MS35338-46 | Washer, Split, Carbon Steel | EA |
| MS35338-46 | Washer, Split, Carbon Steel | EA |
| MS35426-14 | Nut, Wing | EA |
| MS35489-10 | Grommet, 0.312" Inside DIA, 0.312" Side Groove, 1" Outside DIA | EA |
| MS35489-120 | Grommet, 3/4" Inside DIA, 3/8" Side Groove, 2" Outside DIA | EA |
| MS35489-121 | Grommet, 7/8" Inside DIA, 7/16" Side Groove, 2" Outside DIA | EA |
| MS35489-134 | Grommet, 0.188" Inside DIA, 0.188" Side Groove, 3/4" Outside DIA | EA |
| MS35489-14 | Grommet, 1/2" Inside DIA, 0.312" Side Groove, 1.062" Outside DIA | EA |
| MS35489-15 | Grommet, 1/2" Inside DIA, 1/4" Side Groove, 1-1/2" Outside DIA | EA |
| MS35489-17 | Grommet, 0.188" Inside DIA, 0.188" Side Groove, 0.438" Outside DIA | EA |
| MS35489-19 | Grommet, 0.688" Inside DIA, 0.375" Side Groove, 1.312" Outside DIA | EA |
| MS35489-2 | Grommet, 1/8" DIA, 0.188" Side Groove | EA |
| MS35489-2 | Grommet, 1/8" DIA, 0.188" Side Groove | EA |
| MS35489-21 | Grommet, 3/4" Inside DIA, 0.375" Side Groove, 1.812" Outside DIA | EA |
| MS35489-23 | Grommet, 1" Inside DIA, 0.438" Side Groove, 1-3/4" Outside DIA | EA |
| MS35489-24 | Grommet, 1" Inside DIA, 0.248" Side Groove, 2-1/4" Outside DIA | EA |
| MS35489-3 | Grommet, 1/8" Inside DIA, 1/4" Side Groove, 1-1/4" Outside DIA | EA |
| MS35489-31 | Grommet | EA |
| MS35489-33 | Grommet, 0.188" Inside DIA, 1/4" Side Groove, 0.438" Outside DIA | EA |
| MS35489-38 | Grommet | EA |
| MS35489-4 | Grommet, 0.188" Inside DIA, 0.188" Side Groove, 0.438" Outside DIA | EA |
| MS35489-46 | Grommet | EA |
| MS35489-49 | Grommet | EA |
| MS35489-5 | Grommet, 0.188" Inside DIA, 0.188" Side Groove, 0.875" Outside DIA | EA |
| MS35489-6 | Grommet, 1/4" Inside DIA, 0.188" Side Groove, 0.625" Outside DIA | EA |
| MS35489-7 | Grommet, 1/4" Inside DIA, 1/4" Side Groove, 1" Outside DIA | EA |
| MS35489-72 | Grommet | EA |
| MS35489-9 | Grommet, 0.312" Inside DIA, 0.312" Side Groove, 3/4" Outside DIA | EA |
| MS35489-9 | Grommet, 0.312" Inside DIA, 0.312" Side Groove, 3/4" Outside DIA | EA |
| MS35649-202 | Nut, Plain Hexagon, Coarse Thread, Steel, 10-24 Thread | EA |
| MS35649-2252 | Nut, Plain Hexagon, Coarse Thread, Steel, 1/4-20 Thread | EA |
| MS35649-2382 | Nut, Plain Hexagon, Coarse Thread | EA |
| MS35649-242 | Nut, Plain Hexagon, Coarse Thread, Steel, 4-40 Thread | EA |
| MS35649-262 | Nut, Plain Hexagon, Coarse Thread, Steel, 6-32 Thread | EA |
| MS35649-282 | Nut, Plain Hexagon, Coarse Thread, Carbon Steel CAD, 8-32 Thread | EA |
| MS35649-286B | Nut, Plain Hexagon, Coarse Thread, Brass Black Oxide, 8-32 Thread | EA |
| MS35675-12 | Pin | EA |
| MS35769-10 | Gasket, Copper 3/32" Thickness, 9/16" DIA | EA |
| MS35769-13 | Gasket, Copper 3/32" Thickness, 11/16" DIA | EA |
| MS35769-15 | Gasket, Copper 3/32" Thickness, 3/4" DIA | EA |
| MS35769-18 | Gasket, Copper 3/32" Thickness, 7/8" DIA | EA |
| MS35769-2 | Gasket, Copper 3/32" Thickness, 1/4" DIA | EA |

| Part Number | Part Description | Unit of Measure |
|---------------|--|-----------------|
| MS35769-20 | Gasket, Copper 3/32" Thickness, 15/16" DIA | EA |
| MS35769-21 | Gasket, Copper 3/32" Thickness, 1" DIA | EA |
| MS35769-26 | Gasket, Copper 3/32" Thickness, 1-1/8" DIA | EA |
| MS35769-31 | Gasket, Copper 3/32" Thickness, 1-1/4" DIA | EA |
| MS35769-35 | Gasket, Copper 3/32" Thickness, 1-3/8" DIA | EA |
| MS35769-39 | Gasket, Copper 3/32" Thickness | EA |
| MS35769-48 | Gasket, Copper 3/32" Thickness, 1-3/4" DIA | EA |
| MS35769-6 | Gasket, Copper 3/32" Thickness, 3/8" DIA | EA |
| MS35769-66 | Gasket, Copper 3/32" Thickness | EA |
| MS35769-8 | Gasket, Copper 3/32" Thickness | EA |
| MS5008-30 | Cone, 2-1/2" DIA | EA |
| MS51844-42 | Nicropress Sleeve, To Fit Cable DIA 1/16", Unplated Copper | EA |
| MS51844-43 | Nicropress Sleeve, To Fit Cable DIA 3/32", Unplated Copper | EA |
| MS51844-44 | Nicropress Sleeve, To Fit Cable DIA 1/8", Unplated Copper | EA |
| MS51844-45 | Nicropress Sleeve, To Fit Cable DIA 5/32", Unplated Copper | EA |
| MS51844-46 | Nicropress Sleeve | EA |
| MS51861-22 | Screw, Tapping, #6 DIA, 1/4" Length, Pan Head, Type A Point | EA |
| MS51861-24 | Screw, Tapping, #6 DIA, 3/8" Length, Pan Head, Type A Point | EA |
| MS51861-37 | Screw, Tapping, #8 DIA, 3/4" Length, Pan Head, Type A Point | EA |
| MS51959-13 | Screw - C/S SS 4.40 x 1/4 | EA |
| MS51959-15 | Screw - C/S SS 4.40 x 3/8 | EA |
| MS51959-17 | Screw - C/S SS 4.40 x 1/2 | EA |
| MS51959-34 | 6-32x1 Countersunk SS Screw | EA |
| MS51959-41 | Screw | EA |
| MS51959-43 | Screw | EA |
| MS51959-45 | Screw | EA |
| MS51959-46 | Screw | EA |
| MS51959-47 | Screw | EA |
| MS51959-48 | Screw | EA |
| MS51959-49 | Screw | EA |
| MS51959-50 | Screw - C/S SS 832 x 1 1/4 | EA |
| MS51959-51 | Screw - C/S SS 832 x 1 1/2 | EA |
| MS51959-53 | Screw - C/S SS 832 x 2in | EA |
| MS51960-66 | Screw, SS 1032 x 5/8 | EA |
| MS51960-67 | Screw, SS 1032 x 3/4 | EA |
| MS51960-69 | Screw, C/S SS 1032 x 1 | EA |
| MS90354U10-07 | Rivet Huck, Protruding Head, Blind Fastener, High Strength, Alloy Steel 112KSI | EA |
| MS90354U10-08 | Rivet Huck, Protruding Head, Blind Fastener, High Strength, Alloy Steel 112KSI | EA |
| MS9058-06 | Gasket, Plastic, 1/2" DIA | EA |
| MS9100-08 | Nut, 3/4" | EA |
| MS9102-01 | Bracket, SS Angle, 90 Degree | EA |
| MS9135-01 | Gasket, Base, 3-5/16" DIA | EA |
| MS9193-08 | Nipple, 3/4" | EA |
| MS9194-06 | Elbow, 90 Degree, SS, 1/2" | EA |
| MS9194-08 | Elbow, 90 Degree, SS, 3/4" | EA |
| MS9385-10 | O Ring, 5/8" DIA | EA |
| MS9385-12 | O Ring, 3/4" DIA | EA |
| MS9518-13 | Bolt, 1/8-44 Thread, 1/4" Grip | EA |
| MS9575-05 | Bolt, 10-32 Thread, Drilled Shank | EA |
| MS9575-07 | Bolt, 1/4", Mach, Double Hex, Drilled | EA |
| MS9600-054 | Bracket, SS Angle, 90 Degree, "L" Shape | EA |

| Part Number | Part Description | Unit of Measure |
|---------------|--|-----------------|
| N5000-100H | Snap Rings, Retaining Ring, 1" DIA | EA |
| N5000-118H | Snap Rings, Retaining Ring, 1-1/8" DIA | EA |
| N5000-250 | Snap Ring (10D3606-9) | EA |
| NAS1022A8 | Nut | EA |
| NAS1103-2 | Bolt | EA |
| NAS1105-10 | Bolt, 12 Point Externa; Wrenching, 0.3125-24 Thread, 1.697" Length, 1-1/4" Grip, 180,000 PSI | EA |
| NAS1108-56D | Bolt (ok to use NAS6208-56D as alternate) | EA |
| NAS1149C0332R | Washer, Airframe, Corrosion Resistant, To Fit DIA #10", Light Thickness | EA |
| NAS1149C0432R | Washer, Airframe, Corrosion Resistant, To Fit DIA 1/4", Light Thickness | EA |
| NAS1149C0463R | Washer, Airframe, Corrosion Resistant, To Fit DIA 1/4", Standard Thickness | EA |
| NAS1149C0532R | Washer, Airframe, Corrosion Resistant, To Fit DIA 5/16", Light Thickness | EA |
| NAS1149C0563R | Washer, Airframe, Corrosion Resistant, To Fit DIA 5/16", Standard Thickness | EA |
| NAS1149C0663R | Washer, Airframe, Corrosion Resistant, To Fit DIA 3/8", Standard Thickness | EA |
| NAS1149C0732R | Washer, Airframe, Corrosion Resistant, To Fit DIA 7/16", Light Thickness | EA |
| NAS1149C0763R | Washer, Airframe, Corrosion Resistant, To Fit DIA 7/16", Standard Thickness | EA |
| NAS1149C0832R | Washer, Airframe, Corrosion Resistant, To Fit DIA 1/2", Light Thickness | EA |
| NAS1149C0832R | Washer, Airframe, Corrosion Resistant, To Fit DIA 1/2", Light Thickness | EA |
| NAS1149C0863R | Washer, Airframe, Corrosion Resistant, To Fit DIA 1/2", Standard Thickness | EA |
| NAS1149C0932R | Washer, Airframe, Corrosion Resistant, To Fit DIA 9/16", Light Thickness | EA |
| NAS1149C0963R | Washer, Airframe, Corrosion Resistant, To Fit DIA 9/16", Standard Thickness | EA |
| NAS1149C0963R | Washer, Airframe, Corrosion Resistant, To Fit DIA 9/16", Standard Thickness | EA |
| NAS1149C1032R | Washer, Airframe, Corrosion Resistant, To Fit DIA 5/8", Light Thickness | EA |
| NAS1149C1063R | Washer | EA |
| NAS1149C1290R | Washer, Airframe, Carbon Steel, 3/4" DIA | EA |
| NAS1149CN632R | Washer, Airframe, Corrosion Resistant, To Fit DIA #6", Standard Thickness | EA |
| NAS1149CN832R | Washer, Airframe, Corrosion Resistant, To Fit DIA #8", Standard Thickness | EA |
| NAS1149D0316H | Washer, Airframe, Aluminum, To Fit DIA #10, Natural Finish, Light Thickness | EA |
| NAS1149D0316J | Washer, Aluminum, Supersedes AN960JD10LL | EA |
| NAS1149D0316J | Washer, Aluminum, Supersedes AN960JD10LL | EA |
| NAS1149D0363J | WASHER FLAT ALUM. CHEM. FINISH, SCREW SIZE #10 OD.438 ID.203 THK.063 CHEM. FINISH | EA |

| Part Number | Part Description | Unit of Measure |
|---------------|--|-----------------|
| NAS1149D0363J | WASHER FLAT ALUM. CHEM. FINISH, SCREW SIZE #10 OD.438 ID.203 THK.063 CHEM. FINISH | EA |
| NAS1149D0363K | Washer, Airframe, Aluminum, To Fit DIA #10, Anodized per MIL-A-8625, Standard Thickness | EA |
| NAS1149D0416J | Washer, Aluminum, Supersedes AN960PD416L, AN960JD416L | EA |
| NAS1149D0416J | Washer, Aluminum, Supersedes AN960PD416L, AN960JD416L | EA |
| NAS1149D0463J | Washer, Aluminum, Supersedes AN960PD416, AN960JD416 | EA |
| NAS1149D0463J | Washer, Aluminum, Supersedes AN960PD416, AN960JD416 | EA |
| NAS1149D0516J | Washer, Airframe, Aluminum, To Fit DIA 5/16", Anodized Finish, Light Thickness | EA |
| NAS1149D0563J | WASHER FLAT ALUM. CHEM. FINISH, SCREW SIZE 5/16 OD.562 ID.328 THK.063 ALUM. CHEM. FINISH | EA |
| NAS1149D0563J | WASHER FLAT ALUM. CHEM. FINISH, SCREW SIZE 5/16 OD.562 ID.328 THK.063 ALUM. CHEM. FINISH | EA |
| NAS1149D0616J | Washer, Aluminum, Supersedes AN960D616L | EA |
| NAS1149D0616J | Washer, Aluminum, Supersedes AN960D616L | EA |
| NAS1149D0663J | WASHER FLAT ALUM. CHEM. FINISH, SCREW SIZE 3/8 OD.625 ID.390 THK.063 ALUM. CHEM. FINISH | EA |
| NAS1149D0663J | WASHER FLAT ALUM. CHEM. FINISH, SCREW SIZE 3/8 OD.625 ID.390 THK.063 ALUM. CHEM. FINISH | EA |
| NAS1149D0716J | Washer, Airframe, Aluminum, To Fit DIA 7/16", Anodized Finish, Light Thickness | EA |
| NAS1149D0763H | Washer, Airframe, Aluminum, To Fit DIA 7/16", Natural Finish, Standard Thickness | EA |
| NAS1149D0763J | Washer, Airframe, Aluminum, To Fit DIA 7/16", Anodized Finish, Standard Thickness | EA |
| NAS1149D0816J | Washer, Airframe, Aluminum, To Fit DIA 1/2", Anodized Finish, Light Thickness | EA |
| NAS1149D0863J | Washer, Airframe, Aluminum, To Fit DIA 1/2", Anodized Finish, Standard Thickness | EA |
| NAS1149D0916J | Washer, Airframe, Aluminum, To Fit DIA 9/16", Anodized Finish, Light Thickness | EA |
| NAS1149D0963J | Washer, Airframe, Aluminum, To Fit DIA 9/16", Anodized Finish, Standard Thickness | EA |
| NAS1149D1016J | Washer, Airframe, Aluminum, To Fit DIA 5/8", Anodized Finish, Light Thickness | EA |
| NAS1149D1063J | Washer, Airframe, Aluminum, To Fit DIA 5/8", Anodized Finish, Standard Thickness | EA |
| NAS1149D1216J | Washer, Airframe, Aluminum, To Fit DIA 3/4", Anodized Finish, Light Thickness | EA |
| NAS1149D1290J | Washer, Airframe, Aluminum, To Fit DIA 3/4", Anodized Finish, Standard Thickness | EA |
| NAS1149D1416J | Washer, Airframe, Aluminum, To Fit DIA 1/4", Anodized Finish, Standard Thickness | EA |
| NAS1149D1490J | Washer, Airframe, Aluminum, To Fit DIA 1/4", Anodized Finish, Light Thickness | EA |
| NAS1149D1616K | Washer, Airframe, Aluminum, To Fit DIA 3/8", Anodized per MIL-A-8625, Light Thickness | EA |
| NAS1149DN332J | Washer, Airframe, Aluminum, To Fit DIA #3, Anodized Finish, Standard Thickness | EA |
| NAS1149DN616J | Washer, Airframe, Aluminum, To Fit DIA #6, Anodized Finish, Light Thickness | EA |

| Part Number | Part Description | Unit of Measure |
|---------------|--|-----------------|
| NAS1149DN632J | Washer, Airframe, Aluminum, To Fit DIA #6, Anodized Finish, Standard Thickness | EA |
| NAS1149DN816H | Washer, Airframe, Aluminum, To Fit DIA #8, Anodized Finish, Light Thickness | EA |
| NAS1149DN832J | WASHER FLAT ALUM.CHEM. FINISH, SCREW SIZE #8 OD.375 ID.174 THK.032 | EA |
| NAS1149DN832J | WASHER FLAT ALUM.CHEM. FINISH, SCREW SIZE #8 OD.375 ID.174 THK.032 | EA |
| NAS1149F0332P | WASHER FLAT STL. CAD. 2, SCREW SIZE #10 OD.438 ID.203 THK.032 STEEL CAD 2 | EA |
| NAS1149F0332P | WASHER FLAT STL. CAD. 2, SCREW SIZE #10 OD.438 ID.203 THK.032 STEEL CAD 2 | EA |
| NAS1149F0363P | Washer, Aluminum, Supersedes AN960-10 | EA |
| NAS1149F0363P | Washer, Aluminum, Supersedes AN960-10 | EA |
| NAS1149F0363P | Washer, Aluminum, Supersedes AN960-10 | EA |
| NAS1149F0432P | Washer, Airframe, Carbon Steel, To Fit DIA 1/4", Light Thickness | EA |
| NAS1149F0463P | WASHER FLAT STL. CAD. 2, SCREW SIZE 1/4 OD.500 ID.265 THK.063 STEEL CAD 2 | EA |
| NAS1149F0463P | WASHER FLAT STL. CAD. 2, SCREW SIZE 1/4 OD.500 ID.265 THK.063 STEEL CAD 2 | EA |
| NAS1149F0532P | Washer, Airframe, Carbon Steel, To Fit DIA 5/16", Light Thickness | EA |
| NAS1149F0563P | Washer, Airframe, Carbon Steel, To Fit DIA 5/16", Standard Thickness | EA |
| NAS1149F0632P | Washer, Airframe, Carbon Steel, To Fit DIA 3/8", Light Thickness | EA |
| NAS1149F0663P | Washer, Airframe, Carbon Steel, To Fit DIA 3/8", Standard Thickness | EA |
| NAS1149F0732P | Washer, Airframe, Carbon Steel, To Fit DIA 7/16", Light Thickness | EA |
| NAS1149F0763P | Washer, Airframe, Carbon Steel, To Fit DIA 7/16", Standard Thickness | EA |
| NAS1149F0832P | Washer, Airframe, Carbon Steel, To Fit DIA 1/2", Light Thickness | EA |
| NAS1149F0832P | Washer, Airframe, Carbon Steel, To Fit DIA 1/2", Light Thickness | EA |
| NAS1149F0863P | Washer, Airframe, Carbon Steel, To Fit DIA 1/2", Standard Thickness | EA |
| NAS1149F0863P | Washer, Airframe, Carbon Steel, To Fit DIA 1/2", Standard Thickness | EA |
| NAS1149F0932P | Washer, Airframe, Carbon Steel, To Fit DIA 9/16", Light Thickness | EA |
| NAS1149F0963P | Washer, Airframe, Carbon Steel, To Fit DIA 9/16", Standard Thickness | EA |
| NAS1149F0963P | Washer, Airframe, Carbon Steel, To Fit DIA 9/16", Standard Thickness | EA |
| NAS1149F1032P | Washer, Airframe, Carbon Steel, To Fit DIA 5/8", Light Thickness | EA |
| NAS1149F1032P | Washer, Airframe, Carbon Steel, To Fit DIA 5/8", Light Thickness | EA |
| NAS1149F1063P | Washer, Airframe, Carbon Steel, To Fit DIA 5/8", Standard Thickness | EA |
| NAS1149F1232P | Washer, Airframe, Carbon Steel, To Fit DIA 3/4", Light Thickness | EA |
| NAS1149F1290P | Washer, Airframe, Carbon Steel, To Fit DIA 3/4", Standard Thickness | EA |
| NAS1149F1432P | Washer, Airframe, Carbon Steel, To Fit DIA 7/8", Light Thickness | EA |
| NAS1149F1490P | Washer, Airframe, Carbon Steel, To Fit DIA 7/8", Standard Thickness | EA |
| NAS1149FN232P | Washer, Airframe, Carbon Steel, To Fit DIA #2, Standard Thickness | EA |
| NAS1149FN332P | Washer, Airframe, Carbon Steel, To Fit DIA #3, Standard Thickness | EA |
| NAS1149FN432P | Washer, Airframe, Carbon Steel, To Fit DIA #4, Standard Thickness | EA |
| NAS1149FN542P | Washer, Airframe, Carbon Steel, To Fit DIA #5, Standard Thickness | EA |
| NAS1149FN616P | Washer, Airframe, Carbon Steel, To Fit DIA #6, Light Thickness | EA |
| NAS1149FN632P | Washer, Airframe, Carbon Steel, To Fit DIA #6, Standard Thickness | EA |

| Part Number | Part Description | Unit of Measure |
|---------------|---|-----------------|
| NAS1149FN816P | Washer, Airframe, Carbon Steel, To Fit DIA #8, Light Thickness | EA |
| NAS1149FN832P | Washer, Airframe, Carbon Steel, To Fit DIA #8, Standard Thickness | EA |
| NAS1306-10 | Bolt, Close Tolerance, 1.203" Length, 0.625" Grip | EA |
| NAS1308-26D | Bolt, High Strength, 1/2-20 Thread, Drilled Shank | EA |
| NAS1351C08H8 | Screw, Socket Head Cap, Drilled Head, Corrosion Resistant Steel, Thread 0.19-32 | EA |
| NAS1352-3-14 | Screw, Socket Head Cap, 8-32 Thread, 0.375" Length | EA |
| NAS1352-3-18P | Screw, Socket Head Cap | EA |
| NAS1352-3-8P | Screw, Socket Head Cap, 0.19-32 Thread, 1/2" Length | EA |
| NAS1352-4-16P | Screw, Socket Head Cap | EA |
| NAS1352-4-24 | Screw-Cap Skt HD | EA |
| NAS1352-4-36 | Screw, Socket Head Cap | EA |
| NAS1352-4-8P | Screw, Socket Head Cap | EA |
| NAS1423-4 | Nut, Drilled Jam, 1/4-28 Thread | EA |
| NAS1423-6 | Nut, Drilled Jam, 0.375-24 Thread | EA |
| NAS1435E2 | Strap, Eye 1/16" | EA |
| NAS1435E3 | Strap, Eye 3/16" | EA |
| NAS1435E4 | Strap, Eye 1/8" | EA |
| NAS1435E5 | Strap, Eye 5/32" | EA |
| NAS1435K2 | Strap, Fork End 1/18" | EA |
| NAS1435K3 | Strap, Fork End 3/32" | EA |
| NAS1435K4 | Strap, Fork End 1/8" | EA |
| NAS1435K5 | Strap, Fork End 5/32" | EA |
| NAS144-18 | Bolt, Internal Wrenching, Alloy Steel, Thread Size 1/4-28, Grip Length 18 | EA |
| NAS145R | Bolt, Internal Wrenching, 5/16-24 Thread | EA |
| NAS1473A3 | Nutplate, Capped, 10-32 Thread, Two Lug, Floating | EA |
| NAS1473A3 | Nutplate, Capped, 10-32 Thread, Two Lug, Floating | EA |
| NAS1474A3 | Nutplate, Capped, 10-32 Thread, Two Lug, Floating, w/Reduced Rivet Spacing | EA |
| NAS147-82 | Bolt, Internal Wrenching, 7/16-20 Thread, Grip 5-1/8", Undrilled Shank | EA |
| NAS147-84 | Bolt, Internal Wrenching, 7/16-20 Thread, Grip 5-1/4", Undrilled Shank | EA |
| NAS147-97 | Bolt, Internal Wrenching, 7/16-20 Thread, Grip 6-1/8", Drilled Shank | EA |
| NAS147-A26 | Bolt | EA |
| NAS148-28 | Bolt, Internal Wrenching, 1/2-20 Thread, Grip 1-3/4", Undrilled Shank | EA |
| NAS148A94 | Bolt, Internal Wrenching, 1/2-20 Thread, Grip 5-7/8", Drilled Shank | EA |
| NAS1669-3L4 | Bolt, Jo | EA |
| NAS1669-3L5 | Bolt, Jo, Protruding Head, 0.2 DIA, 0.282-0.344 Grip Range | EA |
| NAS1751-3L5 | Bolt, Jo, Protruding Head, 0.2" DIA | EA |
| NAS395-12 | Nut, Tinnerman, "U" Type, Screw Size #8, Length 0.53" | EA |
| NAS427K22 | Pin, Pulley Guard, 1.37" Length | EA |
| NAS427K23 | Pin, Pulley Guard, 1.44" Length | EA |
| NAS427K8 | Pin, Pulley Guard, 1/2" Length | EA |
| NAS428-3A10 | Bolt | EA |
| NAS428H4A12 | Bolt, Crowned Hexagon Head, Length 1-1/4", Adjusting | EA |
| NAS43DD3-12FC | Spacer | EA |
| NAS43DD3-14FC | Spacer, For Bolt DIA #8 or #10, Aluminum, 7/32" Length, Chemical Film | EA |
| NAS43DD3-16FC | Spacer, For Bolt DIA #8 or #10, Aluminum, 1/4" Length, Chemical Film | EA |

| Part Number | Part Description | Unit of Measure |
|---------------|---|-----------------|
| NAS43DD3-20FC | Spacer, For Bolt DIA #8 or #10, Aluminum, 5/16" Length, Chemical Film | EA |
| NAS43DD3-24FC | Spacer, For Bolt DIA #8 or #10, Aluminum, 3/8" Length, Chemical Film | EA |
| NAS43DD3-26N | Spacer, For Bolt DIA #8 or #10, Aluminum, 13/32" Length, Gray Anodize | EA |
| NAS43DD3-28FC | Spacer, For Bolt DIA #8 or #10, Aluminum, 7/16" Length, Chemical Film | EA |
| NAS43DD3-40FC | Spacer, For Bolt DIA #8 or #10, Aluminum, 5/8" Length, Chemical Film | EA |
| NAS43HT3-16 | Spacer, For Bolt DIA #8 or #10, Steel, 1/4" Length, CAD 2 Plated | EA |
| NAS43HT3-20 | Spacer, For Bolt DIA #8 or #10, Steel, 5/16" Length, CAD 2 Plated | EA |
| NAS43HT3-32 | Spacer, For Bolt DIA #8 or #10, Steel, 1/2" Length, CAD 2 Plated | EA |
| NAS43HT3-46 | Spacer, For Bolt DIA #8 or #10, Steel, 23/32" Length, CAD 2 Plated | EA |
| NAS43HT3-62 | Spacer, For Bolt DIA #8 or #10, Steel, 31/32" Length, CAD 2 Plated | EA |
| NAS43HT3-70 | Spacer, For Bolt DIA #8 or #10, Steel, 1-3/32" Length, CAD 2 Plated | EA |
| NAS43HT3-72 | Spacer, For Bolt DIA #8 or #10, Steel, 1-1/8" Length, CAD 2 Plated | EA |
| NAS43HT3-8 | Spacer, For Bolt DIA #8 or #10, Steel, 1/8" Length, CAD 2 Plated | EA |
| NAS43HT4-10 | Spacer, For Bolt DIA 1/4", Steel, 5/32" Length, CAD 2 Plated | EA |
| NAS43HT4-12 | Spacer, For Bolt DIA 1/4", Steel, 5/16" Length, CAD 2 Plated | EA |
| NAS43HT4-17 | Spacer, For Bolt DIA 1/4", Steel, 17/64" Length, CAD 2 Plated | EA |
| NAS43HT4-20 | Spacer, For Bolt DIA 1/4", Steel, 5/16" Length, CAD 2 Plated | EA |
| NAS43HT4-22 | Spacer, For Bolt DIA 1/4", Steel, 11/32" Length, CAD 2 Plated | EA |
| NAS43HT4-28 | Spacer, For Bolt DIA 1/4", Steel, 7/16" Length, CAD 2 Plated | EA |
| NAS43HT4-32 | Spacer, For Bolt DIA 1/4", Steel, 1/2" Length, CAD 2 Plated | EA |
| NAS43HT4-6 | Spacer, For Bolt DIA 1/4", Steel, 3/32" Length, CAD 2 Plated | EA |
| NAS43HT4-7 | Spacer, For Bolt DIA 1/4", Steel, 7/64" Length, CAD 2 Plated | EA |
| NAS43HT4-8 | Spacer, For Bolt DIA 1/4", Steel, 1/8" Length, CAD 2 Plated | EA |
| NAS464P3-6 | Bolt, Close Tolerance, Length 0.698", Grip 0.375" | EA |
| NAS464P3-9 | Bolt | EA |
| NAS50-125 | Snap Ring, Circlip | EA |
| NAS509-14 | Nut, Drilled Jam, 0.875-14 Thread | EA |
| NAS509-3 | Nut, Drilled Jam, 0.19-32 Thread | EA |
| NAS548P10-10 | Screw (was S1022Z10-10) | EA |
| NAS548P6-6 | Screw (was S1022Z6-6) | EA |
| NAS557-10A | Grommet | EA |
| NAS557-12A | Grommet | EA |
| NAS557-4A | Grommet | EA |
| NAS557-6A | Grommet | EA |
| NAS557-8A | Grommet | EA |
| NAS561-3-18 | Pin | EA |
| NAS561-3-8 | Pin | EA |
| NAS561P3-10 | Pin | EA |
| NAS561P3-6 | Pin | EA |
| NAS561P3-8 | Pin | EA |
| NAS561P4-12 | Roll Pin1/8X3/4 | EA |
| NAS561P4-14 | Pin | EA |
| NAS561P5-24 | Pin | EA |
| NAS561P6-18 | Pin | EA |
| NAS561P6-22 | Pin | EA |
| NAS561P6-24 | Pin, Door Handle | EA |
| NAS561P6-28 | Pin | EA |
| NAS561P8-40 | Pin | EA |

| Part Number | Part Description | Unit of Measure |
|-------------|--|-----------------|
| NAS600-4 | Screw, Machine, Pan Head, 4-40 Thread, 1/4" Length, Cruciform Recess, Fully Threaded, Alloy System | EA |
| NAS601-6 | Screw, Machine, Pan Head, 6-32 Thread, 0.375" Length, Cruciform Recess, Fully Threaded, Alloy System | EA |
| NAS617-4 | Packing, 0.072" Thickness, 1/4" Outside DIA | EA |
| NAS617-6 | Packing, 0.078" Thickness, 3/8" Outside DIA | EA |
| NAS6203-10 | Bolt, Close Tolerance, 0.19-32 Thread, 0.948" Length, 0.625" Grip | EA |
| NAS6203-11 | Bolt, Close Tolerance, 0.19-32 Thread, 1.011" Length, 0.688" Grip | EA |
| NAS6203-14 | Bolt, Close Tolerance, 0.19-32 Thread, 1.198" Length, 0.875" Grip | EA |
| NAS6203-20 | Bolt, Close Tolerance, 0.19-32 Thread, 1.573" Length, 1-1/4" Grip | EA |
| NAS6203-25 | Bolt, Close Tolerance, 0.19-32 Thread, 1.885" Length, 1.562" Grip | EA |
| NAS6203-4 | Bolt, Close Tolerance, 0.19-32 Thread, 0.573" Length, 1/4" Grip | EA |
| NAS6203-6D | Bolt, Close Tolerance, 0.19-32 Thread, 0.698" Length, 0.375" Grip, Drilled Shank | EA |
| NAS6203-7 | Bolt, Close Tolerance, 0.19-32 Thread, 0.761" Length, 0.438" Grip | EA |
| NAS6203-9 | Bolt, Close Tolerance, 0.19-32 Thread, 0.885" Length, 0.562" Grip | EA |
| NAS6203-9D | Bolt, Close Tolerance, 0.19-32 Thread, 0.885" Length, 0.562" Grip, Drilled Shank | EA |
| NAS6204-17 | Bolt, Close Tolerance, 1/4-28 Thread, 1.432" Length, 1.062" Grip | EA |
| NAS6204-17 | Bolt, Close Tolerance, 1/4-28 Thread, 1.432" Length, 1.062" Grip | EA |
| NAS6204-19 | Bolt, Close Tolerance, 1/4-28 Thread, 1.558" Length, 1.188" Grip | EA |
| NAS6204-2 | Bolt, Close Tolerance, 1/4-28 Thread, 0.495" Length, 0.125" Grip | EA |
| NAS6204-20 | Bolt, Close Tolerance, 1/4-28 Thread, 1.62" Length, 1-1/4" Grip | EA |
| NAS6204-23D | Bolt, Close Tolerance, 1/4-28 Thread, 1.808" Length, 1.438" Grip, Drilled Shank | EA |
| NAS6204-7 | Bolt, Close Tolerance, 1/4-28 Thread, 0.808" Length, 0.438" Grip | EA |
| NAS6204-8 | Bolt, Close Tolerance, 1/4-28 Thread, 0.870" Length, 1/2" Grip | EA |
| NAS6205-42 | Bolt, Close Tolerance, 5/16-24 Thread, XX" Length, XX" Grip | EA |
| NAS6206-21 | Bolt, Close Tolerance, 3/8-24 Thread, 1.766" Length, 1.312" Grip | EA |
| NAS6206-25 | Bolt, Close Tolerance, 3/8-24 Thread, 2.016" Length, 1.562" Grip | EA |
| NAS6206-27 | Bolt, Close Tolerance, 3/8-24 Thread, 2.142" Length, 1.688" Grip | EA |
| NAS6206-31 | Bolt, Close Tolerance, 3/8-24 Thread, 2.392" Length, 1.938" Grip | EA |
| NAS6206-3H | Bolt | EA |
| NAS6206-60 | Bolt, Close Tolerance, 3/8-24 Thread, XX" Length, XX" Grip | EA |
| NAS6206-62 | Bolt, Close Tolerance, 3/8-24 Thread, XX" Length, XX" Grip | EA |
| NAS6208-25 | Bolt | EA |
| NAS6208-30 | Bolt | EA |
| NAS6208-31 | Bolt | EA |
| NAS6208-32D | Bolt | EA |
| NAS6208-36D | Bolt | EA |
| NAS6208-44 | Bolt | EA |
| NAS6208-50 | Bolt | EA |
| NAS6208-52 | Bolt | EA |
| NAS6208-52D | Bolt | EA |
| NAS6209-25 | Bolt | EA |
| NAS6209-29 | Bolt, (NAS1109-29) | EA |
| NAS6209-31 | Bolt | EA |
| NAS6209-38D | Bolt | EA |
| NAS6210-36D | Bolt | EA |
| NAS6210-52 | Bolt | EA |
| NAS624-80 | Bolt, 12 point, External Wrenching, 1/2" DIA | EA |
| NAS625-12 | Bolt, 12 Point External; Wrenching, 0.3125-24 Thread, 1.322" Length, 3/4" Grip, 180,000 PSI | EA |

| Part Number | Part Description | Unit of Measure |
|--------------|--|-----------------|
| NAS625-14 | Bolt, 12 Point Externa; Wrenching, 0.3125-24 Thread, 1.447" Length, 5/8" Grip, 180,000 PSI | EA |
| NAS625-16 | Bolt, 12 Point Externa; Wrenching, 0.3125-24 Thread, 1.572" Length, 1" Grip, 180,000 PSI | EA |
| NAS625-18 | Bolt, 12 Point Externa; Wrenching, 0.3125-24 Thread, 1.697" Length, 1-1/4" Grip, 180,000 PSI | EA |
| NAS6604-18 | Bolt, Close Tolerance, 1/4-28 Thread, 1.55" Length, 1.125" Grip | EA |
| NAS6604-8 | Bolt, Close Tolerance, 0.925" Length, 1/2" Grip, Non-Drilled Shank | EA |
| NAS6605-20 | Bolt, Close Tolerance, 5/16-24 Thread, 1.719" Length, 1-1/4" Grip, Undrilled | EA |
| NAS6605-28 | Bolt, Close Tolerance, 5/16-24 Thread, 2.219" Length, 1-3/4" Grip, Undrilled | EA |
| NAS6606-13 | Bolt, Close Tolerance, 3/8-24 Thread, 1.39" Length, 0.812" Grip | EA |
| NAS6606-16 | Bolt, Close Tolerance, 3/8-24 Thread, 1.578" Length, 1" Grip | EA |
| NAS6606-22 | Bolt, Close Tolerance, 3/8-24 Thread, 1.953" Length, 1.375" Grip | EA |
| NAS6608D26 | Bolt | EA |
| NAS6609-40 | Bolt (can be used as alternate for NAS6209-40) | EA |
| NAS6610-94 | Bolt (use as alt for AN10-65A) | EA |
| NAS6612-48 | Bolt | EA |
| NAS679A06W | Nut, Self Locking, Low Height, 6-32 Thread, All Metal, Internal Wrenching Feature | EA |
| NAS679A08W | Nut, Self Locking, Low Height, 8-32 Thread, All Metal, Internal Wrenching Feature | EA |
| NAS679A3W | Nut, Self Lock, Steel | EA |
| NAS679A3W | Nut, Self Lock, Steel | EA |
| NAS679A4W | Nut, Self Locking, Low Height, 1/4-28 Thread, All Metal, Internal Wrenching Feature | EA |
| NAS679A5W | Nut, Self Locking, Low Height, 5/16-24 Thread, All Metal, Internal Wrenching Feature | EA |
| NAS679A6W | Nut, Self Locking, Low Height, 3/8-24 Thread, All Metal, Internal Wrenching Feature | EA |
| NAS75-3-008 | Bushing Plain, Press Flat, For Bolt Size #10, 1/4" Length, Alloy Steel Cad II Plated | EA |
| NAS75-5-010 | Bushing Plain, Press Flat, For 5/8" DIA Bolt, 5/16" Length, Alloy Steel Cad II Plated | EA |
| NAS77-5-034 | Bushing, 5/16" DIA, 0.34" Grip, Alloy Steel Cadmium Plated | EA |
| NW-10 | Washer, Nylon #10 (NAS1515H3L) | EA |
| NW-6 | Washer, Nylon #6 | EA |
| NW-8 | Washer, Nylon #8 (100/PKG) | EA |
| PD-100 | Plug, Plastic #10, Red | EA |
| PD-100 | Plug, Plastic #10, Red | EA |
| PFT-4A | Tube; 1/4" X .17" ID X 100' | FT |
| Place Holder | Place Holder for filler Material Req. | EA |
| PLT1M-M | Cable Tie, Nylon, Small, White | EA |
| PLT1M-M0 | Cable Tie, Nylon, Small, Black | EA |
| PLT2S-M | Cable Tie, Nylon, Medium, White | EA |
| PLT2S-M0 | Cable Tie, Nylon, Medium, Black, (1000/pkg) | EA |
| PLT3S-M | Cable Tie, Nylon, Large, White | EA |
| PLT3S-M0 | Cable Tie, Nylon, Large, Black, (1000/pkg) | EA |
| PRP909-8 | O Ring 2-1/2" DIA, Hartzel Prop | EA |
| RA105-00200 | Rivets, Brake Pad, 1/8" DIA | EA |
| RJ0115-000 | Gasket, 2-3/8" DIA | EA |
| RL33SB9 | Rosan Inserts, Lock Ring | EA |
| RM598 | Plate, Phenolic Canvas 1.00in X 24.00in X 24.00in | SF |
| RM598 | Plate, Phenolic Canvas 1.00in X 24.00in X 24.00in | SF |

| Part Number | Part Description | Unit of Measure |
|-------------------|--|-----------------|
| RTV108-3OZ-CLEAR | Silicone, GE, Clear, 3 oz | EA |
| RTV157 | Silicone Sealer, Gray, 2.8 Oz, GE | EA |
| RTV732-3 OZ CLEAR | Sealer, Multi Purpose, Clear, 3 oz | EA |
| RTV732-3 OZ WHITE | Sealer, Multi Purpose, White, 3 oz | EA |
| RTV732-3OZ-BLACK | Sealer, Multi Purpose, Black, 3 oz | EA |
| S1003-29A | Bearing Stabilizer Hinge, 3/8" DIA | EA |
| S1003-65A | Bearing, Spacer | EA |
| S1004-15B | Bearing, Flap3/8" DIA | EA |
| S1004-42A | Bearing Fin, 3/8" DIA | EA |
| S1021A10-10 | Screw, (10 X 5/8 TR PHIL A STL SMS) | EA |
| S1021A10-6 | Screw, (10 X 3/8 TR PHIL A STL SMS) | EA |
| S1021A10-8 | Screw, (10 X 1/2 TR PHIL A STL SMS) | EA |
| S1021A4-12 | Screw, (4 X 3/4 TR PHIL A STL SMS) | EA |
| S1021A4-16 | Screw, (4 X 1 TR PHIL A STL SMS) | EA |
| S1021A4-4 | Screw, (4 X 1/4 TR PHIL A STL SMS) | EA |
| S1021A4-8 | Screw, (4 X 1/2 TR PHIL A STL SMS) | EA |
| S1021A6-10 | Screw, (6 X 5/8 TR PHIL A STL SMS) | EA |
| S1021A6-12 | Screw, (6X3/4 TR PHIL A STL SMS) | EA |
| S1021A6-4 | Screw, (6X1/4 TR PHIL A STL SMS) | EA |
| S1021A6-6 | Screw, (6X3/8 TR PHIL A STL SMS) | EA |
| S1021A6-8 | Screw, (6X1/2 TR PHIL A STL SMS) | EA |
| S1021A8-10 | Screw, (8X5/8 TR PHIL A STL SMS) | EA |
| S1021A8-6 | Screw, (8X3/8 TR PHIL A STL SMS) | EA |
| S1021A8-8 | Screw, (8X1/2 TR PHIL A STL SMS) | EA |
| S1021Z10-10 | Screw, (10X5/8 TR PHIL B STL SMS) | EA |
| S1021Z4-4 | Screw, (4X1/4 TR PHIL B STL SMS) | EA |
| S1021Z4-6 | Screw, (4X3/8 TR PHIL B STL SMS) | EA |
| S1021Z4-8 | Screw, (4X1/2 TR PHIL B STL SMS) | EA |
| S1021Z6-10 | Screw, (6X5/8 TR PHIL B STL SMS) | EA |
| S1021Z6-4 | Screw, (6X1/4 TR PHIL B STL SMS) | EA |
| S1021Z8-12 | Screw, (8X3/4 TR PHIL B STL SMS) | EA |
| S1021Z8-20 | Screw, (8X1-1/4 TR PHIL B STL SMS) | EA |
| S1021Z8-24 | Screw, (8X2 TR PHIL B STL SMS) | EA |
| S1021Z8-7 | Screw | EA |
| S1022Z4-4 | Screw, (NAS548P4-4) | EA |
| S1022Z6-12 | Screw, (NAS548P6-12) | EA |
| S1022Z6-8 | Screw, (NAS548P6-8) | EA |
| S1022Z8-10 | Screw, (NAS548P8-10) | EA |
| S1023A6-8 | Screw | EA |
| S1026BG100 | Kit, Clamp | EA |
| S1090-9 | Body, 3/4-16 | EA |
| S1093-2 | Plug, Button, For 3/16" DIA Holes | EA |
| S1095-2 | Shield, 1/4" DIA Arch | EA |
| S1095-3 | Shield, 1/2" DIA Arch | EA |
| S1095-4 | Shield, 5/8" DIA Arch | EA |
| S1095-5 | Shield, 3/4" DIA Arch | EA |
| S1095-6 | Shield, 7/8" DIA Arch | EA |
| S1110ET19.50 | Duct, 19.5" Length | EA |
| S1110ET25.00 | Duct, 25" Length (now part S1110ET27.00) | EA |

| Part Number | Part Description | Unit of Measure |
|----------------|--|-----------------|
| S1110ET38.00 | Duct, 30" Length | EA |
| S1115-15 | Stud | EA |
| S1115-42 | Stud | EA |
| S1115-43 | Stud | EA |
| S1188-1 | Latch, Cowl Door | EA |
| S1234-11 | Control | EA |
| S133-6P58 | Spacer, 3/8" DIA | EA |
| S1362-12 | Handle Assembly | EA |
| S1362-21 | Strap, Door Assembly | EA |
| S1371-6 | Jackscrew, 8-32 Thread | EA |
| S1378-2-84.00 | Seal, Strip, Black Rubber, Dark Grey, 3/4 | EA |
| S1426-2 | Pin, Hinge, 1/8" DIA | EA |
| S1438-24 | Washer, Plastic White, 5/8" DIA | EA |
| S1443-3 | Doubler Assembly | EA |
| S1450-23H16095 | Washer, 3/8" DIA | EA |
| S1450-31N4-190 | Washer, 1/8" DIA, 1/8" Thick | EA |
| S1450-3-8-032 | Washer, 1/8" DIA, Thin | EA |
| S1450-3A10-080 | Washer, 1/8" DIA, Thick | EA |
| S1450-4-12-064 | Washer, 1/4" DIA | EA |
| S1450-4H12-050 | Washer, 1/4" DIA, CAD II Plating | EA |
| S1483-2 | Handle, LH | EA |
| S1494-8 | Clamp | EA |
| S1497-6 | Fitting | EA |
| S1581-4 | Rod End, 3/16" DIA Bore | EA |
| S1587-1 | Knob, White Plastic | EA |
| S1587-5 | Assy, Knob | EA |
| S1589-3 | Eyelet, 3/16" DIA | EA |
| S1628-012 | Ring, Packing, 3/8" DIA, Thick | EA |
| S1628-014 | Ring, Packing, 1/2" DIA, Thick | EA |
| S1628-111 | Ring, Packing, 3/8" DIA, Thin | EA |
| S1628-114 | Ring, Packing, 5/8" DIA | EA |
| S1628-135 | Ring, Packing, 1-3/4" DIA | EA |
| S1628-214 | Ring, Packing, 1" DIA | EA |
| S1628-225 | O Ring, 1-3/4" DIA | EA |
| S1628-329 | O Ring, 1-3/4" DIA | EA |
| S1629-1 | Filter 0250 | EA |
| S1721-16 | Line, Oxygen, Assembly | EA |
| S1723-5 | Line, Oxygen, Assembly | EA |
| S1732-1 | Filter, 2 X 20 Amp 100 VDC | EA |
| S1762-3 | Tray, Retainer | EA |
| S1771-1 | Knob, Black, Thin | EA |
| S1780-8 | Insert, Metal Disc, 2" DIA | EA |
| S1781-1 | Spacer, Tie Wrap, Mount | EA |
| S1793-1 | Tee, 3/16" DIA & 1/4" DIA Ends, CAD II Plating | EA |
| S1807-1 | Cover, White Plastic Cap | EA |
| S1820-4 | Rod End | EA |
| S1833-1 | Seal | EA |
| S1834-1 | Knob, White, 3/8" DIA | EA |
| S1843-2 | Bracket Holder, 1-1/4" X 5/8" Opening | EA |
| S1868B6 | Insert | EA |
| S1931-8 | Screw, Pan Head, 8-32 Thread, 1/2" Length | EA |
| S1950-4E | Screw Assembly, Interior, 5-40 Thread, 3/4" Length | EA |
| S1982-1 | Knob, Black, 10-32 Thread | EA |

| Part Number | Part Description | Unit of Measure |
|----------------|---|-----------------|
| S1997-6-10 | Bearing, 3/8" DIA, Internal Rollers | EA |
| S2010-3 | Bearing, Yoke, 10-32 Thread | EA |
| S2013-7 | Bearing, 1-3/8" DIA, Outside Surface Rollers | EA |
| S2014-8 | Race, 1-3/8" DIA | EA |
| S2024-1 | Catch | EA |
| S2122-1 | Nut, Curcuit Break, Black, 3/8-24 Thread | EA |
| S2122-2 | Nut, Curcuit Break, Silver, 3/8-24 Thread | EA |
| S2194-2 | Key Blank, SE, (Old A/C Style) | EA |
| S2194-3 | Key Cover, for P/N S2194-2 | EA |
| S2226-3 | Clamp, 3/16" | EA |
| S225-2 | Cover Plate, 5" DIA | EA |
| S225-4F | Plate, Cover | EA |
| S225-5 | Cover Plate, 5" DIA | EA |
| S226-2 | Doubler, Assembly, 4-3/4" DIA | EA |
| S2319-1 | Stud, Camlock | EA |
| S2319-10 | Stud, Camlock | EA |
| S2319-51 | Camlock, Receptacle, 244-16D | EA |
| S2319-63 | Grommet, Engine Cowl, 3/8" Inside DIA, 5/8" Outside DIA | EA |
| S2319-8 | Stud, Camlock | EA |
| S2319-9 | Stud, Camlock | EA |
| S2323-1 | Clamp, 8-32 Thread, 1/4" Grip | EA |
| S2323-13 | Clamp, 1/4-28 Thread, 1/4" Grip | EA |
| S2323-2 | Clamp, 10-32 Thread, 1/4" Grip | EA |
| S2351-1 | Clamp, kit | EA |
| S2357-2 | Clamp | EA |
| S2380-1 | Aeroduct | EA |
| S2385-1 | Washer, 3/8" DIA | EA |
| S2385-3 | Washer, 1/8" DIA | EA |
| S2416-1-31.0 | Belt, V | EA |
| S2418-1 | O Ring, Scraper Nose Gear, 2" DIA | EA |
| S2495-40-0304 | Hose Assembly, Cessna | EA |
| S2495-6-0620 | Hose Assembly, Cessna | EA |
| S2531-1-11 | Channel, Strip Nut | EA |
| S2559-4-1-1530 | Spacer, 1/4" DIA, 1-1/2" Length | EA |
| S2608-1 | Placard, Fuel, "AV Gas Only" | EA |
| S2629-1 | Bearing, 3/16" DIA Bore, PN3A | EA |
| S2642-3 | Corner, 45 Deg, Black Rubber | EA |
| S272-5 | Ball, Metal, Window Latch, 1/8" DIA | EA |
| S2889-3-0174 | Assy, Hose | EA |
| S2906-5-2 | Rivet | EA |
| S290D1032 | Washer, Structural, 3/16" DIA | EA |
| S3060-3H | Bearing | EA |
| S3134-47 | Ferrule, 3/4" DIA | EA |
| S3191-3 | Nut, 8-32 Thread | EA |
| S3231-1 | Nut, Clip, Tinnerman, 1/16" DIA, 5/16" Length | EA |
| S3275-102R | Stud, Camlock | EA |
| S3275-105R | Stud old 27S3-5 | EA |
| S3275-4S | Stud, Camlock | EA |
| S3275-5R | Stud, Camlock | EA |
| S3275-5W | Nut, Camlock | EA |
| S3275-6R | Stud, Camlock | EA |
| S338-4 | Fairlead, 1/4" DIA | EA |
| S339-1 | Clip, Black | EA |

| Part Number | Part Description | Unit of Measure |
|----------------|--|-----------------|
| S3413-104 | Stud, Camlock | EA |
| S3413-120 | Stud, Camlock | EA |
| S3429-2 | Nut Plate, 1/8" DIA, 1" Length | EA |
| S3429-2A | Nut Plate, 1/8" DIA, 1" Length | EA |
| S3431-3 | Nut Plate, 1/8" DIA, 1" Length | EA |
| S3484-6-20G1 | Screw, Instrument Grey, 1-1/4" Length, 8-32 Thread | EA |
| S3594-2 | Sender, RH | EA |
| S5A-225 | Spring, Dzus | EA |
| S8480 | Seal, Prop, 2-1/4" DIA | EA |
| SA01916CH-TEMP | Template Set (Vortex Generators) | EA |
| SK-184 | Reducer Do not buy | EA |
| SK208-123-2 | Support | EA |
| SK208-123B1 | Bracket | EA |
| SP4ZF6MOD | Clevis Pin | EA |
| SP4ZH7MOD | Clevis Pin SS (MS20392-5P19) | EA |
| SP4ZK11MOD | Clevis Pin, SS (MS20392-6P25) | EA |
| SP4ZM12MOD | Clevis Pin SS (MS20392-7P27) | EA |
| SP4ZP15MOD | Clevis Pin SS (MS20392-8P31) | EA |
| SP4ZR16MOD | Clevis Pin, Stainless Steel, DIA 1/8", Length 1-1/2" | EA |
| SP4ZU19MOD | Clevis Pin, Stainless Steel, DIA 1/8", Length 1-3/4" | EA |
| SP90C4 | Cotter Pin, SS | EA |
| SP90C5 | Clevis Cotter Pin | EA |
| SP90E7 | Cotter Pin, SS | EA |
| SP90G8 | Cotter Pin, SS | EA |
| SP90H16 | Cotter Pin, Stainless Steel, 1/8" DIA | EA |
| SPWRT 432 | Eye Bolt, 1/2 DIA, 3/4-16 Thread | EA |
| SPWRT 433 | Flange, 1/2-20 Thread | EA |
| SS FHA 4X1/2 | Screw | EA |
| SS FHA 4X5/8 | Screw | EA |
| SS TATP 10X1/2 | Screw | EA |
| SS TATP 10X3/8 | Screw | EA |
| SS TATP 10X5/8 | Screw | EA |
| SS TATP 6X1/2 | Screw | EA |
| SS TATP 6X3/8 | Screw | EA |
| SS TATP 6X5/8 | Screw | EA |
| SS TATP 8X1/2 | Screw | EA |
| SS TATP 8X3/8 | Screw | EA |
| SS TATP 8X5/8 | Screw, Type A Truss Phillips #8 X 5/8" | EA |
| SS TATP 8X5/8 | Screw, Type A Truss Phillips #8 X 5/8" | EA |
| SS TBTP 8X1/2 | Screw | EA |
| ST2231-04 | Clamp, Cushion, 1/4" | EA |
| ST2231-05 | Clamp, Cushion, 5/16" | EA |
| ST62SH | Wiper, 5/8" DIA | EA |
| STD1410 | Nut, Exhaust, Lycomming, 1/4-28 Thread | EA |
| STD1411 | Nut, 1/4-28 Thread | EA |
| STD1925 | Screw, 10-32 Thread, 1/2" Length | EA |
| STD2044 | Nut, Exhaust 1/20 Self Locking, 10-32 Thread | EA |
| SW2AA37 | Spacer/Bezel | EA |
| T-1 | Marker Flag Cable Ties, 3/8 x 3/16 Tag | EA |
| T-10 | Cable Tie Mount #10 Screw On | EA |
| T-10 | Cable Tie Mount #10 Screw On | EA |
| T-1025 | Seal, P Style | EA |

| Part Number | Part Description | Unit of Measure |
|--------------|---|-----------------|
| T18L | Cable Tie, 18" | EA |
| T-2 | Marker Flag Cable Ties, 5/16 x 1 Tag | EA |
| T-3 | Cable Tie Mount 3/4" x 3/4", Adhesvie Mount | EA |
| T-4 | Cable Tie Base 1 1/8 x 1 1/8, Adhesvie Mount | EA |
| T-5 | Arrow Mount For Cable Ties up to 0.14 Wide | EA |
| T-6 | Cable Tie Bases 7/16 x 5/8 | EA |
| T-7 | Cable Tie Mount #6 Screw On | EA |
| T-8 | Cable Tie Mount #8 Screw On | EA |
| TA56 | Tape, Cowl Chafe Seal Cloth, 1" x 1/16" x 15' roll | FT |
| TM2S6-M | Cable Tie Mount, 1/8" DIA | EA |
| U2597 | Strainer Element, 1-5/8" DIA | EA |
| U635 | Strainer - Sediment | EA |
| VSF1015N12B | Seal | EA |
| W1283 | Gasket, Nav Light | EA |
| XH99608F1099 | Clip | EA |
| Z4302X | Barrel Nut | EA |
| AN10-30A | Bolt, 5/8-18 Thread, Steel Cad II Plated, No Hole Shank | EA |
| AN10-31A | Bolt, Airframe, 5/8-18 Thread, 2-5/16" Grip, 3-17/64" Length, Undrilled Shank | EA |
| AN10-31A | Bolt, Airframe, 5/8-18 Thread, 2-5/16" Grip, 3-17/64" Length, Undrilled Shank | EA |
| AN10-32A | Bolt, 5/8-18 Thread, 2-7/16" Grip, 3.391" Overall Length, Steel Cad II Plated, No Hole Shank | EA |
| AN10-47A | Bolt, 5/8-18 Thread, 4-1/16" Grip, 5.016" Overall Length, Steel Cad II Plated, No Hole Shank | EA |
| AN10-47A | Bolt, 5/8-18 Thread, 4-1/16" Grip, 5.016" Overall Length, Steel Cad II Plated, No Hole Shank | EA |
| AN10-65A | Bolt, Airframe, 5/8-18 Thread, 5-13/16" Grip, 6-49/64" Length, Undrilled Shank | EA |
| AN28-30A | Bolt, Clevis | EA |
| AN28-34A | Bolt | EA |
| AN44-12A | Bolt Eye, 15/16-24 Thread, 1/4" Bolt Size, 13/16" Grip, 1-11/32" Length, Undrilled | EA |
| AN4-81A | Bolt Can use AN4-81 | EA |
| AN6C34A | Bolt, Airframe, Corrosion Ressistant, 3/8-24 Thread, 2-15/16" Grip, 3-37/64 Length, Undrilled Shank | EA |
| AN8-33A | Bolt, Airframe, 1/2-20 Thread, 2-11/16" Grip, 3-15/32" Length, Undrilled Shank | EA |
| MS16997-96 | Bolt | EA |
| MS20115-3 | Shackle | EA |
| MS20115-5 | Shackle | EA |
| MS20219-2 | Pulley, Cable Size 1/16 & 3/32, Max Load 480 lbs, Outside DIA 1-3/4", Inside DIA 1/4" | EA |
| MS20219-2 | Pulley, Cable Size 1/16 & 3/32, Max Load 480 lbs, Outside DIA 1-3/4", Inside DIA 1/4" | EA |
| MS24566-2B | Pulley, Control, Anti-Fristion Bearing, For Cable Sizes 1/16, 5/64, & 3/32 | EA |
| MS24694S145 | Screw, Flat Head (100 Deg), Structural Machine, Carbon Steel | EA |
| MS24694S145 | Screw, Flat Head (100 Deg), Structural Machine, Carbon Steel | EA |
| NAS6209-26 | Bolt (ok to use NAS1109-26) | EA |
| NAS6209-26 | Bolt (ok to use NAS1109-26) | EA |
| NAS6209-40 | Bolt | EA |
| NAS6209-42 | Bolt | EA |
| NAS6209-42 | Bolt | EA |
| NAS6210-54 | Bolt (alternate NAS1110-54) | EA |

| Part Number | Part Description | Unit of Measure |
|-------------|--|-----------------|
| NAS6605-17 | Bolt, Close Tolerance, 0.3125-24 Thread, Undrilled Shank, 1.531" Length, 1.062" Grip | EA |